

PROFESSIONAL
**COMMERCIAL
REFRIGERATION**
EQUIPMENTS



STAINLESS STEEL SERIES
(GASTRONORM STANDARD)

GN COUNTER

- ★ Stainless steel for both interior and exterior with round corner at the bottom for easy cleaning
- ★ 1 shelf per door & compatible for GN1/1 pan
- ★ Self-closing door
- ★ Replaceable magnetic door seal
- ★ Option of adjustable feet or casters
- ★ Option of GN1/3, GN2/3, GN1/2 drawers



GX-GN2100TN



GX-GN2200BT

Model	GX-GN2100TN	GX-GN2100BT	GX-GN2200TN	GX-GN2200BT
Dimension(W*D*H /mm)	1360*700*850	1360*700*850	1360*700*950	1360*700*950
Net Capacity(L)	282	282	282	282
Cooling System	Ventilated	Ventilated	Ventilated	Ventilated
Temperature(° C)	-2 ~ +8	-18 ~ -22	-2 ~ +8	-18 ~ -22
Compressor	Zanussi	Danfoss	Zanussi	Danfoss
Controller	Dixell	Dixell	Dixell	Dixell
Refrigerant	R134a	R404a	R134a	R404a
Climate Rating	38° C	32° C	38° C	32° C
Loading (40')	48	48	48	48
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz

GN COUNTER

- ★ Stainless steel for both interior and exterior with round corner at the bottom for easy cleaning
- ★ 1 shelf per door & compatible for GN1/1 pan
- ★ Self-closing door
- ★ Replaceable magnetic door seal
- ★ Option of adjustable feet or casters
- ★ Option of GN1/3, GN2/3, GN1/2 drawers


GX-GN3100TN

GX-GN3200BT

Model	GX-GN3100TN	GX-GN3100BT	GX-GN3200TN	GX-GN3200BT
Dimension(W*D*H /mm)	1795*700*850	1795*700*850	1795*700*950	1795*700*950
Net Capacity(L)	417	417	417	417
Cooling System	Ventilated	Ventilated	Ventilated	Ventilated
Temperature(° C)	-2 ~ +8	-18 ~ -22	-2 ~ +8	-18 ~ -22
Compressor	Zanussi	Danfoss	Zanussi	Danfoss
Controller	Dixell	Dixell	Dixell	Dixell
Refrigerant	R134a	R404a	R134a	R404a
Climate Rating	38° C	32° C	38° C	32° C
Loading (40')	38	38	38	38
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz

GN COUNTER

- ★ Stainless steel for both interior and exterior with round corner at the bottom for easy cleaning
- ★ 1 shelf per door & compatible for GN1/1 pan
- ★ Self-closing door
- ★ Replaceable magnetic door seal
- ★ Option of adjustable feet or casters
- ★ Option of GN1/3, GN2/3, GN1/2 drawers



GX-GN4100TN



GX-GN4200BT

Model	GX-GN4100TN	GX-GN4100BT	GX-GN4200TN	GX-GN4200BT
Dimension(W*D*H /mm)	2230*700*850	2230*700*850	2230*700*950	2230*700*950
Net Capacity(L)	553	553	553	553
Cooling System	Ventilated	Ventilated	Ventilated	Ventilated
Temperature(° C)	-2 ~ +8	-18 ~ -22	-2 ~ +8	-18 ~ -22
Compressor	Embraco	Danfoss	Embraco	Danfoss
Controller	Dixell	Dixell	Dixell	Dixell
Refrigerant	R134a	R404a	R134a	R404a
Climate Rating	32° C	32° C	32° C	32° C
Loading (40')	32	32	32	32
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz

GN COUNTER

- ★ Stainless steel for both interior and exterior with round corner at the bottom for easy cleaning
- ★ 1 shelf per door & compatible for GN1/1 pan
- ★ Self-closing door
- ★ Replaceable magnetic door seal
- ★ Option of adjustable feet or casters


GX-GN2100TNG

GX-GN3100TNG

GX-GN4100TNG

Model	GX-GN2100TNG	GX-GN3100TNG	GX-GN4100TNG
Dimension(W*D*H /mm)	1360*700*850	1795*700*850	2230*700*850
Net Capacity(L)	282	417	553
Cooling System	Ventilated	Ventilated	Ventilated
Temperature(° C)	-2 ~ +8	-2 ~ +8	-2 ~ +8
Compressor	Zanussi	Zanussi	Embraco
Controller	Dixell	Dixell	Dixell
Refrigerant	R134a	R134a	R134a
Climate Rating	32° C	32° C	32° C
Loading (40')	48	38	32
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz

SNACK COUNTER-600mm(D)

- ★ Stainless steel for both interior and exterior with round corner at the bottom for easy cleaning
- ★ 1 adjustable shelf per door
- ★ Self-closing door
- ★ Replaceable magnetic door seal
- ★ Option of adjustable feet or casters


GX-SNACK3100TN

GX-SNACK2100TN

GX-SNACK4100TN

Model	GX-SNACK2100TN	GX-SNACK3100TN	GX-SNACK4100TN
Dimension(W*D*H /mm)	1360*600*850	1795*600*850	2230*600*850
Net Capacity(L)	228	339	449
Cooling System	Ventilated	Ventilated	Ventilated
Temperature(° C)	-2 ~ +8	-2 ~ +8	-2 ~ +8
Compressor	Zanussi	Zanussi	Embraco
Controller	Dixell	Dixell	Dixell
Refrigerant	R134a	R134a	R134a
Climate Rating	32° C	32° C	32° C
Loading (40')	48	38	32
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz

Model	GX-SNACK2100BT	GX-SNACK3100BT	GX-SNACK4100BT
Dimension(W*D*H /mm)	1360*600*850	1795*600*850	2230*600*850
Net Capacity(L)	228	339	449
Cooling System	Ventilated	Ventilated	Ventilated
Temperature(° C)	-18 ~ -22	-18 ~ -22	-18 ~ -22
Compressor	Danfoss	Danfoss	Danfoss
Controller	Dixell	Dixell	Dixell
Refrigerant	R404a	R404a	R404a
Climate Rating	32° C	32° C	32° C
Loading (40')	48	38	32
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz

SNACK COUNTER-600mm(D)

- ★ Stainless steel for both interior and exterior with round corner at the bottom for easy cleaning
- ★ 1 adjustable shelf per door
- ★ Self-closing door
- ★ Replaceable magnetic door seal
- ★ Option of adjustable feet or casters



GX-SNACK3100TNG



GX-SNACK2100TNG



GX-SNACK4100TNG

Model	GX-SNACK2100TNG	GX-SNACK3100TNG	GX-SNACK4100TNG
Dimension(W*D*H /mm)	1360*600*850	1795*600*850	2230*600*850
Net Capacity(L)	228	339	449
Cooling System	Ventilated	Ventilated	Ventilated
Temperature(° C)	+2 ~ +8	+2 ~ +8	+2 ~ +8
Compressor	Zanussi	Zanussi	Embraco
Controller	Dixell	Dixell	Dixell
Refrigerant	R134a	R134a	R134a
Climate Rating	32° C	32° C	32° C
Loading (40')	48	38	32
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz

UNDERCOUNTER-650mm(H)

- ★ Stainless steel for both interior and exterior with round corner at the bottom for easy cleaning
- ★ 1 adjustable shelf per door
- ★ Self-closing door
- ★ Replaceable magnetic door seal
- ★ Option of adjustable feet or casters
- ★ Option of GN1/3 drawers



GX-U-GN3160TN



GX-U-GN4100TN

Model	GX-U-GN2100TN	GX-U-GN3100TN	GX-U-GN4100TN
Dimension(W*D*H /mm)	1360*700*650	1795*700*650	2230*700*650
Net Capacity(L)	214	317	420
Cooling System	Ventilated	Ventilated	Ventilated
Temperature(° C)	-2 ~ +8	-2 ~ +8	-2 ~ +8
Compressor	Zanussi	Zanussi	Embraco
Controller	Dixell	Dixell	Dixell
Refrigerant	R134a	R134a	R134a
Climate Rating	32° C	32° C	32° C
Loading (40')	72	54	48
Voltage/Frequency	220 ~ 240V/50Hz	220 ~ 240V/50Hz	220 ~ 240V/50Hz