

Main Characteristic:

- DC MMA welding machine
- HF ARC-starting, TIG welding lightly
- With function of Arc force adjustment
- LCD Digit show
- Be able to be equipped with water-cooling torch
- Be able to weld mid steel, stainless steel, copper and Titanor metal etc
- Be able to use all kind of welding rod, such as acid and basic rod arc

主要特徵:

- 直流手工弧焊功能
- 高頻弧焊，令氬焊操作輕鬆自如
- 手工電弧焊具有獨特電弧推力調節功能，方便實用
- LED數碼電流顯示，清晰直觀
- 可選用水冷功能及配置
- 可焊接碳鋼、不銹鋼、合金鋼、銅、鈦等多種金屬材料
- 可使用酸性、鹼性等各種類型的焊條



ARC WELDING WORKING CONSTRUCTION:

ARC安裝示意圖:



COMPLETED CARRY CASE ACCESSORIES INCLUDE:

手提焊機所有配件:

手弧焊電焊鉗	MMA ELECTRODE HOLDER
接地夾	EARTH CLAMP
電纜綫	WELDING CABLE
焊接引出插頭	WELDING CABLE JOINT

TECHNICAL SPECIFICATIONS

ARC WELDING MACHINE ARC 酷銳逆變直流手弧焊電焊機		Colo ARC400BT	Colo ARC500BT	Colo ARC630BT
AC Input Voltage	交流輸入電壓	AC.(Three phase) 220V~415V ± 15%		
Rated input power capacity	額定輸入電源容量	17kW	25kW	35kW
Input frequency	輸入電壓頻率	50/60Hz	50/60Hz	50/60Hz
No-load voltage	空載電壓	72V	72V	72V
Output current range	輸出電流調節範圍	40-400A	40-500A	40-630A
Rated output coltage	額定輸出電壓	36V	40V	44V
Duty cycle	負載持續率	60	60	60
No-load power	空載損耗	200W	200W	200W
Efficiency	效率	85%	85%	85%
Power factor	功率因數	0.93	0.93	0.93
Insulation class	絕緣等級	B	B	B
Gross weight	毛重	46Kg	49Kg	52Kg
Overall dimension	外形尺寸	620×350×640mm	620×350×640mm	620×350×640mm
Protection class of case	外殼防護等級	IP 21	IP 21	IP 21
Drive adjustment range	推力調節範圍	0-100	0-100	0-100
Electrode diameter	電焊條直徑	2.5-6mm	2.5-6mm	2.5-8mm