

Main Characteristic:

- HF Arc-starting,impulse control and strong welding permeability
- Be satisfied requirements of welding technological
- Be able to weld mild steel,stainless steel,copper and titanor metal etc
- Suit for fitting up stainless steel,patching kitchen equipment and moulder
- Adjustable impulse control,be able to weld automatically

主要特徵:

- 高頻引弧，脈衝控制，焊接滲透力強
- 焊接範圍寬，適合于各種工藝焊接要求
- 可焊接碳鋼、不銹鋼、合金鋼、銅、鈦及多種金屬材料
- 適用于不銹鋼安裝，廚房設備及工模具修補
- 脈衝可調控制，可用于自動焊



TIG WELDING WORKING CONSTRUCTION:

TIG 安裝示意圖:



COMPLETED CARRY CASE ACCESSORIES INCLUDE:

手提焊機所有配件:

氬弧焊電焊槍	TIG ELECTRODE HOLDER
接地夾	EARTH CLAMP
電纜綫	WELDING CABLE
焊接引出插頭	WELDING CABLE JOINT

TECHNICAL SPECIFICATIONS

TIG WELDING MACHINE TIG 酷銳逆變直流氬弧焊電焊機		Colo TIG220ET	Colo TIG250ET	Colo TIG315ET
AC Input Voltage	交流輸入電壓	AC.(single phase) 110V~240V±15%	AC.(three phase) 220V~415V±15%	
Rated input power capacity	額定輸入電源容量	5.5kW	7kW	8.5kW
No-load voltage	空載電壓	43V	43V	43V
Output current range	輸出電流調節範圍	20-220A	20-250A	20-315A
Rated output voltage	額定輸出電壓	20V	20V	20V
Duty cycle	負載持續率	60%	60%	60%
No-load power	空載損耗	40W	40W	40W
Efficiency	效率	85%	85%	85%
Power factor	功率因數	0.93	0.93	0.93
Arc-sarting	引弧方式	HF	HF	HF
Insulation class	絕緣等級	B	B	B
Gross weight	毛重	15.5Kg	16Kg	18.5Kg
Overall dimension	外形尺寸	432×205×355mm	432×205×355mm	530×205×380mm
Protection class of case	外殼防護等級	IP 21	IP 21	IP 21
Down-slope time	下降時間	—	—	—
Welding thickness	適合焊接板厚	2-8mm	3-10mm	3-10mm