



HORBO

swimming pool

AND SPA EQUIPMENT



EXCELLENT
PERFORMANCE



HIGH
TECHNOLOGY



EASY
MAINTENANCE

CONTENT

<u>WALL-MOUNTED FILTER</u>	1-10
<u>INGROUND FILTER</u>	11-23
<u>SAND FILTER SERIES</u>	24-31
<u>PUMP SERIES</u>	32-39
<u>UNDERWATER LIGHT SERIES</u>	40-48
<u>SPA SERIES</u>	49-57
<u>MACHINE ROOM EQUIPMENT</u>	58-68
<u>POOL SURROUNDING ACCESSORIES</u>	69-78
<u>LADDER SERIES</u>	79-82
<u>CLEANING EQUIPMENT</u>	83-87
<u>SAUNA SERIES</u>	88-100
<u>STEAM ROOM SERIES</u>	101-105
<u>LEISURE FURNITURE SERIES</u>	106-107
<u>SPA HOT TUB SERIES</u>	108-118



WALL-MOUNTED FILTER

Model : HPK8020
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Acrylic, so the filter is anti-acid anti-fading, and easy to clean. Integrated filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards



TECHNICAL CHARACTERISTICS



Dimensions	1110x670x780mm
Flow rate	10m ³ /h 15m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Acrylic
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x1HP	1x1.5HP
Filtration basket with bag	1pc	
Chlorine feeder	1pc	
Light (Warm white)	1xLED	12W/12V
Time controller	1pc	
Swim jet	2pcs	
Handle rail (S.S.)	2pcs	
Ozone (optional)	1pc	(options)

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc




WALL-MOUNTED FILTER

Model : HPK8025
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Acrylic, so the filter is anti-acid anti-fading, and easy to clean. Integrated filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.

- 1 Stainless-steel hand rail
- 2 Cable pipe
- 3 Transformer and terminal box
- 4 Sewage pipe
- 5 Cartridge filter
- 6 Sterilizer
- 7 Injector nozzle
- 8 Swimming pool lamp
- 9 Water inlet
- 10 Water outlet
- 11 Hoarding
- 12 Concrete
- 13 Poolside tile



TECHNICAL CHARACTERISTICS



Dimensions	1120x690x1100mm
Flow rate	25m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Acrylic
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x2HP	
Filtration basket with bag	1pc	
Chlorine feeder	1pc	
Light (Warm white)	1xLED	12W/12V
Time controller	1pc	
Swim jet	2pcs	
Handle rail (S.S.)	2pcs	
Ozone (optional)	1pc	(options)

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc





WALL-MOUNTED FILTER

Model : HPK8022
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of ABS , so the filter is anti-acid anti-fading, and easy to clean Integrated filter installation without room, simple installation convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.



TECHNICAL CHARACTERISTICS



Dimensions	1450x530x1060mm
Flow rate	25m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	ABS
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x2HP	
Filtration basket with bag	1pc	
Light (Warm white)	1xLED	12W/12V
Time controller	1pc	
Swim jet	2pcs	
Ozone (optional)	1pc	

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc





WALL-MOUNTED FILTER

Model : HPK8026
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Acrylic, so the filter is anti-acid anti-fading, and easy to clean. Integrated filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.



TECHNICAL CHARACTERISTICS



Dimensions	1150x710x1090mm
Flow rate	25m ³ /h 35m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Acrylic
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x2HP	1x3HP
Filtration basket with bag	1pc	2pcs
Chlorine Feeder	1pc	
Light (Warm white)	1xLED	12W / 12V
Time controller	1pc	
Swim jet	2pcs	
Handle rail (S.S)	2pcs	
Ozone (optional)	1pc	Options

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc





WALL-MOUNTED FILTER

Model : HPK8028
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Acrylic, so the filter is anti-acid anti-fading, and easy to clean. Integrated filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.



LEAF BASKET



SPRAY NOZZLE



CHLORINE FEEDER



INJECTOR NOZZLE



LED UNDERWATER LIGHT



FILTER BAG



TECHNICAL CHARACTERISTICS


Dimensions	1150x710x1090mm	
Flow rate	25m ³ /h 35m ³ /h	
Voltage	220V/50Hz or 60Hz	
Precision of filtration bag	$\leq 5\mu$	
Operating noise	$\leq 50\text{Db}$	
Material	Acrylic	
Installation	Wall mounted	

EQUIPMENT

Filtration Pump	1x2HP	1x3HP
Filtration basket with bag	1pc	2pcs
Chlorine Feeder	1pc	
Light (Warm white)	1xLED	12W / 12V
Time controller	1pc	
Swim jet	2pcs	
Handle rail (S.S)	2pcs	
Ozone (optional)	1pc	Options

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc






WALL-MOUNTED FILTER

Model : HPK8023
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Acrylic. The wall-mounted filter is change to traditional sand filter. Now the filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.



1	Filter shell	9	Make air controller on/off
2	Water injector	10	Air controller on/off
3	Control box	11	Spa jet
4	Drain valve	12	Pool light
5	Drain water pipe	13	Water filter
6	Water pump	14	Water inlet
7	Active connector	15	Pressure water purifier
8	Chlorinator feeder	16	Ozone disinfection



TECHNICAL CHARACTERISTICS



Dimensions	1050x550x860mm
Flow rate	10m³/h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Acrylic
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x1HP	
Filtration basket with bag	1pc	
Chlorine Feeder	1pc	
Light (Warm white)	1xLED	12W / 12V
Time controller	1pc	
Swim jet	2pcs	
Ozone (optional)	1pc	Options

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc






WALL-MOUNTED FILTER

Model : HPK8030
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Acrylic, so the filter is anti-acid anti-fading, and easy to clean. Integrated filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. It's big flow rate for 8pes filter bag.



TECHNICAL CHARACTERISTICS




Dimensions	1100x1200x1120mm
Flow rate	47m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Acrylic
Installation	Inground

EQUIPMENT

Filtration Pump	1x4HP	
Filtration basket with bag	8pc	
Chlorine Feeder	1pc	
Light (Warm white)	1xLED	12W / 12V
Time controller	1pc	
Swim jet	2pcs x 5"	

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc





WALL-MOUNTED FILTER

Model : HPK8021
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Polyethylene. The wall-mounted filter is change to traditional sand filter. Now the filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.



TECHNICAL CHARACTERISTICS



Dimensions	950x580x800mm
Flow rate	15m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Polyethylene
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x1.0 HP	
Filtration basket with bag	1pc	
Chlorine Feeder	1pc	
Light (Warm white)	1xLED	12W / 12V
Time controller	1pc	
Swim jet	2pcs	
Handle rail (S.S)	2pcs	
Ozone (optional)	1pc	Options

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc





WALL-MOUNTED FILTER

Model : HPK8029
(Children Swimming Pool)

The enclosure of wall-mounted filter is made of high quality Polyethylene. The wall-mounted filter is change to traditional sand filter. Now the filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.



TECHNICAL CHARACTERISTICS



Dimensions	1095x705x1230mm
Flow rate	25m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Polyethylene
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x2HP	
Filtration basket with bag	1pc	
Chlorine Feeder	1pc	
Light (Warm white)	1xLED	12W / 12V
Time controller	1pc	
Swim jet	2pcs	
Handle rail (S.S)	2pcs	
Ozone (optional)	1pc	Options

SYSTEM

Filtration system	1pc	
Disinfection system	1pc	
Time control system	1pc	
Circle system	1pc	
Lighting system	1pc	





WALL-MOUNTED FILTER

Model : HPK8032

The enclosure of wall-mounted filter is made of high quality Polyethylene. The wall-mounted filter is change to traditional sand filter. Now the filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. The filter is made according to Countries codes and standards.



TECHNICAL CHARACTERISTICS


Dimensions	1090x600x960mm
Flow rate	25m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Polyethylene
Installation	Wall mounted

EQUIPMENT

Filtration Pump	1x2HP	
Filtration basket with bag	1pc	
Light (Warm white)	1xLED	12W / 12V
Time controller	1pc	
Swim jet	2pcs	
Ozone (optional)	1pc	Options

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc
Lighting system	1pc



INGROUND FILTER





QUARTS SAND FILTER

Model : HPK8017

The enclosure of inground filter is made of high quality fiberglass and polyvinyl chloride, which is strong and durable, rust-proof, low temperature resistance and anti-uv light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; Easy to install, no need a special machine room.

Notes: Massage pump, salt chlorinator and automatic chlorine off-line feeder(Optional)



- a Connect backwater inlet Ø50
- b Connect vacuum suction Ø50
- c Connect skimmer Ø50
- d Connect the outlet of the massage pump Ø63
- e Connect the inlet of the massage pump Ø63
- f Connect the water outlet Ø50
- g Connect the sewage outlet Ø50

TECHNICAL CHARACTERISTICS

Power	1HP/220V	1.5HP/220V
Filter type	Sand filter Ø525mm / Ø625mm	
Flow rate	12m³/h	16m³/h
External Dimension	1400x1250x1020mm	
Disinfection	Sterilizer	
Water pump	120w/220v	
Salt chlorinator	16~42 g/h	Options
Massage pump	3HP/220V	Options
UV	65w/220v	Options
CCOREL.250		Options

- Complete filtration
- Complete circulation
- Dose sterilization
- Circulating water pump
- Massage pump
- Pressure relief valve
- Pressure display
- 6-multi-port valve
- Automatic doser
- Time controller
- Contactor





QUARTS SAND FILTER

Model : HPK8018

The enclosure of inground filter is made of high quality fiberglass and polyvinyl chloride, which is strong and durable, rust-proof, low temperature resistance and anti-uv light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; Easy to install, no need a special machine room.

Notes: Massage pump, salt chlorinator and automatic chlorine off-line feeder(Optional)



- a Connect backwater inlet Φ50
- b Connect vacuum suction Φ50
- c Connect skimmer Φ50
- d Connect the outlet of the massage pump Φ63
- e Connect the inlet of the massage pump Φ63
- f Connect the water outlet Φ50
- g Connect the sewage outlet Φ50

TECHNICAL CHARACTERISTICS

Power	2HP/220V	3HP/220V
Filter type	Sand filter Φ800mm / Φ900mm	
Flow rate	25m³/h	31m³/h
External Dimension	1730x1600x1280mm	
Disinfection	Sterilizer	
Water pump	120w/220v	
Salt chlorinator	16~42 g/h	Options
Massage pump	3HP/220V	Options
UV	85w/220v	Options
CCOREL.250	Options	

- Complete filtration
- Complete circulation
- Dose sterilization
- Circulating water pump
- Massage pump
- Pressure relief valve
- Pressure display
- 6-multi-port valve
- Automatic doser
- Time controller
- Contactor






QUARTS SAND FILTER

Model : HPK8010

In-ground filter are made of fiberglass and polyvinyl chloride, which is design and good-looking and durable. The in-ground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground sand filter assemble complete set filtration configuration to high filtering capacity and to reach to back wash. According with swimming pool specifications and standards.

NOTES: Ozone and heater(optional)



- a | Connected wall return
- b | Connected skimmer
- c | Connected suction fitting
- d | Connected wall return
- e | Connected backwash

- Complete filtration
- Complete circulation
- Dose sterilization
- Circulating water pump
- Pressure relief valve
- Pressure display
- 6-multi-port valve
- Automatic doser
- Time controller
- Contactor

TECHNICAL CHARACTERISTICS

Power	1.5HP/220V	2.0HP/220V
Filter type	Sand filter Φ625mm / Φ700mm	
Flow rate	16m ³ /h	21m ³ /h
External Dimension	1380x1180x1100mm	
Disinfection	Sterilizer	




QUARTS SAND FILTER

Model : HPK8011

In-ground filter are made of fiberglass and polyvinyl chloride, which reasonable design and good-looking and durable. The inground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground sand filter assemble complete set filtration configuration to high filtering capacity and to reach to back wash. According with swimming pool specifications and standards, it's the best choice for Big and commercial swimming pools.

NOTES: Ozone and heater (optional).



a	Connected wall return
b	Connected skimmer
c	Connected suction fitting
d	Connected wall return
e	Connected backwash

- Complete filtration
- Complete circulation
- Dose sterilization
- Circulating water pump
- Pressure relief valve
- Pressure display
- 6-multi-port valve
- Automatic doser
- Time controller
- Contactor

TECHNICAL CHARACTERISTICS

Power	2HP/220V	3HP/220V
Filter type	Sand filter Φ800mm	Φ900mm Φ1000mm
Flow rate	26m³/h	33m³/h
External Dimension	1650x1600x1260mm	
Disinfection	Sterilizer	






QUARTS SAND FILTER


Model : HPK8012

In-ground filter are made of fiberglass and polyvinyl chloride, which reasonable design and good-looking and durable. The inground does not need a machine house, which save construction cost, convenient operation and save maintenance cost. Multic use in-ground polyester fiber filter assemble complete set filtration configuration to high filtering capacity. According with swimming pool specifications and standards.

NOTES: Ozone and heater(optional).



- a Connected wall return
- b Connected skimmer
- c Connected suction fitting
- d Connected wall return



Housing leakage pipe DN50

TECHNICAL CHARACTERISTICS

Power	3HP/220V
Filter type	Polyester Fiber 2x75ft ²
Filter Capacity	36m ³ /h
External Dimension	1380x1180x1200mm
Disinfection	Sterilizer



GL-002
(Time control box)






QUARTS SAND FILTER

Model : HPK8019

The enclosure of wall-mounted filter is made of high quality Acrylic and fiberglass, so the filter is anti-acid anti-fading, and easy to clean. Integrated filter installation without room, simple installation, convenient operation, excellent performance, thereby reducing the construction cost. It's big flow rate for 8pcs filter bag.



TECHNICAL CHARACTERISTICS



Dimensions	1370x1000x720mm
Flow rate	47m ³ /h
Voltage	220V/50Hz or 60Hz
Precision of filtration bag	≤5μ
Operating noise	≤50Db
Material	Fiberglass/Acrylic
Installation	Inground

EQUIPMENT

Filtration Pump	1x4HP
Filtration basket with bag	8pcs
Chlorine feeder	1pc
Time controller	1pc
4" Connection Inlet	1pc

SYSTEM

Filtration system	1pc
Disinfection system	1pc
Time control system	1pc
Circle system	1pc




Model : HPK8015


The enclosure is made of high quality fiberglass and Acrylic, which is strong and durable, rust-proof, low temperature resistance and anti-UV light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; easy to install, no need a special machine room.

Notes: Massage pump, salt chlorinator and automatic chlorine off-line feeder(Optional).

1	Filter shell
2	Sand filter
3	Junction box
4	Water quality controller
5	Chlorinator feeder
6	Submersible pump
7	UV sterilizer
8	Water pump




- a Connect the water return, suction fitting
- b Connect the water outlet (after the water disinfection)
- c Connect the water outlet (after the UV)
- d Connect the water outlet (after the Submersible pump)
- e Connect the water outlet (sand filter)



TECHNICAL CHARACTERISTICS

Power	1HP/220V	1.5HP/220V
Filter type	Sand filter Φ525mm	Φ625mm
Flow rate	12m³/h	16m³/h
External Dimension	1300x1250x960mm	
Disinfection	Sterilizer	
Water pump	120W/220V	
Salt chlorinator	16~42 g/h	(options)
UV	65W/220V	(options)
CCOREI	(options)	






QUARTS SAND FILTER

Model : HPK8016


The enclosure is made of high quality fiberglass and Acrylic, which is strong and durable, rust-proof, low temperature resistance and anti-UV light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; easy to install, no need a special machine room.

Notes: Massage pump, salt chlorinator and automatic chlorine off-line feeder (Optional).




1	Filter shell
2	Sand filter
3	Chlorinator feeder
4	Water pump
5	Submersible pump

- a Connect the water return, suction fitting
- b Connect the water outlet (after the water disinfection)
- c Connect the water outlet (after the UV)
- d Connect the water outlet (after the Submersible pump)
- e Connect the water outlet (sand filter)



TECHNICAL CHARACTERISTICS


Power	2HP/220V	3HP/220V
Filter type	Sand filter Φ800mm	Φ900mm
Flow rate	25m ³ /h	31m ³ /h
External Dimension	1650x1700x1250mm	
Disinfection	Sterilizer	
Water pump	120W/220V	
Salt chlorinator	16~42 g/h	(options)
UV	85W/220V	(options)
CCOREI	(options)	




QUARTS SAND FILTER

Model : HPK8013

The enclosure is made of high quality fiberglass and Acrylic, which is strong and durable, rust-proof, low temperature resistance and anti-UV light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; easy to install, no need a special machine room.



- | | |
|---|-------------------------------|
| a | Connect backwater inlet Ø50 |
| b | Connect the water outlet Ø50 |
| c | Connect the sewage outlet Ø50 |



TECHNICAL CHARACTERISTICS

Power	0.5 HP/220V	0.75HP	3HP/220V
Filter type	Sand filter Ø400mm	Ø450mm	Ø525mm
Flow rate	8m³/h	10m³/h	12m³/h
External Dimension	950x950x950mm		
Water pump	120W/220V	Options	
Disinfection	Sterilizer		



- Complete filtration
- Complete circulation
- Dose sterilization
- Circulating water pump
- Massage pump
- Pressure relief valve
- Pressure display
- 6-multi-port valve
- Automatic doser
- Time controller
- Contactor

The enclosure is made of high quality fiberglass and Acrylic, which is strong and durable, rust-proof, low temperature resistance and anti-UV light, etc. Equipped with filtering timing automatic control system and the automatic drainage system; easy to install, no need a special machine room. Equipped with cartridge filter inside the box, easy to operate.



1	Filter shell
2	Cartridge filtration
3	Chlorinator feeder
4	Water pump

a	Connect the water return
b	Connect the water return
c	Connect the water outlet
d	Connect the water outlet (cartridge filtration)



TECHNICAL CHARACTERISTICS

Power	3.0 HP/220V	
Filter type	Cartridge filtration AF50x3pc	
Flow rate	42m ³ /h	
External Dimension	1450x1070x780	
Disinfection	Sterilizer	
Water pump	120W/220	Options




QUARTS SAND FILTER

Model : HPK8035A



- a | Connect the water return, sunction fitting
- d | Connect the circulation outlet
- e | Connected backwash


Power	0.75 HP/220V	1.0HP/220V
Filter type	Sand filter Ø525mm	
Flow rate	10m³/h	12m³/h
External Dimension	1150x1100x810mm	
Chlorine feeder	CL-100	1pc
Time Controller		1pc



- a | Connect the water return, sunction fitting
- d | Connect the circulation outlet
- e | Connected backwash

Power	1.0 HP/220V	1.5HP/220V
Filter type	Sand filter Ø525mm / Ø650mm	
Flow rate	12m³/h	16m³/h
External Dimension	1150x1100x900mm	
Chlorine feeder	CL-100	1pc
Time Controller		1pc

Model : HPK8035B





HPK-8031A

TECHNICAL CHARACTERISTICS

Model No.	HPK8031 (Pool massage)
Material	(Acrylic)
Dimension	2600(L) x 1600(W) x 1200(H)mm
Weight	-
Color	(bone color)
Power	220V/50Hz
Flow rate	25m³/h
Hydrotherapy system	<ul style="list-style-type: none"> - 26 massage nozzles (Jet), 30 bubble massage nozzles (Airjet), stainless steel nozzle set (s, s jet) - 2 circulating water supply ports (Circulating) and 1 countercurrent swimming nozzle (Swim jet)
Filtering system	<ol style="list-style-type: none"> 1. 2 filter barrels (1 for 5 microns/1 for 15 microns) (Filter bag) 2. 2 water outlets (Water return) 3. Sinking separate waterproof equipment box (1200x1000x500mm) (Water proof box)
Treatment	Ozone generator (500mg/h, 132W) (Ozone)
Lighting	Swimming pool underwater lights (LED 18W/12V) (Light)
Control panel	<ol style="list-style-type: none"> 1. Fully automatic digital controller (digital clock/water temperature display) (Digital controller) options 2. Massage water flow adjustment knob (Flow control valve) options 3. Air/water mixing ratio adjustment knob (Air control valve) options
HPK-8031A Pumps	<ul style="list-style-type: none"> - Filter water pump (1pcs/2HP) (Filtration pump) options - Massage pumps (2pcsx3HP) (Massage pump) Option - Air pump (1pcs/900W) (Air blower) options
Approval	Ce certification





HORBO SAND FILTER SERIES





"HP" SERIES FIBERGLASS TOP MOUNT FILTER

Bobbin-wound fiberglass reinforced tank is still the most popular standard in the industry after all. With Uv-resistant surface finished, it is able to operate under prolong sunlight for years of reliability. HP series (HP400-HP1400) filters are equipped with a sixposition, clamp and screw styles muliport vale and ABS laterals.



HP400-700




HPQ400-700



HP750-1400

Highlight Features


- Max operating pressure 36psi/2.5bar
- Max temperature of 43°C (109°F)
- Universal standard of union connection provided
- Suggested size of media:0.5-1.2mm



TECHNICAL CHARACTERISTICS

Model	Filter Area (m ²)	Valve Connecting	Max Flow Rate	Gravel (Kg)	A mm	B mm
HP400	0.13	1.5 inch	50 mm	8 m ³ /h	35	760 400
HP450	0.16	1.5 inch	50 mm	10 m ³ /h	45	815 450
HP525	0.22	1.5 inch	50 mm	12 m ³ /h	85	880 525
HP625	0.30	1.5 inch	50 mm	16 m ³ /h	150	1005 625
HP700	0.40	1.5 inch	50 mm	20 m ³ /h	210	1100 700
HP700B	0.40	2.0 inch	63 mm	21 m ³ /h	215	1150 700
HP750	0.45	2.0 inch	63 mm	23 m ³ /h	300	1180 750
HP800	0.50	2.0 inch	63 mm	25 m ³ /h	355	1310 800
HP900	0.64	2.0 inch	63 mm	31 m ³ /h	470	1380 900
HP1000	0.79	2.0 inch	63 mm	36 m ³ /h	620	1495 1000
HP1100	0.96	2.0 inch	63 mm	42 m ³ /h	800	1580 1100
HP1200	1.13	2.0 inch	63 mm	45 m ³ /h	900	1600 1200
HP1400	1.54	2.0 inch	63 mm	56 m ³ /h	1350	1810 1400

Functions : 6-Way Multiport Valve





"HSL" SERIES FIBERGLASS SIDE MOUNT DEEP BED FILTER

HSL Series Side Mount Deep Bed Filter offers a more thorough filtration with the standard of either 1mm or 1.2mm deep sand bed which is suitable for high filtration performance of domestic swimming pool



Lateral system




Manhole

Highlight Features

- Max operating pressure 36psi/2.5bar
- Max temperature of 43°C (109°F)
- Maximum filtration velocity : 50m³ / h/m²
- Universal standard of union connection provided
- Suggested size of media : 0.5-1.2mm
- Dual layers of laterals
- 4" Sight glass
- 158mm manhole for servicing
- 2" bottom drain

TECHNICAL CHARACTERISTICS

Model	Filter Area (m ²)	Valve Connecting		Max Flow Rate		Gravel (Kg)
HSL700-1.0	0.38	1.5 inch	63mm	253lpm	15.20m ³ /h	580
HSL700-1.2	0.38	1.5 inch	63mm	253lpm	15.20m ³ /h	696
HSL800-1.0	0.50	2.0 inch	63mm	333lpm	20.00m ³ /h	769
HSL800-1.2	0.50	2.0 inch	63mm	333lpm	20.00m ³ /h	914
HSL900-1.0	0.63	2.0 inch	63mm	420lpm	25.2m ³ /h	957
HSL900-1.2	0.63	2.0 inch	63mm	420lpm	25.2m ³ /h	1146
HSL1000-1.0	0.78	2.0 inch	63mm	520lpm	31.20m ³ /h	1204
HSL1000-1.2	0.78	2.0 inch	63mm	520lpm	31.20m ³ /h	1436



Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm
HSL700-1.0	388	758	844	987	1320	1672	700	1000	576
HSL700-1.2	388	758	844	987	1520	1872	700	1200	576
HSL800-1.0	422	752	838	981	1313	1702	800	1000	800
HSL800-1.2	422	752	838	981	1513	1902	800	1200	800
HSL900-1.0	441	771	857	1000	1331	1735	900	1000	800
HSL900-1.2	441	771	857	1000	1531	1935	900	1200	800
HSL1000-1.0	515	885	971	1114	1406	1813	1000	1000	995
HSL1000-1.2	600	970	971	1199	1560	2013	1000	1200	995

Note : Suggested sand weight varies with differences in filter media size,
For reference only





"HPS" SERIES FIBERGLASS SIDE MOUNT FILTER

Bobbin-wound fiberglass reinforced tank is still the most popular standard in the industry after all. With Uv-resistant surface finished, it is able to operate under prolong sunlight for years of reliability. "Hps"series filters are equipped with a six position, clamp and screw styles muliport vale and ABS laterals.



HPS525-700



Highlight Features

- Max operating pressure 36psi/2.5bar
- Max temperature of 43°C (109°F)
- Universal standard of union connection provided
- Suggested size of media : 0.5-1.2mm



HP750-1400

TECHNICAL CHARACTERISTICS

Model	Filter Area (m ²)	Valve Connecting	Max Flow Rate	Gravel (Kg)	A mm	B mm
HPS25	0.22	1.5 inch	50mm	12m ³ /h	85	780
HPS625	0.30	1.5 inch	50mm	16m ³ /h	150	880
HPS700	0.40	1.5 inch	50mm	20m ³ /h	210	945
HPS700B	0.40	2.0 inch	63mm	21m ³ /h	215	945
HPS750	0.45	2.0 inch	63mm	23m ³ /h	300	960
HPS800	0.50	2.0 inch	63mm	25m ³ /h	355	1080
HPS900	0.64	2.0 inch	63mm	31m ³ /h	470	1100
HPS1000	0.79	2.0 inch	63mm	36m ³ /h	620	1285
HPS1100	0.96	2.0 inch	63mm	42m ³ /h	800	1380
HPS1200	1.13	2.0 inch	63mm	45m ³ /h	900	1500
HPS1400	1.54	2.0 inch	63mm	56m ³ /h	1350	1580

Note : Reference Only






"HPL" SERIES FIBERGLASS SIDE MOUNT FILTER

HPL Series Commercial Sand Filter satisfies the demand of different water treatment including pools installed within-floor cleaning systems spa, fountains and public swimming pool.



HPL 1200-2350



Highlight Features

- Max operating pressure 36psi/2.5bar
- Max temperature of 43°C (109°F)
- Universal standard of union connection provided
- Suggested size of media : 0.5-1.2mm



water inlet



water outlet

TECHNICAL CHARACTERISTICS

Model	Filter Area (m ²)	Valve Connections	Max Flow Rate	Gravel (Kg)	A mm	B mm
HPL1200	1.13	3.0 inch	90mm	55m ³ /h	900	1410
HPL1400	1.54	3.0 inch	90mm	76m ³ /h	1350	1570
HPL1600	2.06	4.0 inch	110mm	100m ³ /h	2300	1740
HPL1800	2.52	6.0 inch	160mm	120m ³ /h	2900	2040
HPL2000	2.97	6.0 inch	160mm	145m ³ /h	4000	2210
HPL2300	4.43	8.0 inch	200mm	210m ³ /h	6000	2510
HPL2350	4.43	8.0 inch	200mm	210m ³ /h	6000	2510
						2350

4/5 Way Butterfly Valve



4 Way Butterfly Valve

250kPa/36psi/2.5bar
400kPa/58psi/4.0bar
43°C (109 °F)

Max operating pressure : 250kPa/36psi/2.5bar
Factory Testing Pressure : 400kPa/58psi/4.0bar
Maximum Water Temperature : 43°C (109 °F)




5 Way Butterfly Valve





"HFSB" SERIES FIBERGLASS COMBO

Designed for easy set-up domestic pool, "HFSB" Series filtration combo offers the right solution for home user who is looking for user-friendly and excellent filtration performance. HFSB Series Filtration Combo includes top mount fiberglass filter tank, 6-way muliport value, swimming pool pumps attached with base.



Highlight Features

- Max operating pressure 36psi/2.5bar
- Max temperature of 43°C (109°F)
- Universal standard of union connection provided
- Suggested size of media : 0.5-1.2mm



TECHNICAL CHARACTERISTICS						
Model No	Filter	Pump	Valve Connections	Sand (Kg)		
HFSB500-6W	PS525	STP100	1.5 Inch	50 mm	85	
HFSB650-6W	PS625	STP120	1.5 Inch	50 mm	145	
Model No	A mm	B mm	C mm	D mm	Max Flow Rate	
HFSB500-6W	770	867	390	527	760	185lpm 11.10m³/h
HFSB650-6W	850	967	430	627	760	260lpm 15.60m³/h

"HPSF" SERIES FIBERGLASS COMBO

Designed for easy set-up domestic pool,"HPSF" Series filtration combo offers the right solution for home user who is looking for user-friendly and excellent filtration performance. HPSF Series Filtration Combo includes top mount fiberglass filter tank, 6-way muliport value, swimming pool pumps attached with base.



Highlight Features

- Max operating pressure 36psi/2.5bar
- Max temperature of 43°C (109°F)
- Universal standard of union connection provided
- Suggested size of media : 0.5-1.2mm



TECHNICAL CHARACTERISTICS						
Model No	Max Flow Rate	Filter	Pump	Valve Connections	Sand (Kg)	
HPSF400-6W	6.48	P400	STP50	1.5 Inch	50 mm	35
HPSF450-6W	8.10	P450	STP75	1.5 Inch	50 mm	45
HPSF525-6W	11.1	P525	STP100	1.5 Inch	50 mm	85
HPSF625-6W	15.6	P625	STP120	1.5 Inch	50 mm	150



STAINLESS STEEL FILTER SERIES



TOP-MOUNT SAND FILTER



SIDE-MOUNT SAND FILTER




TOP-MOUNT SAND FILTER

Top-Mount Sand Filter

Model No	Tank Dia. mm	Hight mm	Pipe Size (inch)	Filter Area	Silca Sand	Flow (m³/h)	Pressure (Kg/cm²)
HD400	400	800	1.5	0.13	70	6.7	2.5
HD500	500	870	1.5	0.22	100	10.8	2.5
HD600	600	970	1.5	0.36	170	16.4	2.5
HD700	700	1000	2.0	0.41	190	21.3	2.5
HD800	800	1160	2.0	0.51	300	26.8	2.5
HD900	900	1260	2.0	0.65	400	32.6	2.5
HD1000	1000	1270	2.0	0.81	500	40.3	2.5

Top-Mount Sand Filter

Model No	Tank Dia. mm	Hight mm	Pipe Size (inch)	Filter Area	Silca Sand	Flow (m³/h)	Pressure (Kg/cm²)
HD1200	1200	1450	3	1.14	1100	55	2.5
HD1400	1400	1570	4	1.56	1900	76	2.5
HD1600	1600	1760	4	2.01	2300	100	2.5
HD1800	1800	2040	4	2.54	2900	129	2.5
HD2000	2000	2240	6	2.97	4600	147	2.5
HD2200	2200	2520	6	4.10	5800	218	2.5
HD2300	2300	2550	6	4.43	6000	220	2.5
HD2500	2500	2680	8	4.89	6700	240	2.5



Top-Mount Sand Filter

Code	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U
040416	1800	1700	400	φ400	1600	φ160	1320	100	1050	120	φ500	480	260	870	990	250	360	900	440	100	2350
040418	2020	1920	400	φ400	1800	φ160	1480	100	1050	120	φ500	500	260	1080	1090	250	460	1000	440	100	2800
040420	2260	2160	600	φ400	2000	φ160	1640	120	1050	120	φ500	700	300	1100	1270	350	380	1120	550	160	3000
040424	2660	2560	600	φ400	2400	φ160	2300	120	1050	120	φ500	900	300	1480	1470	350	580	1320	550	160	3000
040425	2760	2660	600	φ400	2500	φ160	2300	120	1050	120	φ500	1050	300	1600	1520	350	630	1370	550	160	3000

CRYSTAL SAND FILTER MATERIAL



The paper core crystal sand filter material can effectively reduce the frequency of electric backwashing and save the number of water use; it has more advantages than quartz sand. Higher wear resistance, longer service life, not easy to break. No biofilm will be formed, and the surface area is 300 times larger than that of sand; suitable for it is used for filtration of gymnasium swimming pools, dedicated to marine aquariums, private villa swimming pools, and children's water parks.

Technical Characteristics	
Size mm	Weight (Kg/bag)
0.5-0.8	25
1.0-2.0	25
3.0-4.0	25

CARTRIDGE FILTER


Cartridge filtration is an effective trouble-free proven method of filtration. Pool water enters the filter and passes through a polyester single element cartridge. Suspended particles are trapped and the water is returned to the pool. As the build-up of dirt in the element increases, so the water pressure rises and the flow decreases. When the pressure reaches an unacceptable level the element must be removed and cleaned.



Cleaning brush

HAF PAPER

Model	Core diameter (mm)	Caliber (mm)	High (cm)	Filter material	Filtration accuracy (μm)
HAF25	Φ183	Φ78	18.45		
HAF50	Φ183	Φ78	36.45		
HAF75	Φ183	Φ78	54.45		
HAF100	Φ183	Φ78	72.45		
HAF150	Φ183	Φ78	90.45		



HAF PAPER FILTER

Technical Characteristics

Model	diameter (mm)	Height (mm)	Pump selection range (w)	Filter area (m^2)	Flow (m^3/h)	Greatest pressure (kpa)	Long cm	Width cm	High cm	Weight kg
HAF25	225	387	250-370	2.3	7.0	350	32	32	51	5.85
HAF50	225	567	550-750	4.7	14.0	350	32	32	69	7.35
HAF75	225	747	750-1100	7.0	17.0	350	32	32	86	9.05
HAF100	225	927	1100-1500	9.4	22.9	350	32	32	104.5	10.8
HAF150	225	1107	1100-2200	14.0	33.4	350	32	32	122	12.6

PUMP


SERIES






NEW "HPB" SERIES PUMP

NEW "HPB" series heavy duty pump delivers high flow and energy efficiency ultra performance. It is suitable for commercial swimming pool 2 inch suction. Ring lock seal design to eliminate suction leaks and to maximize suction efficiency.



OVERALL DIMENSION




TECHNICAL CHARACTERISTICS


New Model	Power (p ₁)	QMax (l/min)	HMax (m)	V	Packaging Size (mm)
	KW	HP			
HPB-120	0.9	1.2	350	12.5	220 675x315x420
HPB-150	1.1	1.5	380	16.5	220 675x315x420
HPB-200	1.5	2.0	500	20	220 675x315x420
HPB-300	2.2	3.0	600	22	200 675x315x420
HPB-300	2.2	3.0	600	22	380 675x315x420
HPB-400	3.0	4.0	650	25	380 700x315x420

NEW "HPC" SERIES PUMP

NEW "HPC" series swimming pool pump is designed for medium head installation in medium or domestic pool 1.5 inch suction and discharge port with transparent lid. It operates at a low decibel and easy maintenance.



OVERALL DIMENSION



TECHNICAL CHARACTERISTICS

New Model	QMax (l/min)	HMax (m)	V/Hz		Power (p ₁)	Amps	Fitting Size	Kg
			Kw	Hp				
HPC-050	195	7	220-240/50	0.37	0.50	1.9	48.5 Or 50	9.3
HPC-075	255	10	220-240/50	0.55	0.75	2.7	48.5 Or 50	9.5
HPC-100	340	12.5	220-240/50	0.75	1.0	3.8	48.5 Or 50	9.7
HPC-150	390	17.5	220-240/50	1.1	1.5	5.8	48.5 Or 50	10.9
HPC-200	470	18.5	220-240/50	1.5	2.0	7.0	48.5 Or 50	11.5




"HPC" SERIES PUMP

"Hpc" series swimming pool pump is designed for medium head installation in medium or domestic pool 1.5 inch suction and discharge port with transparent lid. It operates at a low decibel and easy maintenance.




Highlight Features:

- *Asynchronous, two poles
- *Class insulation: 130
- *IPX5 waterproof standard
- *Built-in thermal protection
- *Overload protection
- *Available for 50Hz or 60Hz with 220v/380v/110v
- *Special design union compatible for both Imperial and Metric measurement standard



OVERALL DIMENSION




TECHNICAL CHARACTERISTICS


Model	Input Power	Horse Power	Port Size	Weight (Kg)	Packaging Size (mm)
HPC075	0.55KW	0.75HP	1.5 inch / 50mm	12.0	12.10
HPC100	0.75KW	1.0 HP	1.5 inch / 50mm	13.40	13.40
HPC150	1.10KW	1.5 HP	1.5 inch / 50mm	14.90	14.90
HPC200	1.50KW	2.0 HP	1.5 inch / 50mm	14.40	15.40

"HPB" SERIES PUMP

"HPB" series heavy duty pump delivers high flow and energy efficiency ultra performance. It is suitable for commercial swimming pool. 2 inch suction and discharge port with transparent lid. Ring lock seal design to eliminate suction leaks and to maximize suction efficiency.



OVERALL DIMENSION



TECHNICAL CHARACTERISTICS

Model	Input Power	Horse Power	Port Size	Weight (Kg)
HPB15	1.10KW	1.5HP	2.0 inch / 63mm	17.00
HPB20	1.50KW	2.0HP	2.0 inch / 63mm	23.00
HPB30	2.20KW	3.0HP	2.0 inch / 63mm	24.00




"HPR" SERIES PUMP

"HPR" series heavy duty pump delivers high flow and energy efficiency ultra performance. It is suitable for commercial spa pool. 2 inch suction and discharge port with transparent lid. Ring lock seal design to eliminate suction leaks and to maximize suction efficiency.





Highlight Features:

- *Asynchronous, two poles
- *Class insulation: 130
- *IPX5 waterproof standard
- *Built-in thermal protection
- *Overload protection
- *Available for 50Hz or 60Hz with 220v/380v/110v
- *Special design union compatible for both Imperial and Metric measurement standard




OVERALL DIMENSION



Model	Input Power	Horse Power	Port Size		Weight (Kg)
			2.0 inch / 63mm	2.0 inch / 63mm	
HPR15	1.10KW	1.5 HP	2.0 inch / 63mm	2.0 inch / 63mm	16.30
HPR20	1.50KW	2.0 HP	2.0 inch / 63mm	2.0 inch / 63mm	19.70
HPR30	2.20KW	3.0 HP	2.0 inch / 63mm	2.0 inch / 63mm	22.10

"HHS" SERIES PUMP




TECHNICAL CHARACTERISTICS

Model	Qmax (m³/h)	Hmax (m)	V/Hz	Weight		Inlet φ D (Inch)	Qutle φ E (Inch)
				Kw	Hp		
HHS-30	38	18	380/50	2.2	3	2.5"/75mm	2.5"/75mm
HHS-50	55	20	380/50	3.8	5	2.5"/75mm	2.5"/75mm
HH-55	60	19	380/50	4.0	5.5	3.0"/90mm	3.0"/90mm
HH-75	80	20	380/50	5.5	7.5	3.0"/90mm	3.0"/90mm




"HP" SERIES PUMP



Model	Qmax (m³/h)	Hmax (m)	V/Hz	Weight		Inlet φ D (Inch)	Qutle φ E (Inch)
				Kw	Hp		
HP-55	60	19	380/50	4	5.5	3.0"/90mm	3.0"/90mm
HP-75	80	20	380/50	5.5	7.5	3.0"/90mm	3.0"/90mm
HP-100	95	21	380/50	7.5	10	3.0"/90mm	3.0"/90mm
HP-150	110	22	380/50	11	15	3.0"/90mm	3.0"/90mm

"HFD" SERIES PUMP




Model	Qmax (m³/h)	Hmax (m)	V/Hz	Technical Characteristics			
				Inlet Flange (mm)	Outlet Flange (mm)	Inlet φ D (Inch)	Qutle φ E (Inch)
HFD-55	60	16	380/50	4-M12φ90	4-φ18φ75	φ86	φ63
HFD-75	75	18	380/50	4-M12φ90	4-φ18φ75	φ86	φ63
HFD-100	120	18	380/50	8-φ18φ110	4-φ18φ90	φ100	φ80
HFD-150	160	18	380/50	8-φ18φ110	4-φ18φ90	φ100	φ80






HWE SERIES PUMP



TECHNICAL CHARACTERISTICS

Model	Qmax (m³/h)	Hmax (m)	V/Hz	Power		(Amps)	Inlet/Outlet
				KW	HP		
HWE-400	1480	16	380/50	3.0	4	5.9	(DN150(6"))
HWE-500	1680	17	380/50	4.0	5	6.8	(DN150(6"))
HWE-750	1830	22	380/50	5.5	7.5	10.3	(DN150(6"))
HWE-1000	2560	22	380/50	7.5	10	12.7	(DN150(6"))
HWE-1500	3000	26	380/50	11	15	20.1	(DN150(6"))
HWE-2000	3100	29	380/50	15	20	26.7	(DN150(6"))
HWE-2500	3300	31	380/50	18.5	25	30.3	(DN150(6"))

"HWQ" SERIES PUMP



TECHNICAL CHARACTERISTICS

Model	Qmax (m³/h)	Hmax (m)	V/Hz	Power		(Amps)	Inlet/Outlet
				KW	HP		
HWQ-400	1480	16	380/50	3.0	4	5.9	(DN150(6"))
HWQ-500	1680	17	380/50	4.0	5	6.8	(DN150(6"))
HWQ-750	1830	22	380/50	5.5	7.5	10.3	(DN150(6"))
HWQ-1000	2560	22	380/50	7.5	10	12.7	(DN150(6"))
HWQ-1500	3000	26	380/50	11	15	20.1	(DN150(6"))
HWQ-2000	3100	29	380/50	15	20	26.7	(DN150(6"))
HWQ-2500	3300	31	380/50	18.5	25	30.3	(DN150(6"))






SWIM JET 2000

- Jet Swim house made of stainless steel, front and handle made of polished acid-proof stainless steel AISI 304. For mounting in concrete, wood or building block walls.
- Pump power: 3KW
- Control box including contactor and overload protection
- Air mixture control
- Air mixture hose
- Hose connectors
- Hose clamps
- Hose for suction and pressure
- Valves



TECHNICAL CHARACTERISTICS

Model	Power (KW)	Voltage (V)	Pump Connection (mm)	Water Capacity (L/Min)	Jet Material
HPK2000	2.18	220	φ63	35	Stainless Steel






SWIM JET 3000

- Jet Swim house made of stainless steel, front and handle made of polished acid-proof stainless steel AISI 304. For mounting in concrete, wood or building block walls.
- Pump power: 3KW
- Control box including contactor and overload protection
- Air mixture control
- Air mixture hose
- Hose connectors
- Hose clamps
- Hose for suction and pressure
- Valves



TECHNICAL CHARACTERISTICS



Model	Power (KW)	Voltage (V)	Pump Connection (mm)	Water Capacity (L/Min)	Jet Material
HPK3000	3	220/380	φ75	70	Bronze, Stainless Steel






WP-4HP/220v/380v



PROPULSION SYSTEM



HPK8100



HPK8000

The propulsion system is made of high-density fiberglass and acrylic materials, high load and high temperature operation, more reliable. As a newgeneration swimming machine developed, it's a device for infinity swimming, turning the small pool into an endless pool. Through a special hydraulic pushing device a directional water flow is formed and pushed to the swimmer to achieve the purpose of exercise.

TECHNICAL CHARACTERISTICS

Model	Power (KW)	Voltage (V)	Packaging Size (mm)
HPK8100	2.8	380	1200x980x1300
HPK8000	2x2.8	380	1860x1150x1340



UNDER WATER LIGHT SERIES



UNDERWATER LIGHT SERIES



HPK6001S Wall Mounted Type Pool Light

Material: 304 Stainless Steel	Waterproof Standard: IP68
Cable: 3x1.5mm ² x1.5m	Available: LED 6x1W/12V
(White Color / Automatic Color Change)	

HPK6003 Wall Mounted Type Pool Light

Material: 304 Stainless Steel	Available:
Cable: 3x1.5mm ² x1.5m	1. 100W/12V Halogen light bulb
Waterproof Standard: IP68	2. LED 9x1W/12V
(White Color / Auto Color Change)	3. LED 12x1W/12V




HPK6001 Wall Mounted Type Pool Light

Material: 304 Stainless Steel	Available:
Cable: 2x1.5mm ² x1.5m	1. 100W/12V Halogen light bulb
Waterproof Standard: IP68	
(White Color / Auto Color Change)	

HPK6005 Wall Mounted Type Pool Light

Material: ABS + UV	Available:
Cable: 2x1.5mm ² x1.5m	1. 100W/12V Halogen light bulb
Waterproof Standard: IP68	
(White Color / Auto Color Change)	



HPK6004S Wall Mounted Type Pool Light

Material: ABS + UV	Available:
Cable: 3x1.5mm ² x1.5m	1. 100W/12V Halogen light bulb
Waterproof Standard: IP68	
(White Color / Auto Color Change)	

HPK6004 Wall Mounted Type Pool Light

Material: ABS + UV	Available:
Cable: 2x1.5mm ² x1.5m	1. 100W/12V Halogen light bulb
Waterproof Standard: IP68	
(White Color / Auto Color Change)	

UNDERWATER LIGHT SERIES



HPK6006 Wall Mounted Type Pool Light

Material: ABS + UV
Cable: 2x1.5mm²x1.5m

Waterproof Standard: IP68


- Available:
1. 100W/12V Halogen light bulb
 2. 144 LED Bulbs 12W/12V
 3. 252 LED Bulbs 25W/12V
 4. LED 9x1W/12V
 5. LED 12x1W/12V
 6. LED 18x1W/12V
- (White Color / Auto Color Change)

HPK6007 Wall Mounted Type Pool Light

Material: ABS + UV
Cable: 2x1.5mm²x1.5m

Waterproof Standard: IP68

- Available:
1. 100W/12V Halogen light bulb
 2. 144 LED Bulbs 12W/12V
 3. 252 LED Bulbs 25W/12V
 4. LED 9x1W/12V
 5. LED 12x1W/12V
 6. LED 18x1W/12V
- (White Color / Auto Color Change)




HPK6010 Buried Type Pool Light

Material: 304 Stainless Steel
Cable: 3x2.5mm²x1.5m

Waterproof Standard: IP68

- Available:
1. 100W/12V Halogen light bulb
 2. 36 LED Bulbs 3W/12V
 3. 90 LED Bulbs 6W/12V
- (White Color / Auto Color Change)



HPK6011 Buried Type Pool Light

Material: 304 Stainless Steel
Cable: 3x4mm²x1.5m

Waterproof Standard: IP68

- Available:
1. 300W/12V Halogen light bulb
 2. 252 LED Bulbs 18W/12V
- (White Color / Auto Color Change)

HPK6017 Buried Type Pool Light

Material: ABS + UV
Cable: 2x4mm²x1.5m

Waterproof Standard: IP68



- Available:
1. 300W/12V Halogen light bulb
 2. 252 LED Bulbs 18W/12V
 3. 441 LED Bulbs 35W/12V
 4. 546 LED Bulbs 40W/12V
 5. LED 12x1W/12V
 6. LED 18x1W/12V
 7. LED 24x1W/12V
 8. LED 18x3W 35W/12V
- (White Color / Auto Color Change)

HPK6017V Buried Type Pool Light (For Liner Pool)

Material: ABS + UV
Cable: 2x4mm²x1.5m

Waterproof Standard: IP68

- Available:
1. 300W/12V Halogen light bulb
 2. 252 LED Bulbs 18W/12V
 3. 441 LED Bulbs 35W/12V
 4. LED 12x1W/12V
 5. LED 18x1W/12V
 6. LED 24x1W/12V
 7. LED 18x3W 35W/12V
- (White Color / Auto Color Change)



HPK6016 Buried Type Pool Light

Material: ABS + UV
Cable: 2x4mm²x1.5m

Waterproof Standard: IP68

- Available:
1. 300W/12V Halogen light bulb
 2. 252 LED Bulbs 18W/12V
 3. 441 LED Bulbs 35W/12V
 4. 546 LED Bulbs 40W/12V
 5. LED 12x1W/12V
 6. LED 18x1W/12V
 7. LED 24x1W/12V
 8. LED 18x3W 35W/12V
- (White Color / Auto Color Change)

HPK6016A Buried Type Pool Light

Material: ABS + UV
Cable: 2x4mm²x1.5m

Waterproof Standard: IP68


- Available:
1. 300W/12V Halogen light bulb
 2. 252 LED Bulbs 18W/12V
 3. 441 LED Bulbs 35W/12V
 4. 546 LED Bulbs 40W/12V
 5. LED 12x1W/12V
 6. LED 18x1W/12V
 7. LED 24x1W/12V
 8. LED 18x3W 35W/12V
- (White Color / Auto Color Change)


HPK6625

Material: AISI-304 Stainless steel

Watt/Voltage: 7x1W/12V

Waterproof: IP68


HPK6626

Material: AISI-304 Stainless steel

Watt/Voltage: 9x1W/12V

Waterproof: IP68


HPK6627

Material: AISI-304 Stainless steel

Watt/Voltage: 24W/18W/12V

Waterproof: IP68

Watt/Voltage: 300W/12V (PARS6)

Cable: 3x2.5mm²x2.0m


HPK6628


Material: AISI-304 Stainless steel

Watt/Voltage: 12W/9W/6W/12V

Waterproof: IP68

Watt/Voltage: 100W/12V


Cable: 3x2.5mm²x2.0m


HPK6629

Material: AISI-304 Stainless steel

Watt/Voltage: 3x1W/12V


Waterproof: IP68


HPK6630

Material: AISI-304 Stainless steel

Watt/Voltage: 9x1W/12V


Waterproof: IP68


HPK6631

Material: AISI-304 Stainless steel

Watt/Voltage: 1W/12V

Waterproof: IP68


HPK6632

Material: AISI-304 Stainless steel


Watt/Voltage: 12W/9W/6W/12W

Waterproof: IP68




RGB SERIES UNDERWATER LIGHT

RGB REMOTE CONTROL



REMOTE CONTROL ARM



RGB MODE FUNCTION DESCRIPTION

MODE 1: STATIC BLUE

MODE 4: STATIC PURPLE

MODE 7: STATIC WHITE

MODE 2: STATIC RED

MODE 5: STATIC CYAN

MODE 3: STATIC GREEN

MODE 6: STATIC YELLOW

MODE 8: (RGB MATERIAL) RG IS ALWAYS BRIGHT, AND FADES TO 1.9S (R↓ G) G IS ALWAYS BRIGHT, AND R FADES TO 1.95 → (GL) G FADES TO 1.95 (RGB) RB IS ALWAYS BRIGHT, AND G FADES TO 1.9S+ (RB) R IS ALWAYS ON, GRADUALLY GETTING DARKER 1.9S + (RI) R IS GETTING DARKER 1.95 (RGB) GB IS ALWAYS BRIGHTER, R IS GETTING DARKER 1.95 → (G↓ B) DAY IS ALWAYS BRIGHTER, G IS GETTING DARKER 1.95 → (B↓) DAYTIME IS GETTING DARKER 1.95 CYCLE.

MODE 9: (G↓ B↑) RED FADES TO DARK WHILE GREEN FADES TO BRIGHT 1.95+ (GBT) GREEN FADES TO DARK WHILE BLUE FADES TO BRIGHT 1.95 (RT B↓) BLUE FADES TO DARK WHILE RED FADES TO BRIGHT 1.95 LOOP .

MODE 10: R (60MS) → G(60MS) → B(60MS) → CYCLE 10 TIMES R(120MS) → G(120MS) → B(120MS) → CYCLE 5 TIMES → R(180MS) → G(180MS) → B(180MS) CYCLE 5 TIMES → R(240MS) → G(240MS) → DAY(240MS) + CYCLE 5 TIMES → CYCLE FROM THE BEGINNING (CLOCKWISE ROTATION)


MODE 11: R(100MS) → DAY(100MS) → G(100MS) → LOOP 5 TIMES → R(160MS) → B(160MS) → G(160MS) + CYCLE 5 TIMES (220MS) → B(220MS) → G(220MS) → CYCLE 5 TIMES (280MS) → B(280MS) → G(280MS) → CYCLE 5 TIMES → CYCLE FROM THE BEGINNING (COUNTER CLOCKWISE ROTATION)

MODE 12: (RT) RED FADES TO BRIGHTER 1.9S (R↓) RED FADES TO DARKER 1.9S (G↑) GREEN FADES TO BRIGHTER 1.9S (G↑) GREEN FADES TO DARKER 1.9S (B↑) BLUE FADES BRIGHT 1.95 → (B↓) BLUE COLOR FADES 1.95 CYCLES.

THE TIME IS BASED ON THE FASTEST SPEED! GEAR G↓ B↑ IS THE GUIDELINE. THE 2ND GEAR IS SLOWER BY 1 LETTER 2T, AND THE 3RD GEAR IS -3T105-10



RGB SERIES UNDERWATER LIGHT



HPK8001 Wall Mounted Type Pool Light


Material: PC

Cable: 2x1.0mm²x1.5m

Waterproof Standard: IP68

Available:

1. LED Bulbs 18W/12V/24V
 2. LED Bulbs 25W/12V/24V
 3. LED Bulbs 35W/12V/24V
 4. LED Bulbs 40W/12V/24V
- (White Color / Auto Color Change)



HPK8002 Wall Mounted Type Pool Light


Material: PC

Cable: 2x1.0mm²x1.5m

Waterproof Standard: IP68

Available:

1. LED Bulbs 12W/12V/24V
 2. LED Bulbs 18W/12V/24V
 3. LED Bulbs 25W/12V/24V
 4. LED Bulbs 9x1W/12V/24V
 5. LED Bulbs 12x1W/12V/24V
- (White Color / Auto Color Change)



HPK8003 Wall Mounted Type Pool Light

Material: 304 Stainless Steel

Cable: 3x1.0mm²x1.5m

Waterproof Standard: IP68

Available:

1. LED Bulbs 18W/12V/24V
 2. LED Bulbs 25W/12V/24V
 3. LED Bulbs 35W/12V/24V
 4. LED Bulbs 40W/12V/24V
 5. LED Bulbs 12x1W/12V/24V
 6. LED Bulbs 18x1W/12V/24V
- (White Color / Auto Color Change)



HPK8004S Wall Mounted Type Pool Light


Material: PC

Cable: 3x1.0mm²x1.5m

Waterproof Standard: IP68

Available:

1. LED Bulbs 12W/12V/24V
 2. LED Bulbs 18W/12V/24V
 3. LED Bulbs 25W/12V/24V
 4. LED Bulbs 12x1W/12V/24V
 5. LED Bulbs 18x1W/12V/24V
- (White Color / Auto Color Change)



HPK8005S Wall Mounted Type Pool Light

Material: PC

Cable: 2x1.0mm²x1.5m

Waterproof Standard: IP68

Available:

1. LED Bulbs 12W/12V/24V
 2. LED Bulbs 18W/12V/24V
 3. LED Bulbs 25W/12V/24V
 4. LED Bulbs 9x1W/12V/24V
 5. LED Bulbs 12x1W/12V/24V
- (White Color / Auto Color Change)

TRANSFORMERS



HVT-041

Transformers

(220V→12V) 50Hz/60Hz
50W / 100W / 150W / 200W
300W / 400W / 500W / 600W



HVT-042

Transformers

(220V→12V) 50Hz/60Hz
60W / 105W / 200W /
300W / 400W



HSP-034

Junction Box



HVT-043


Transformers

(220V→12V) 50Hz/60Hz
500W / 600W / 800W / 1000W




WATER DESCENT


"HORBO" water descent provide several sizes and configurations to be available for different installation requirements. With a suitable water pump and filtration system, you can enjoy vibrant water falling effect, which will bring elegance and visual interest to the private gardens, swimming pools, parks or gardens. The soothing sound of the water flowing will add pleasure to people.



- + High stability, advanced artificial waterfall over in China
- * Built-in waterproof LED lights to beautify the water color
- * The LED lights are powered by 12V DC, RGB light source are safe and reliable
- + The LED lights can be operated through remote control, different light mode changes
- + The outlets of the waterfall are available in different sizes to meet different installation requirements
- + Multiple water descent systems can be connected to one controller to meet the effect synchronization of light mode




Approximate projection of sheet of water per 300mm of waterfall length.




"HORBO" water descent are suitable for installation on finished walls and new construction walls, as well length and thickness of the wall product design unique novel, beautiful. Efficient to hide the outlet, Showing a beautiful linear effect of the water.

TECHNICAL INFORMATION




MULTIPLE WATER DESCENT WITH VALVE MOUNTING




With LED Light

Model	Connection Size	A mm	B mm	C mm	D mm	Power	Voltage
HWD300-25-LED	1.5 Inch	50 mm	306	138	76	25	4W DC12V
HWD300-150-LED	1.5 Inch	50 mm	306	263	76	150	4W DC12V
HWD300-230-LED	1.5 Inch	50 mm	306	343	76	230	4W DC12V
HWD600-25-LED	1.5 Inch	50 mm	606	138	76	25	8W DC12V
HWD600-150-LED	1.5 Inch	50 mm	606	263	76	150	8W DC12V
HWD600-230-LED	1.5 Inch	50 mm	606	343	76	230	8W DC12V
HWD900-25-LED	1.5 Inch	50 mm	906	138	76	25	12W DC12V
HWD900-150-LED	1.5 Inch	50 mm	906	263	76	150	12W DC12V
HWD900-230-LED	1.5 Inch	50 mm	906	343	76	230	12W DC12V
HWD1200-25-LED	1.5 Inch	50 mm	1206	138	76	25	17W DC12V
HWD1200-150-LED	1.5 Inch	50 mm	1206	263	76	150	17W DC12V
HWD1200-230-LED	1.5 Inch	50 mm	1206	343	76	230	17W DC12V



Without LED Light

Model	Connection Size	A mm	B mm	C mm	D mm	Power	Voltage
HWD300-25	1.5 Inch	50 mm	306	138	76	25	- -
HWD300-150	1.5 Inch	50 mm	306	263	76	150	- -
HWD300-230	1.5 Inch	50 mm	306	343	76	230	- -
HWD600-25	1.5 Inch	50 mm	606	138	76	25	- -
HWD600-150	1.5 Inch	50 mm	606	263	76	150	- -
HWD600-230	1.5 Inch	50 mm	606	343	76	230	- -
HWD900-25	1.5 Inch	50 mm	906	138	76	25	- -
HWD900-150	1.5 Inch	50 mm	906	263	76	150	- -
HWD900-230	1.5 Inch	50 mm	906	343	76	230	- -
HWD1200-25	1.5 Inch	50 mm	1206	138	76	25	- -
HWD1200-150	1.5 Inch	50 mm	1206	263	76	150	- -
HWD1200-230	1.5 Inch	50 mm	1206	343	76	230	- -



HK-01



HK-25




HK-25




HK-02

Product Number	Model	Product Description	Operating Temperature	Input	Output	Transmitting Distance
08080016	HK24 / HK-02	LED CONTROL BOX	-20+40°C	AC 100V-240V 50/60HZ	DC 12V/24W	3M
08080017	HK25/ HK-01	LED CONTROL BOX	-20+40°C	AC 100V-240V 50/60HZ	DC 12V/60W	20M




Do not move the retaining bar before installation is complete, and avoid prolonged exposure to the sun!






ACYLIC POOL WATER FALL



Technical Characteristics

Model	Take Over Size	A mm	B mm	C mm	D mm	E mm	Power	Voltage
HWF-300	1.5 Inch	50 mm	603	423.5	320	236	416	-
HWF-301	2 Inch	63 mm	750	540.6	395	280	500	-
HWF-300LED	1.5 Inch	50 mm	603	423.5	320	236	416	12.0W DC12V
HWF-301LED	2 Inch	63 mm	750	540.6	395	280	500	13.0W DC12V




Technical Characteristics

Model	Take Over Size	A mm	B mm	C mm	D mm	E mm	Power	Voltage
HWF-302	1.5 Inch	50 mm	603	450	300	280	400	-
HWF-303	2 Inch	63 mm	800	500	400	350	500	-
HWF-302LED	1.5 Inch	50 mm	603	450	300	280	400	13.0W DC12V
HWF-303LED	2 Inch	63 mm	800	500	400	350	500	14.0W DC12V

MODEL : HK25



Operating Temperature	20~+40°C
Input	AC 100V-220V 50/60Hz
Output	DC 12V/60W
Transmitting Distance	20m





HORBO SPA SERIES




SPA SERIES



Description	Model No.	Material	Lenth (mm)	Width (mm)
Spa Bed	HVTSPA-14	Acrylic	1996	830


Thousands of tiny oxygenated water bubbles surge out from the back of the recliner and wrap around the human body, Forming a water film on the surface of the skin, delicately . caressing the human body's skin and acupoints, on the one hand. It can restore the skin's tension and elasticity and replenish moisture; on the other hand, it can relieve nervousness. Mood, eliminate insomnia and other symptoms.



Description	Model No.	Material	Lenth (mm)	Width (mm)
Massage Seat	HVTSPA-15	Acrylic	950	700




Soak in hot water to quickly open the pores of the human body, and multiple sets of massage nozzles massage the shoulders, back, buttocks, and soles of the human body.



Description	Model No.	Material	Lenth (mm)	Width (mm)
Massage Seat	HVTSPA-09	Acrylic	890	600



Using hot water to soak, the pores of the human body are quickly opened, and multiple sets of massage nozzles are used to massage the human body's legs and back.





SPA SERIES



HVTSPA-05
VICHY SHOWER



HVTSPA-06B
WATER PRESSURE MASSAGE BED
(1860*680MM)



HVTSPA-06A
WATER PRESSURE MASSAGE BED
(1860*680MM)



HVTSPA-17
HYDROTHERAPY BED
(1900*720MM)



HVTSPA-03
SALT BATH HYDROMASSAGE BED
(2150*1060*610MM)



HVTSPA-02
SALT BATH HYDROMASSAGE BED
(2150*1060*610MM)



HVTSPA-01
SALT BATH BED
(2100*1060*570MM)



HVTSPA-05
WATER FOOT MASSAGER
(580*360*480MM)



HVTSPA-11
MASSAGE BED
(1900*600*600MM)





INDUCTIVE CONTROLLER



HVTP-33301

Exquisite Purple Crystal Sensor | $\phi 130 \times 65$
Single Channel Induction Controller (Disk Assembly) | 66x72x115



HVTP-33302

Diamond Purple Crystal Sensor | $\phi 130 \times 70$
Single Channel Induction Controller (Disk Assembly) | 66x72x115



HVTP-33304

Frosted White Crystal Sensor | $\phi 130 \times 65$
Single Channel Induction Controller (Disk Assembly) | 66x72x115



HVTP-33305

Diamond White Crystal Sensor | $\phi 130 \times 90$
Single Channel Induction Controller (Disk Assembly) | 66x72x115



HVTP-338

STAINLESS STEEL & CRYSTAL SENSOR
 $\phi 90 \times 40$



HVTSPA-02

CHROMIUM PLATED ABS & SIWER ABS SENSOR
 $\phi 90 \times 40$



HVTP-340

STAINLESS STEEL INCLINED COLUMN & ABS SENSOR
 $\phi 115 \times 90$




HVTP-33306

UNDER WATER MASSAGE LAMP
 $113 \times 113 \times 81$



HVTP-33311

SMALL DISPLAY SCREEN (WALL HANGING)
 $270 \times 150 \times 30$



HVTP-33309

SMALL DISPLAY SCREEN (CONCEALED INSTALLATION)
 $265 \times 130 \times 30$



HVTP-33310

DOUBLE SIDED DESKTOP DISPLAY SCREEN (TWO SIDES & TWO TEMPERATURE)
 $270 \times 140 \times 100$



HVTP-33312

BIG DISPLAY SCREEN (WALL HANGING)
 $265 \times 270 \times 30$

SPA SERIES



HVT-090
ARC HOOK WATER WATERFALL
600X300MM



HVT-7090
DOLPHIN FOUNTAIN



HVT-092
WATER CURTAIN



HVT-081
WATER CURTAIN



HVT-011B
UNIVERSAL STRENGTH
SHOWER



HVT-030B
DUCK MOUTH
SHOWER



HVT-020B
BARRAGE SHOWER



HVT-031
BACK MASSAGE
SHOWER



HVT-080
HIGH WATERFALL
SCREEN EQUIPMENT
SIZE: 400/500/600MM



HVT-1111B
ROUND BUBBLE BOARD



HVT-0022
WATER MIST NOZZLE



SPA SERIES



HVT-022
FAN SHAPE
SHOWER



HVT-023
UNIVERSAL
PHOENIX
TAIL SHOWER



HVT-030
DUCK MOUTH
IMPACTOR SHAPE
SHOWER




HVT-020
HEAVY RAIN
SHOWER




HVT-011
UNIVERSAL
STRENGTH
SHOWER



HVT-010
UNIVERSAL
AIR JET
SHOWER



HVT-0004
AERATED NOZZLE



HVT-0007
PHOENIX TAIL NOZZLE



HVT-00023
UNIVERSAL JADE CHOPSTICK
SHOWER NOZZLE



HVT-0011
SPRAYING ROUND NOZZLE



HVT-0006
HEAVY RAIN NOZZLE



HVT-0003
UNIVERSAL WATER
HAMMER NOZZLE



HVT-0014
SLIMMING NOZZLE



HVT-0012/13
DUCK MOUTH
SHUP NOZZLE



HVT-0009
FIVE HOLES ROUND NOZZLE



HVT-0010
THREE HOLES ROUND NOZZLE



HVT-0018
SINGLE HOLE BUBBLE NOZZLE



HVT-0019
THREE HOLE BUBBLE NOZZLE



HVT-061
BALL SHAPE
RAIN SHOWER



HVT-062
BALL SHAPE
RAIN SHOWER



HVT-063
BALL UNIVERSAL
HAMMER SHOWER




HVT-064
BALL UNIVERSAL
DUCK SHOWER



HVT-065
NEW HEAVY
RAIN SHOWER




HVT-066
NEW DUCK MONTH
SHAPE SHOWER



HVT-068
DOUBLE
HEAD SHOWER




HVT-111
ROUND BUBBLE SHOWER
SIZE: φ300MM



HVT-110
ROUND SPRAYING SHOWER
SIZE: φ300MM



HVT-112
FOUNTAIN NOZZLE
SIZE: φ300MM



HVT-113
SQUARE BUBBLE SHOWER
SIZE: 350X350MM



HVT-116
FLOATING BATH SPRAY BOARD
SIZE: 350X350MM



HVT-115
SIZE: 250X180MM



HVT-117
HIPS MASSAGE
SIZE: 400X25MM



HVT-120
WATER FOOT HYDRAULIC MASSAGER
SIZE: 350X350MM



HVT-114
RAIN SHOWER
SIZE: 1000X300X100MM



HVT-118
STAINLESS STEEL SPA MASSAGE CHAIR
SIZE: 600X500MM



HVT-121
ACUPUNCTURE SHOWER



HVT-128
BODY MASSAGE SHOWER



HVT-133
BARREL IMPACT



HVT-123
NINE HOLE BUBBLE DEVICE



HVT-122
BATH BRACKET



HVT-067
ACUPUNCTURE SHOWER



SPA SERIES



HVT-137
PATTING BATH
SIZE: 1500X350X1700MM



HVT-136
STAINLESS STEEL AIR BUBBLE BED
SIZE: 1700X600MM




HVT-125
VICHY SHOWER
SIZE: 980X220MM



HVT-119
VICHY SHOWER
SIZE: 2600X1600X200MM



HVT-119
VICHY SHOWER
SIZE: 2000X200MM



HVT-131
WATER LINK



HVT-135B
HAIR COLLECTOR
DN50/DN80/DN100/DN150



HVT-135A
HAIR COLLECTOR
DN50/DN80/DN100/DN150



HVT-135C
HAIR COLLECTOR
DN50/DN80/DN100/DN150



HVT-139
FORCED SHOWER



CARTOON IMPACT BATH



DOLPHIN
HP-04 H=1330MM



PENGUIN
HP-08 H=1330MM



FISH
HP-03 H=1340MM



GOLDEN DRAGON
HP-02 H=1450MM



CLOWN
HP-10



CONCH
HP-09



SEA LION
HP-06 H=1400MM



LITTLE ELEPHANT
HP-07 H=1320MM




HIPPOCAMPI
HP-05 H=1400MM



HVT301
WATER MUSHROOM



HVT302
STAINLESS STEEL
WATER MUSHROOM



HORBO MACHINE ROOM EQUIPMENT





AIR BLOWER



HVTP-002



HVTP-003

FEATURE

- Centrifugal vanes make high pressure, great outflow and low noise.
- High quality engine ensures safe and steady effect. Non-oil lubrication and pure compressed air. Phosphorize disposition, regular coloring and adhesive strength.
- Wide range of power, long life of this machine.

APPLICATION

- To be used in paper cutters, filter cigarette shapers, pulverizingdries, net printers, photo plate makers, liquid-canning machines, electric welding equipment, film machinery, plate makers, liquicanning machines, electric welding equipment, film machinery, papertransporting, clothes dry-cleaning, rinsing, air cleaning, pneumatic conveying, material conveying, collection and so on.

NOTE

- The products must be put at dry and ventilated places abovewater level.

TECHNICAL CHARACTERISTICS

Model	Voltage	Power	Pressure	Vacuum	Output	Pressure	Weight	Dimensions
HXB-550	220v/380v/50Hz	550w	15kPa	-12kPa	95m ³ /h	< 10kPa	10kg	294x288x315mm
HXB-750	220v/380v/50Hz	750w	18kPa	-14kPa	110m ³ /h	< 10kPa	14kg	294x288x315mm
HXB-1100	220v/380v/50Hz	1100w	22kPa	-18kPa	165m ³ /h	< 16kPa	20kg	313x333x339mm
HXB-1500	220v/380v/50Hz	1500w	25kPa	-18kPa	230m ³ /h	< 13kPa	25kg	332x328x358mm
HXB-2200	380v/50Hz	2200w	36kPa	-24kPa	260m ³ /h	< 20kPa	35kg	345x360x371mm
HXB-4000	380v/50Hz	4000w	40kPa	-26kPa	350m ³ /h	< 22kPa	50Kg	434.5x482x440mm



PLATE HEAT EXCHANGER



HVT-P-011

1-10M²
1-10M² PLATE TYPE HEAT EXCHARGER

TECHNICAL CHARACTERISTICS

Model	Exchange Area	In/Outlet Water	WxHxThickness	Maximum Weight
HBR005	0.5-5	40	230x580x (158-300)	70
HBR01	2-10	50	320x860x (472-760)	280
HBR02	8-30	65	410x1180x (660-1060)	590
HBR03	10-60	100	490x1420x (730-1400)	1450

PLATE HEAT EXCHANGER



HVT-P-010I

I TYPE HEAT EXCHANGER

HVT-P-010II

II TYPE HEAT EXCHANGER

HVT-P-010III

III TYPE HEAT EXCHANGER

FEATURE

- Heat Exchanges are highly engineered for fast heating, high capacity and easy use.
- High capacity, multi-tubular heat exchange.
- Primary inlet water circuit(heating agent).
- High efficiency, low energy consumption.

TECHNICAL CHARACTERISTICS

Model	Power (Kw)	Heat Water Flow (l/min)	Cold Water Flow (l/min)	Heat Tranference		Length (mm)	Volume (m ³)
				SQFT	(m ²)		
HMF80	24	20	150	2.0	0.10	310	<30
HMF200	60	30	250	4.6	0.45	590	60-75
HMF400	120	50	360	12.0	1.10	1090	115-175



"3T" WATER HEATER

TECHNICAL CHARACTERISTICS

Item No.	Power (KW)	Inlet/Outlet (Inch)	Voltage (V)	Package (mm) LxWxH
HH-55	5.5	1.5	220/380	500x385x130
HH-75	7.5	1.5	220/380	500x385x130
HH-110	11	1.5	220/380	500x385x130
HH-150	15	1.5	220/380	500x385x130
HH-180	18	1.5	220/380	500x385x130
HH-240	24	2	380	705x390x405
HH-320	32	2	380	705x390x405
HH-360	36	2	380	705x390x405
HH-450	45	2	380	730x400x530
HH-600	60	2	380	730x400x530



HVT-007
"T" WATER HEATER
5.5-60KW/220V/380V

TECHNICAL CHARACTERISTICS

Item No.	Power (KW)	Inlet/Outlet (Inch)	Voltage (V)	Package (mm) LxWxH
HHS-55	5.5	1.5	220/380	500x385x130
HHS-75	7.5	1.5	220/380	500x385x130
HHS-110	11	1.5	220/380	500x385x130
HHS-150	15	1.5	220/380	500x385x130
HHS-180	18	1.5	220/380	500x385x130
HHS-240	24	2	380	705x390x405
HHS-320	32	2	380	705x390x405
HHS-360	36	2	380	705x390x405
HHS-450	45	2	380	730x400x530
HHS-600	60	2	380	730x400x530



HVT-006
"T" WATER HEATER
5.5-60KW/220V/380V



COOL MACHINE



10HP/380V
1450x800x1600mm



8HP/380V
1450x800x1600mm

2HP/220V
3HP/380V
930x650x960mm

5HP/380V
1250x650x1080mm



TECHNICAL CHARACTERISTICS

Model No.	HMD20D	HMD30D	HMD50D	HMD100D	HMD150D	HMD200D
Rated input power (KW)	1.84	2.98	4.6	9.2	11	19
Delivered (KW)	7	14	21	42	50	84
Rated voltage (V)	220	220/380	380	380	380	380
Rated frequency (Hz)			50			
Rated Current (A)	8	13/6	9	18	25	35
Maximum outlet water temperature (°C)			35/45			
Water flow (L/H)	2,000	3,600	5,500	11,000	15,000	22,000
Circulating water pipes (mm)	50	50	50	63	63	75
Dimensions (mm)	1050*350*620	1120*490*710	1120*490*1260	1440*760*1060	1440*760*1060	1990*980*2080
Weight (KG)	75	95	150	300	330	600
Level of security			IPX4			
Electric shock protection grade			One Grade			
Noise (Db)	<40Db	<45Db	<55Db	<60Db	<60Db	-
Refrigerant			R417A/R407C/R22/R404A			
Compressor			-			
Evaporator			Finned heat exchanger			
Condenser			Titanium heat exchanger			
Throttle units			Electric expansion valve			
Defrost	PID defrost, according to the time, fin temperature and environment temperature running state, intelligent defrost					
Control system	Multi-Control					
The test conditions of above parameter	Dry bulb temperature: 20°C Wet bulb temperature: 17°C Inlet water temperature: 15°C					



DEHUMIDIFY UNIT

HDH-504B

- Front air inlet, left side air outlet.
- Defrosting function automatically starts when the ambient temp is below 18°C.
- Intelligent Micro-computer control with Digital Displaying humidity level.
- Four casters make the machine move freely.
- Filter, easy take-down for cleaning.

2.6-3m 40-60m² Applied area: 2.6-3m Height 40-60m²

Voltage / Cycle	Power Input (W)	Compressor	Bucket Capacity (Kg)	Packing Size (mm)	Gross Weight (Kg)
220V/50Hz	920	Rotary	8	530X375X730	32



HDH-504B

HDH-1382B

- Left side air outlet, front air inlet.
- Defrosting function automatically starts when the ambient temp is below 18°C.
- Digital display makes humidity control more freely.
- Four casters make the machine move freely.
- External drainage pipe drains off water continuously.

2.6-3m 140-160m² Applied area: 2.6-3m Height 140-160m²

Voltage / Cycle	Power Input (W)	Compressor	Packing Size (mm)	Gross Weight (Kg)
220V/50Hz	2000	Rotary	710X575X1175	78



HDH-1382B

HDH-1603B

- Upward air outlet, front air inlet.
- Defrosting function automatically starts when the ambient temp is below 18°C.
- Digital display makes humidity control more freely.

2.6-3m 170-200m² Applied area: 2.6-3m Height 170-200m²

Voltage / Cycle	Power Input (W)	Compressor	Packing Size (mm)	Gross Weight (Kg)
220V/50Hz	3220	Rotary	760X565X1910	137



HDH-1603B



HNQ SERIES CHLORINATOR

"HORBO" Saltwater solutions:

Salt chlorinators, are an alternative means of sanitizing your pool with chlorine using the process of electrolysis.



The electrolysis process is achieved by passing the salt water solution through an electrolytic cell which converts sodium chloride (salt) in the water into chlorine gas which, when dissolved in water become sodium hypochlorite (liquid chlorine).

Safe and respecting the environment, this technology brings you:

- Relaxation: Your pool is automatically disinfected.
- Safety: Reduction in chlorine storage and handling.
- Comfort: Clean, safe and crystal-clear water.
- Health and well-being: Therapeutic, saltwater does not irritate eyes and dry out skin.

PRODUCT CHARACTERISTICS

- The chlorine production of HNQ series salt chlorine generator has been improved obviously, and the disinfection of swimming pool is more efficient.
- It can adjust the chlorine production in 6 grades, meet the requirements of swimming pool in different operation periods, save energy and be very environmentally friendly.
- Simple operation, Chinese and English menu function settings, with manual and automatic time control.
- The reactor has the function of forced heat dissipation and automatic reverse pole cleaning. The reactor has the structure of resin protective layer, and the service life of the product is longer.
- HNQ series salt ammonia generator can realize automatic control of swimming pool by uncontrollable circulating water pump (1 set) and underwater lamp (1 set).
- E has the functions of water flow detection, water temperature display, internal overheating protection, salt level prompt, and high-definition OLED display screen.
- There are two optional outlets, which greatly facilitates different management requirements in actual installation.
- Designed removable movable titanium plate structure for easy installation and maintenance.

TECHNICAL CHARACTERISTICS

Model	Dimensions (mm)	(g/h)	Working power supply	(Max)	m ³
HNQ 20	365x260x140	16	AC220-240V/50Hz	250W	≤68
HNQ 30	365x260x140	25	AC220-240V/50Hz	250W	≤105
HNQ 40	365x260x140	33	AC220-240V/50Hz	250W	≤140
HNQ 50	365x260x140	42	AC100-240V/50Hz	250W	≤175

CCOREL 250 SERIES POOL CONTROLLER

HVT-P-024


240x200x120mm



SIMPLE TO OPERATE

The CCOREL 250 ORP/PH Digital Controller automatically maintains both sanitizer ORP(oxidation-reduction potential or redox) and water PH in pools and spas. All operating functions are clearly labeled and accessible from the front panel with safety and easy-reset features not found on other controllers. The default PH control level is 7.0. Below 6.9, the water is too acidic and causes corrosion and eye irritation. Above 7.5, it is too alkaline and causes are irritation plus water cloudiness, scaling, stains and reduced sanitizer efficiency. The default ORP control level is 650mV, values for prevention of germs and bacteria.

Installation of MINDER





SWIMMING POOL EQUIPMENT

**HVT-004**

SIDEKICK-CHLORINE FEEDER

703#

MAXIMUM PRESSURE: 10 BAR
FLOW RATE: 9L/HWORKING TYPE: ELECTRONIC
VOLTAGE: 220V

803#

MAXIMUM PRESSURE: 4 BAR
FLOW RATE: 54L/HWORKING TYPE: ELECTRONIC
VOLTAGE: 220V**HVT-005**SIDEKICK-CHLORINE FEEDER
BLUE WHITE

C-660P

MAXIMUM PRESSURE: 4 BAR
FLOW RATE: 13L/HWORKING TYPE: MECHANICAL
VOLTAGE: 20V


C-6125P

MAXIMUM PRESSURE: 2.1 BAR
YEBFLOW RATE: 30L/HWORKING TYPE: MECHANICAL
VOLTAGE: 220V**HVT-009/HVT-009A**


CL-100

AUTOMATIC CHOLINE/BROMINE
OFF-LINE FEEDER

CL-200

AUTOMATIC CHOLINE/BROMINE
OFF-LINE FEEDER**HVT-008**
AUTOMATIC CHOLINE/BROMINE
OFF-LINE FEEDER**HOM-3834**
SUP & BLUE CLARIFIER**HOM-3835**
SUP & BLUE ALGAECLIDE**HVT-027**
CHLORINE OF SANITIZING**HOM-3836**
ALGAECLIDE
(IMPORTED COPPER SULFATE)**HOM-3837**
PH REGULATOR
25KG**HOM-3838**
PRECIPITATING AGENT
(ALUMINUM CHLORIDE)

- PVC plastic chamber is compatible for fresh water, sea water, chlorine feeder and salt chlorinator.
- Lamp life : 9000 hours of operation, approximate 12 months of continuous service.
- Ballasts : UL, CUL, TUV-CE listed, LED visual & audible alarm, Overheating protection, Instant start.



TECHNICAL CHARACTERISTICS

Model	16ml/cm ² UVT=90%	Dimension (mm) A/B/C/D/E/F	Inlet/Outlet Union (Unit. Inch)	UV Lamp	Output Power	Voltage Power	Designed working pressure	Operation Temperature
HPL-I	162GPM (36612LPH)	765/988/219/ 210/351/305	2"	T585	85w	100-240V 50-60Hz	40 Psi	2-40°C
HPL-II	204GPM (46104LPH)	1065/1288/219/ 210/351/305	2"	T5120	120w	100-240V 50-60Hz	40 Psi	2-40°C

UV GERMICIDAL LAMP



HUVF-60

TECHNICAL CHARACTERISTICS

Power of the modulation tube	Wax water flow rate	Water volume	Using frequency	Applications
30W	540	2000	4.5-22 H/EEEK	Aquarium / Fish pond
40W	740	3000	4.0-20 H/EEEK	Aquarium / Fish pond
50W	1140	5000	4.25 H/EEEK	Aquarium / Fish pond
80W	1740	8000	4.0-20 H/EEEK	Aquarium / Fish pond / pool
160W	3480	16000	2.0-10 H/EEEK	Aquarium / Fish pond
240W	5220	24000	1.2-8 H/EEEK	Aquarium / Fish pond



REMOVING ALGAE WITH UV STERILIZER



HUVA 80W-240W	
Water treatment capacity	10T/H
Size	980*110*270mm
Working pressure	<0.8Mpa
Voltage	220v/50Hz
Power	80w-240W
Caliber	DN40 (external thread)
99.9% Bactericidal rate	99.9% Sterilization rate

HUVF 360W-2160W	
Water treatment capacity	40T/H
Size	1280*165*430mm
Working pressure	<0.8Mpa
Voltage	220v/50Hz
Power	360w~2160W
Caliber	DN80 (external thread)
99.9% Bactericidal rate	99.9% Sterilization rate



OZONE GENERATOR

Main application :

Ozone generator is mainly used in medicine, water, pure water, mineral water, secondary water supply, swimming pool, aquaculture water, food and beverage industries such as water disinfection essence processing, and chemical industry, papermaking industry such as degreasing, bleaching, for life, industry, hospital sewage treatment (sterilization, remove BOD, COD,etc.), as well as the life sewage, industrial cooling water reuse treatment, etc.

Model	Product	LxWxH	Ozone Output	Voltage	Weight (Kg)	Power	
HHY-013	Ozone	80x55x130	80g/h	220V/50Hz	40	1000	
			100g/h		60	1300	
			120g/h		65	1500	
HHY-004		32x25x82	5g/h		11	160	
			10g/h		13	180	
HHY-003	Ozone	40x30x93	20g/h		25	380	
			40g/h		30	400	
Max. Ozone Density							
Max. Ozone Density			80-100mg/L Oxygen Source: 80-100mg/L		15-20mg/L Dry air Source: 15-20mg/L		



HRD
HORBO

HORBO POOL AND SPA ACCESSORIES





POOL AND SPA ACCESSORIES





POOL AND SPA ACCESSORIES



HVTP-602
18/25/30 CM



HVTP-604
18/20/25/30 CM



HVTP-605
18/20/25/30 CM



HVTP-607
18/25/30 CM



HVTP-609
ABS 18/25/30 CM



HVTP-613
30/35/40 CM



HVTP-610
18/20/25 CM



HVTP-617

ALUMINIUM ALLOY GRATINGS




HVTP-616
18/20/25/30 CM



POOL DEPARTURE PLATFORM



HVTP-303
STANDARD ONE-STEP STARTING BLOCK




HVTP-305
STANDARD TWO-STEP STARTING BLOCK



HVTP-301
STANDARD ONE-STEP STARTING BLOCK




HVTP-3011
STANDARD ONE-STEP STARTING BLOCK



Model No.	Specification
HFT 3045	300-45°Fiberglass Corner Tile (White)
HFT 2545	250-45°Fiberglass Corner Tile (White)
HFT 2045	200-45°Fiberglass Corner Tile (White)

45°CORNER TILE FOR GRATING


Model	A	B	H	L
HFT 3045	174	50	28.5	300
HFT 2545	154	50	28.5	250
HFT 2045	133	50	28.5	200



Model No.	Specification
HFT3030	300-90°Fiberglass Corner Tile (White)
HFT2590	250-90°Fiberglass Corner Tile (White)
HFT2090	200-90°Fiberglass Corner Tile (White)

90°CORNER TILE FOR GRATING


Model	A	H	L
HFT3030	350	28.5	300
HFT2590	300	28.5	250
HFT2090	250	28.5	200



Model No.	Specification
HPT 3045	300-45°Fiberglass Corner Tile (White)
HPT 2545	250-45°Fiberglass Corner Tile (White)
HPT 2045	200-45°Fiberglass Corner Tile (White)

NEW 45°CORNER TILE FOR GRATING

Model	A	B	H	L
HPT 3045	174	50	28.5	300
HPT 2545	154	50	28.5	250
HPT 2045	133	50	28.5	200




Model No.	Specification
HFT3030	300-90°Fiberglass Corner Tile (White)
HFT2590	250-90°Fiberglass Corner Tile (White)
HFT2090	200-90°Fiberglass Corner Tile (White)

NEW 90°CORNER TILE FOR GRATING


Model	A	H	L
HPT3090	350	28.5	300
HPT2590	300	28.5	250
HPT2090	250	28.5	200

SKIMMER




Model No.	Colour	Material
HSP0030C	White	ABS+UV

SKIMMER




Model No.	Colour	Material
HSP0030V	White	ABS+UV

SKIMMER




Model No.	Colour	Material
HSP0040C	White	ABS+UV

SKIMMER




Model No.	Colour	Material
HSP0040V	White	ABS+UV

MAIN DRAIN (FOR VINYL POOL)




Model No.	Colour	Material
HSP2850V	White	ABS+UV

MAIN DRAIN (FOR CONCRETE POOL)




Model No.	Colour	Material
HSP2850C	White	ABS+UV

OUTLET FITTING




Model No.	Colour	Material	Connection
HSP2851	White	ABS+UV	1.5 interpolation 2"external

OUTLET FITTING




Model No.	Colour	Material	Connection
HSP2852	White	ABS+UV	1.5

SUCTION NOZZLE



Model No.	Colour	Material	Connection
HSP2853	White	ABS+UV	1.5 interpolation 2"external

SUCTION NOZZLE



Model No.	Colour	Material	Connection
HSP2854	White	ABS+UV	1.5




POOL AND SPA ACCESSORIES

VACUUM FITTING (FOR VINYL POOL)



Model No.	Colour	Material
HSP2827V	White	ABS+UV & PVC

WALL RETURN (FOR VINYL POOL)




Model No.	Colour	Material
HSP2829V	White	ABS+UV & PVC

WALL RETURN





Model No.	Colour	Material
HSP1007V	White	ABS+UV & PVC

MAIN DRAIN




Model No.	Colour	Material
HSP1423	White	ABS+PVC

SUCTION FITTING





Model No.	Colour	Material	Size
HSP1022	White	ABS+UV	1.5"
HSP1022	White	ABS+UV	2" thread

WALL INLET (FOR VINYL POOL)



Model No.	Colour	Material
HSP2828V	White	ABS+UV & PVC

OUTLET FITTING (FOR VINYL POOL)




Model No.	Colour	Material
HSP1006V	White	ABS+PVC

WALL RETURN




Model No.	Colour	Material
HSP1008V	White	ABS+UV & PVC

OUT/INLET FITTING




Model No.	Colour	Material
HSP1425	White	ABS

COVER OF SUCTION FITTING




Model No.	Colour	Material
HSP1022A	White	ABS+UV
HSP1022B	White	ABS+UV

MASSAGE JET




Model No.	Colour	Material
HSP-1434	White	ABS+UV

MASSAGE JET-STAINLESS



Model No.	Colour	Material
HSP-1434S	White	SS304+ABS

EYE BALL SKT




Model No.	Colour	Size	Material
HSP1432	White	DN50/DN63	ABS

WATER RETURN



Model No.	Colour	Size	Material
HSP1433	White	DN50/DN63	ABS

GUTTER DRAIN




Model No.	Colour	Size	Material
HSP1435	White	DN50/DN63	ABS

EYE BALL SKT



Model No.	Colour	Size	Material
HSP1436	White	DN50/DN63	ABS

GUTTER DRAIN




Model No.	Colour	Material
HSP-2819	White	ABS+UV & PVC

WALL RETURN




Model No.	Colour	Material
HSP-2824	White	ABS+UV & PVC

MAIN DRAIN



Model No.	Colour	Material	Specification
HSP1031	White	ABS	9"x9"
HSP1032	White	ABS	12"x12"

MAIN DRAIN




Model No.	Colour	Material	Specification
HSP1035	White	ABS	9"x9"
HSP1036	White	ABS	12"x12"




POOL AND SPA ACCESSORIES

SPRAY NOZZLE




Model No.	Colour	Size	Material
HPL-1419B	White	1.5"/10mm	ABS+UV

SPRAY NOZZLE




Model No.	Colour	Size	Material
HP-1419C	White	1.5"/12.5mm	ABS+UV

SUCCESSIVE SPRAY NOZZLE



Model No.	Specification
HSP2856	Grey 1.5

SPRAY NOZZLE



Model No.	Colour	Material
HSP1450T	White	ABS



HSP-0022
SS SUCTION NOZZLE (SCREW)



HSP-0024
SS SUCTION RETURN (SCREW)



HSP-0029
SS GUTTER DRAIN (SCREW)



HSP-0030
COPPER FLOOR DRAIN



HSP-1030S
MAIN DRAIN



HSP-1031S
MAIN DRAIN



HSP-0022A
MOTOR PNEUMATIC SWITCH



HSP-0022
PLASTIC CHROME PLATING SWITCH



HSP-0023
PLASTIC ADJUST SWITCH



POOL AND SPA ACCESSORIES



HB-158
CONNECTOR
WHITE 3/4"



HF03
TEE
SIZE: DN50, DN63 SOCKET



HF09-90
DEGREE ELBOW
SIZE: DN50, DN63 SOCKET



HN103
1.5"-2"



HN102
2"-15"/1.5"-1"



HN101
1.5" / 2"



HF71
DOUBLE UNION BALL VALVE
SIZE: 1/2"-TO 4" THREAD, SOCKET
1/2"-2": 235PSI MAX.
2-1/2"-4": 150PSI MAX.



HF61
SINGLE UNION BALL VALVE
SIZE: 1/2"-TO 2" THREAD, SOCKET
235PSI MAX



HA-127
NON-RETURN VALVE
WHITE 2"



HA-128
NON-RETURN VALVE



HF-62



HH201
ONE-WAY THREAD UNION



NON-0324



ANCHOR TYPE



HN104
PVC
2"/1.5"/1"



HSP1068
CHACK VALVE



HSP1030
MAIN DRAIN



HSP-1096
SKIMMER




HSP-2855
DISCHARGE JET



PUMP CONNECTION




Non-Slip Vinyl Liner




MODEL	SIZE	THICKNESS
clear blue pool liner	2x25 (40) m	1.2mm
mosaic pool liner	1.83x25 (40) m	1.5mm
dark blue pool liner	1.83x25 (40) m	1.5mm
blue white pool liner	1.83x25 (40) m	1.5mm

Instruction:




1. Inner Frame Of Polyester Weft
2. Highly Resistant PVC

Installation details :



REMARK



Ideal for residential pools. Manufactured in reinforced PVC-P, this material is the most useful for lining pools thanks to enhanced malleability, resistance to tearing, ease of welding, resistance to discoloration by UV rays and with a wide range of available colors.

Made-to-measure liners are put together by high frequency welding machines at our facilities. Perfectly adaptable to any pool design or shape, with excellent watertight features, so you can forget about annoying leaks.

*Ensures total watertightness in odd shaped pools or pools with numerous steps. *Highly flexible and adaptable.

*Smooth and pleasant to touch, it is easy to maintain and durable.

*Highly resistant to impacts and tearing.


*PVC does not release dioxins into the atmosphere and can be recycled.

*Compatible with concrete, prefabricated or steel panel pools. Can also be installed in pools with overflow.




HORBO LADDER SERIES







HSF LADDER							
Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm
HSF-215	502	1330	650	640	180	200	250
HSF-315	502	1580	650	640	180	200	250
HSF-415	502	1830	650	640	180	200	250
HSF-515	502	2080	650	640	180	200	250



HSL LADDER							
Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm
HSL-215	502	1330	650	640	180	200	250
HSL-315	502	1580	650	640	180	200	250
HSL-415	502	1830	650	640	180	200	250
HSL-515	502	2080	650	640	180	200	250




HMU LADDER							
Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm
HMU-215	502	1330	365	640	180	200	250
HMU-315	502	1580	365	640	180	200	250
HMU-415	502	1830	365	640	180	200	250
HMU-515	502	2080	365	640	180	200	250



HSP LADDER							
Item No	Step	A mm	B mm	C mm	D mm	E mm	F mm
HSP2+2	2+2	1150	1380	250	730	420	500
HSP3+3	3+3	1150	1580	250	930	420	500
HSP4+4	4+4	1360	1880	250	1230	420	500
HSP4+4	4+4	1360	1900	250	1350	420	500
HSP5+5	5+5	1700	2120	250	1530	420	500





HLF LADDER										
Model	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	I mm	J mm
HLF215	493	1460	1042	830	190	200	250	561	831	750
HLF315	493	1710	1042	830	190	200	250	811	831	750
HLF415	493	1960	1042	830	190	200	250	1061	831	750
HLF515	493	2210	1042	830	190	200	250	1311	831	750



With polished Stainless Steel pipe ($\phi 42\text{mm}$), this ladder is specially designed for over flow pool with attractive appearance. Easily installed with anchoring or flange fixtures.

HANDRAIL COMPONENT

The following components are for the installation of grad rails around the edge of the pool.



Straight handrails

Polished Stainless Steel AISI 304 or AISI 316.

Handrail length in 1m.

Model: With AISI-304 With AISI-316



Straight bracket with base plate

Polished Stainless Steel AISI 304 or AISI 316.

Applicable for both concrete pool and vinyl pool.





End Cup

Polished Stainless Steel AISI 304 or AISI 316.

For the end of $\phi 42\text{mm}$ pipe.

Model: With AISI-304 With AISI-316






HARB SERIES

Model	Description
HARB-F	Exit Handrail
HARB-F	Exit Handrail



Polished AISI 304 or AISI 316 Stainless Steel (ϕ 42mm) pipe.
Both anchor and



HARC SERIES

Model	Description
HARC	Exit Handrail
HARC	Exit Handrail


Polished AISI 304 or AISI 316 Stainless Steel (ϕ 42mm) pipe.
Both anchor and flange installations are available.



HARG SERIES

Model	Model	Description
HARG	HARG-F	Exit Handrail
HARG	HARG-F	Exit Handrail

Polished AISI 304 or AISI 316 Stainless Steel (ϕ 42mm) pipe. Both anchor and flange installations are available.



HARS SERIES

Model	Model	Description
HARS	HARS-F	Exit Handrail
HARS	HARS-F	Exit Handrail

Polished AISI 304 or AISI 316 Stainless Steel (ϕ 42mm) pipe. Both anchor and flange installations are available.

HORBO CLEANING EQUIPMENT



CLEANING EQUIPMENT

**H3002**

H3002 SUPER EDITION
CABLE LENGTH 30 METERS
CYCLE TIME: 4/6/8 HOURS

**DOLPHIN H3002# CLEANER ROBOT**

CABLE LENGTH 30M, REMOTE CONTROL,
PROGRAMMABLE, CLIMB WALL

**H2V**

DOLPHIN 2X2# CLEANER ROBOT
CABLE LENGTH 45M, REMOTE CONTROL,
PROGRAMMABLE, CLIMB WALL,
BEST CHOICE FOR OLYMPIC POOL

**HHJ-2042L**

AUTOMATIC POOL CLEANER

**HPAC-08**

AUTOMATIC POOL CLEANER
CA REQUIRES A PUMP OF MINIMUM 0. 75HP/550W
(OR MINIMUM FLOW OF 6. 5M3/HR/1700GAL/HR)

**HVTP-51**

MANUAL POOL CLEANER

**HVTP-050**

SS CLEANNING CAR

**HVTP-336**

SS VACCUM HEAD
1000X350MM



CLEANING EQUIPMENT



HPVH-01
TRIANGULAR LINER VAC HEAD W
SWIVEL CUFF



HPVH-06
DELUXE TRIANGULAR TRANSPARENT
CAST IRON WEIGHTED VAC HEAD



HPVH-07
VAC HEAD W/SIDE BRUSHES



HPVH-03
VAC HEAD BRUSHES



HPVH-09
FLEXIBLE VAC HEAD W
SWIVEL BRUSH FOR IG POOL



HPVH-08
FLEXIBLE VAC HEAD
FOR IN-GROUND POOL



HPV-05
14-19" VACUUM HEAD



HPV-03
14-19" VACUUM HEAD



HPVH-17
DELUXE VACUUM
BRUSH W/EASY BUTTON



HPVH-18
DELUXE VACUUM HEAD W
TRANSPARENT COVER & EASY BUTTON



HPVH-16
DELUXE PENTAGONAL VACUUM
HEAD W/EASY BUTTON



HPVH-20
14-19" ALUMINUM FOLDING
VACUUM HEAD W/4 FOLDING PANELS



HPLS-02
PROFESSIONAL ALUMINIUM
LEAF SKIMMER




HPLS-1001
DELUXE LEAF SKIMMER
W/EASY BUTTON



HPDRS-1001
DELUXE DEEP RAKE
W/EASY BUTTON



HPDRS-05
PROFESSIONAL HEAVY DUTY
DEEP RAKE W/ALU FRAME



HPDRS-10
PROFESSIONAL DELUXE DEEP
RAKE W/SQUEEGEE STRIP
AND REPLACEABLE NET



HPLS-01
STANDARD LEAF SKIMMER (BLUE)



HPDRS-04
ECONOMY DEEP BAG RAKE



HPDRS-01
HEAVY DUTY PLASTIC LEAF RAKE
WITH LONG WEARING SCREEN MESH



HPLS-03
HEAVY DUTY PLASTIC
LEAF SKIMMER (BLUE)



HPLSH-02
LEAF SKIMMER WITH
48"/122CM ALUMINUM POLE



CLEANING EQUIPMENT



HPB-04
OVERSIZED POLYBRISTLE
WALL BRUSH W/EZ-CLIP



HPB-11
18'/45CM METAL
BACK WALL BRUSH



HPB-08
18'/45CM STAINLESS
STEEL ALGAE BRUSH



HPB-02
PROFESSIONAL HEAVY DUTY
DEEP RAKE W/ALU FRAME



HPB-03
FLEXIBLE BRUSH W/
ALU HANDLE & EXTRA BRISTLES



HPB-05
10'/26CM POLYBRISTLE
WALL BRUSH



HPB-06
10'/26CM STAINLESS
STEEL ALGAE BRUSH



HPB-07
10'/26CM STAINLESS
STEEL ALGAE BRUSH



HPD-01
DELUXE LARGE CHEMICAL
DISPENSER FOR 3' TABLETS



HPT-13
LARGE SCALE FLOATING
DIAL THERMOMETER



HPT-05
DELUXE ROUND
THERMOMETER W/STRING



HPT-08
JIM BUOY
THERMOMETER W/STRING



HPT-11
FLOATING ANIMAL
THERMOMETER IN 4 STYLES



ELECTRONIC TESTER



HPTK-02
PH.OTO



HPTK-01
BASIC PH & CI TEST KIT(20CC)



HPTK-05
5-WAY TEST KIT (PH/Cl/ALKALINITY/
ACID DEMAND/BROMINE)



HVTP-360
TELESCOPIC POLE
3M/5M/7M/8M/9M



HVTP-361
LIFE SAVING HOOK



HPhR-01
HOSE REEL WITHOUT HOSE



HVTP-362
VACUUM HOSE
912/15/30



HVTP-363
VACUUM HOSE
9/12/15/30




HVTP-364
VACUUM HOSE
2"10




HPCR-01
IN-GROUND POOL COVER REEL W/
SS FRAME FOR ϕ 3-1/4" TUBES



HPCR-02
ABOVE GROUND POOL COVER REEL W/
ABS FRAME FOR ϕ 3-1/4" & 1-1/2" TUBES



Swimming pool tiles are a special high-tech product, available in two types: glazed flat surface and body-colored corrugated surface, with complete specifications and perfect matching. The glaze comes in various colors such as black, white, blue and so on. It is crystal clear and clean, and the corrugated surface has the characteristics of simple and elegant material, non-slip and wear resistance. Designed for long-term immersion in water in swimming pools, it has water pressure resistance, corrosion resistance, excellent hot and cold physical properties, and no chemical reaction to human skin.





HORBO

SAUNA SERIES





After enjoying sauna, you will find that you're relaxed, your body and brain is disentangled from the boring work and saily vexation. Tired, headache has gone with the heat. For the busy modern live, it's a good way for you to relax yourself.

6mm Tempered Glass Secured
Door Bronze Colour With
magnet handle

Thermo-Hidrometer

Sauna Wooden Floor

Special spruce wood with
glass wool isolation wall
panes 7.5cm



Sandglass





Suitable Heater








Spruce Benches





LUXURY COMBINED TYPE SAUNA ROOM







HKV-AC100
900X900X1900MM



HKV-AC200
1200X1000X1900MM



HKV-AC320
1300X1200X2000MM



HKV-AC300
1500X1000X1900MM



HKV-AC400
1800X1200X1900MM



HKV-AC500
1200X1300X2000MM





FARIN FFRARED SWEAT STREAM ROOM SERIES

Model	HKN-001A	HKN-002A	HKN-003A	HKN-004A
Size	90x95x190cm	120x105x190cm	150x115x190cm	180x125x190cm
Voltage	110v/220v	110v/220v	110v/220v	110v/220v
Power	1400w	1700w	2100w	2600w
Material	Spruce wood		Cedar wood	




FARIN FFRARED SWEAT STREAM ROOM SERIES

Model	HKN-001B	HKN-002B	HKN-003B	HKN-004B
Size	90x95x190cm	120x105x190cm	150x115x190cm	180x125x190cm
Voltage	110v/220v	110v/220v	110v/220v	110v/220v
Power	1400w	1700w	2100w	2600w
Material	Spruce wood		Cedar wood	



FARIN FFRARED SWEAT STREAM ROOM SERIES

Model	HKN-001C	HKN-002C	HKN-003C	HKN-004C
Size	90x95x190cm	120x105x190cm	150x115x190cm	180x125x190cm
Voltage	110v/220v	110v/220v	110v/220v	110v/220v
Power	1400w	1700w	2100w	2600w
Material	Spruce wood		Cedar wood	




FARIN FFRARED SWEAT STREAM ROOM SERIES

Model	HKN-001H	HKN-002H	HKN-003H	HKN-004H
Size	90x95x190cm	120x105x190cm	150x115x190cm	180x125x190cm
Voltage	110v/220v	110v/220v	110v/220v	110v/220v
Power	1400w	1700w	2100w	2600w
Material			Cedar wood	

SAUNA HEATER SERIES



Installation dimension




MODEL	Power (kW)	Sauna room			Min.Distance to heater		
		Min.Capacity	Max.Capacity	Height	Min.A from side wall to back wall	Min.Suspension ceiling	Min.B for guard bar and upper stool
HH-105	10.5	9	15	190	12	120	15
HH-135	13.5	11	20	210	16	140	20
HH-165	16.5	16	25	210	16	140	20

Technical Characteristics

Model	Power	Applicable space (m³)
HH-105	10.5KW	9-15
HH-135	13.5KW	10-18
HH-165	16.5KW	14-24



Installation dimension




Distance	4.5KW	6KW	8KW	9KW
A (mm)	35	50	100	120
B (mm)	20	30	30	40
C (mm)	35	50	80	100

Technical Characteristics

Model	Power	Applicable space (m³)
HH-45B	4.5KW	3-6
HH-60B	6.0KW	5-9
HH-80B	8.0KW	8-12
HH-90B	9.0Kw	9-13



Installation dimension




Distance	4.5KW	6KW	8KW	9KW
A (mm)	35	50	100	120
B (mm)	20	30	30	40
C (mm)	35	50	80	100

Technical Characteristics

Model	Power	Applicable space (m³)
HH-45BS	4.5KW	3-6
HH-60BS	6.0KW	5-9
HH-80BS	8.0KW	8-12
HH-90BS	9.0KW	9-13

SAUNA HEATER SERIES


Installation dimension



Model	Power (Kw)	Sauna Room			Min. Distance To Heater		
		Min. Capacity	Max. Capacity	Height	Min. A From Side Wall To Back Wall	Min. Suspension Ceiling	Min. B For Guard Bar and Upper Stool
HSAV-10.5	10.5	9	15	190	12	120	15
HSAV-12	12.0	10	18	210	16	140	20
HSAV-15	15.0	14	24	210	16	140	20
HSAV-18	18.0	15	27	210	20	150	25

Item No.	Model	Power	Applicable Space (m³)
13022	HSAV-10.5	10.5KW	9-15
13023	HSAV-12	12.0KW	10-18
13024	HSAV-15	15.0KW	14-24
13025	HSAV-18	18.0KW	15-27


Installation dimension



Model	Power (Kw)	Sauna Room			Min. Distance To Heater		
		Min. Capacity	Max. Capacity	Height	Min. A From Side Wall To Back Wall	Min. Suspension Ceiling	Min. B For Guard Bar and Upper Stool
HSAV-21	21.0	19	31	220	20	160	25
HSAV-24	24.0	24	38	230	20	170	25
HSAV-27	27.0	30	46	240	20	180	25
HSAV-30	30.0	37	53	240	20	180	25

Item No.	Model	Power	Applicable Space (m³)
13026	HSAV-21	21.0KW	19-31
13027	HSAV-24	24.0KW	24-38
13028	HSAV-27	27.0KW	30-46
13029	HSAV-30	30.0KW	37-53

Installation dimension



Type	Power (Kw)	Sauna Room			Min. Distance To Heater		
		Min. Capacity	Max. Capacity	Height	Min. A From Side Wall To Back Wall	Min. Suspension Ceiling	Min. B For Guard Bar and Upper Stool
-	10.5	9	15	190	12	120	15
-	12.0	10	18	210	16	140	20
-	15.0	14	24	210	16	140	20

Item No.	Model	Power	Applicable Space (m³)
61006	HSA-105	10.5KW	9-15
61007	HSA-120	12.0KW	10-18
61008	HSA-150	15.0KW	14-24
61009	HSA-180	18.0KW	15-27



SAUNA HEATER SERIES

HJM



Installation dimension

Sauna heater	A	C	D
3KW	50	280	80
3.6KW			

Item No.	Model	Power	Applicable Space (m³)
13021	HJM-30BS	3.0KW	2-4
13022	HJM-36BS	3.6KW	2-4

Being light and elegant, it is applicable for luxurious VIP room and households. There are coated and full stainless steel casings available for customers

HSCA



Installation dimension

Sauna Heater Distance	3KW	4.5KW	6KW	8KW	9KW
A (mm)	50	80	100	130	130
C (mm)	280	280	280	300	300
D (mm)	80	100	150	200	200

Item No.	Model	Power	Applicable Space (m³)
13001	HSCA-03A	3.0KW	2-4
13002	HSCA-4.5A	4.5KW	3-6
13003	HSCA-06A	6.0KW	5-9
13004	HSCA-08A	8.0KW	8-12
13005	HSCA-09A	9.0KW	9-13

HSCA



Installation dimension

Sauna Heater Distance	3KW	4.5KW	6KW	8KW	9KW
A (mm)	50	80	100	130	130
C (mm)	280	280	280	300	300
D (mm)	80	100	150	200	200

Item No.	Model	Power	Applicable Space (m³)
B13001	HSCA-B-03A	3.0KW	2-4
B13002	HSCA-B-4.5A	4.5KW	3-6
B13003	HSCA-B-06A	6.0KW	5-9
B13004	HSCA-B-08A	8.0KW	8-12
B13005	HSCA-B-09A	9.0KW	9-13



SAUNA ACCESSORIES



HSCA-1000W



HSCA-1500W



HSCA-2000W



HSCA-2670W



HSCA-3000W




HSAV-1500W



HSAV-2000W



HSAV-2500W



HSAV-3000W



HSAA-2000W



HSAWO-2000W



HSAWO-2700W



HSAWO-3000W



HSAWO/SA-1500W



HSAWO/SA-2000W



HXN-01 / HXN-02
3-9KW / 9-15KW
OUTSIDE CONTROL PANEL




HSX-01 / HSX-02
3-9KW / 9-15KW
OUTSIDE DIGITAL CONTROL PANEL



HX-01
EXTERNAL CONTROL ADAPTER



HVK-01 / HVK-02
3-9KW / 12-15KW
CONTROL PANEL



HGS-A2016
SAUNA CONTROLLER CIRCUIT



HGS-A2018
SENSOR UNIT



HGS-A2019
TIMER



HGS-A2020
CONTACTOR



HGS-A2017
THERMOSTAT



HKS-1115
WOODEN DRUM AND SPOON



HKS-1114
WOODEN DRUM AND SPOON



HKS-1112
WOODEN DRUM AND SPOON



HKS-1101
WOODEN DRUM AND SPOON



HKS-1102
WOODEN DRUM AND SPOON



HKS-2402
LAMP SHADE



HKS-2403
LAMP SHADE



HKS-2404
LAMP SHADE



HKS-2405
LAMP SHADE



HKS-2406
LAMP SHADE



HKS-2407
LAMP SHADE



HKS-2408
LAMP SHADE



HKS-2409
LAMP SHADE



HKS-2410
LAMP SHADE



HK-021
SAUNA WOOD LAMP SHADE



HK-022
SAUNA WOOD LAMP SHADE



HKS-2015
WOODEN TEMPERATURE
AND MOISTURE METER



HKS-2016
WOODEN TEMPERATURE
AND MOISTURE METER



HKS-2017
WOODEN TEMPERATURE
AND MOISTURE METER



HKS-2018
WOODEN TEMPERATURE
AND MOISTURE METER




HKS-2019
WOODEN TEMPERATURE
AND MOISTURE METER



HKS-2020
WOODEN TEMPERATURE
AND MOISTURE METER



HKS-2021
WOODEN TEMPERATURE
AND MOISTURE METER



HKS-2022
WOODEN TEMPERATURE
AND MOISTURE METER





HKS-2001
WOODEN TEMPERATURE
MOISTURE METER



HKS-2003
WOODEN TEMPERATURE
MOISTURE METER



HKS-2004
WOODEN TEMPERATURE
MOISTURE METER



HKS-2005
WOODEN TEMPERATURE
MOISTURE METER




HKS-2006
WOODEN TEMPERATURE
MOISTURE METER



HKS-2002
WOODEN TEMPERATURE
MOISTURE METER



HKS-2010
WOODEN TEMPERATURE
MOISTURE METER



HKS-2008
WOODEN TEMPERATURE
MOISTURE METER



HKS-2012
WOODEN TEMPERATURE
MOISTURE METER



HKS-2014
WOODEN TEMPERATURE
MOISTURE METER



HK-018
WOODEN TEMPERATURE
MOISTURE METER




HK-020
WOODEN CLOCK



HKS-2506
WOODEN CLOCK



HK-015
WOODEN TEMPERATURE
MOISTURE METER



HK-017
WOOD-FRAME TEMPERATURE



HK-033
SAUNA ROOM VENTILATION



HKS-2502
SAUNA ROOM VENTILATION



HKS-2503
SAUNA ROOM VENTILATION



HKS-2504
SAUNA ROOM VENTILATION



HKS-2505
SAUNA ROOM VENTILATION



HK-035
SAND TIMER



HKS-2507
SAND TIMER




HKS-2508
SAND TIMER



HKS-2511
SAND TIMER



HKS-2510
SAND TIMER






HORBO


STEAM ROOM SERIES



STEAM ROOM	
Model	Size (mm)
H6A	2460*1800*2150
H8A	3050*1800*2150
H10A	3640*1800*2150
H12A	4230*1800*2150
H14A	4280*1800*2150
H16A	5410*1800*2150
H2B	1260*1020*2150
H4B	1800*1280*2150
H6B	1800*1870*2150
H8B	1800*2460*2150
H10B	1800*3050*2150
H12B	1800*3740*2150
H14B	1800*4230*2150
H16B	1800*4820*2150
H10C	2500*2120*2250
H12C	3080*2120*2250
H14C	3660*2120*2250
H16C	4240*2120*2250
H18C	4900*2120*2250
H20C	5480*2120*2250
H4D	2120*1340*2250
H6D	2120*1340*2250
H7D	2120*1920*2250
H8D	2120*1920*2250
H10D	2120*2500*2250
H12D	2120*3080*2250
H14D	2120*3660*2250
H2G	1270*1340*2250
H12E	2500*3100*2200
H16E	3700*3100*2200
H18E	4300*3100*2200
H20E	4900*3100*2200
H8F	3100*1300*2200
H10F	3100*1900*2200
H12F	3100*2500*2200
H14F	3100*3100*2200
H16F	3100*3700*2200
H18F	3100*4300*2200
H20F	3100*4900*2200



The structure of steam room





Material: Tempered glass, Acrylic
304Stainless steel / Aluminium alloy



Control system: Smart control system

Function: Intelligent touch screen wireless control panel, FM radio CD player, MP3, Temperature / Time adjusting with top light, 4.5kw steam generator, Lock function, Moveable thermotherapy shower tap

Others:

1. Frame Color (Black, Grey)
2. Plate Material option: Imported Acrylic, Chinese Acrylic
3. Steam generator option: Imported steam generator
4. Installation accessories.

Product Structure:



HKDL-02A

Product Size: 1310x1140x2150mm



Material: Tempered glass, Acrylic 304Stainless steel/ Aluminium alloy


Control system: Smart control system

Function: Temperature/Time adjusting, top light, 4.5-18KW steam generator

Others:

1. Frame Color (Black,Grey)
2. Plate Material option: Imported Acrylic, Chinese Acrylic
3. Steam generator option: Imported steam generator
4. Installation accessories.


Product Structure:



HKDL-06B

Product Size: 2250x1320x2150mm


Product Structure:



HKDL-08B

Product Size: 2250x1920x2150mm


Product Structure:




HKDL-10B

Product Size: 2250x2520x2150mm


MORE PRODUCT STRUCTURE




Size: 2250x3120x2150mm




Size: 2250x3720x2150mm




Size: 2250x4320x2150mm



Size: 2250x4920x2150mm



Size: 2250x5520x2150mm



Size: 2250x6120x2150mm

TECHNICAL CHARACTERISTICS



Model	Power (kw)	Voltage (V)	Current (A)	Room (m³)	AWG	Dimensions	Gross weight
HST-30	3.0	200-240	13.6	2.5-5	3*11	300*130*230	6Kg
HST-40	4.0	200-240	18.2	5-6	3*10		
HST-50	5.0	200-240	22.7		3*9		
		380-415	9.1		5*13	395*135*395	10.5-11
HST-60	6.0	200-240	27.3	6-7	3*8		
		380-415	9.1		5*13		
HST-70	7.0	200-240	31.8	7-9	3*8		
		380-415	11.4		5*12		
HST-80	8.0	200-240	36.4	9-10	3*7	445*135*395	15.6-16.2
		380-415	13.6		5*11		
HST-90	9.0	200-240	41	10-12	3*7		
		380-415	13.6		5*11		
HST-105	10.5	380-415	16	12-15	5*11		
HST-120	12.0	380-415	18	15-18	5*10		
HST-150	15.0	380-415	23	18-21	5*9		
HST-180	18.0	380-415	27.3	21-24	5*8	500*200*520	15.6-18



TECHNICAL CHARACTERISTICS

Model	Power (kw)	Voltage (V)	Dimensions (mm)	Applicable space (m³)
HHA-40	4.0	220/380	210*650*430	5
HHA-60	6.0	220/380	210*650*430	6
HHA-80	8.0	220/380	210*650*430	8
HHA-90	9.0	220/380	210*650*430	9
HHA-120	12	380	260*650*600	12
HHA-150	15	380	260*650*600	15
HHA-180	18	380	260*650*600	18



TECHNICAL CHARACTERISTICS

Model	Power (kw)	Voltage (V)	Current (A)	Room (m³)	AWG	Dimensions	Gross weight
HDON-45	4.5	200-240	20	3-5	3*10		
		380-415	7		5*14		
HDON-60	6.0	200-240	27.3	6-7	3*8	530*225*410	14
		380-415	9		5*13		
HDON-90	9.0	200-240	41	10-12	3*7		
		380-415	14		5*11		
HDON-105	10.5	200-240	16	12-15	5*11		
HDON-120	12.0	380-415	18	15-18	5*10		
HDON-150	15.0	380-415	23	18-21	5*9	530*225*470	19
HDON-180	18.0	380-415	27.3	21-25	5*8		


HORBO

LEISURE FURNITURE SERIES





LEISURE FURNITURE SERIES



HTYS-004



HTYS-005



HTYS-003

HORBO

SPA HOT TUB

SERIES





SPA HOT TUB SERIES

HJY-8605



Dimensions	5850x2200x1500mm
Capacity	11000L
Seating	2 seats
Dry Weight	1500 kg
Filled Weight	11000L
Total Jets	24pcs



EQUIPMENT	
Counter Current Pump	1x2.8KW/380V
High Performance Pumps	1x2HP
Circulation Pump	1x1.0HP
9-speed flow controller	1pc
LED Light	1pc
Ozone	1pc
Plastic wood skirt LED light	1pc
Inlet/outlet	1pc
Sand filter P400	1pc
Cartridge filter	1pc
Headrest	2pcs
Fiberglass Base Tray	1pc





SPA HOT TUB SERIES

HJY8801



Dimensions	6900x2220x1550mm
Capacity	9000L
Seating	2 seats
Dry Weight	1600kg
Filled Weight	9000kg
Total Jets	24pcs

EQUIPMENT

Counter Current Pump	1X2.8KW / 380V
High Performance Pumps	1X2HP
Circulation Pump	1X1HP
Heater	1X3KW
LED Light	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	2pc
Headrest	2pc
Sand Filter P400 (Options)	
9-speed flow controller	1pc



HJY8601



Dimensions	5870x2200x1520mm
Capacity	7600L (Approx)
Seating	5 seats + 1 Lounger
Dry Weight	1275kg (Approx)
Filled Weight	8000kg (Approx)
Total Jets	59pcs

EQUIPMENT

High Performance Pumps	2x2HP, 2x3HP
Circulation Pump	2x0.5HP
Heater	2x3kw
LED Light	2pc
Blower	400W
Aroma therapy	1pc
Ozone	1pc
Controller	2pcs
Synthetic Cabinet	1pc
Drain	1pc
Filtration Sie	1pc
High Density Foam Insulation	1pc
Headrest	5pcs



HJY8602



Dimensions	5850x2200x1600mm
Capacity	8500L (Approx)
Seating	4 seats
Dry Weight	1300kg
Filled Weight	11000Kg
Total Jets	53pcs

EQUIPMENT

High Performance Pumps	3x3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	2pcs



Dimensions	5700x2240x1520mm
Capacity	7600L
Seating	2 seats
Dry Weight	1275Kg
Filled Weight	8000Kg
Total Jets	46pcs

EQUIPMENT

High Performance Pumps	3x3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	2pcs
Fiberglass Base Tray	1pc
Lockable Thermo Hard Cover	1pc
Treated Timber Frame	1pc





SPA HOT TUB SERIES

HJY8603



Dimensions	4180x2200x1430mm
Capacity	5600L (Approx)
Seating	2 seats
Dry Weight	1000kg
Filled Weight	6500kg
Total Jets	33pcs
EQUIPMENT	
High Performance Pumps	3x3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pcs
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	2pcs



HJY8801-A



Dimensions	5870x2280x1520mm
Capacity	7600L
Seating	2 seats + 1 Lounger
Dry Weight	1275kg
Filled Weight	8000kg
Total Jets	61 pcs
EQUIPMENT	
High Performance Pumps	3x3HP
Circulation Pump	2x0.5HP
Heater	2x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	2pcs
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc



HJY8803



Dimensions	4560x2240x1420mm
Capacity	5600L
Seating	3 seats
Dry Weight	1000kg
Filled Weight	6500kg
Total Jets	43pcs
EQUIPMENT	
High Performance Pumps	3x3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	2pcs
Fiberglass Base Tray	1pc
Lockable thermo Hard Cover	1pc
Treated Timber Frame	1pc



HJY8001



Dimensions	4000x2200x950mm
Capacity	3000L
Seating	6 seats + 2 loungers
Dry Weight	860kg
Filled Weight	4230kg
Total Jets	118pcs
EQUIPMENT	
High Performance Pumps	2X3HP, 1x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	2pcs
High Density Foam Insulation	1pc
Headrest	1pcs
Fiberglass Base Tray	1pc





SPA HOT TUB SERIES

HJY8005



Dimensions	2100x1050x760mm
Capacity	600L
Seating	2 seats
Dry Weight	180kg
Filled Weight	780kg
Total Jets	23pcs

EQUIPMENT	
High Performance Pumps	1x2HP 2speed
Heater	4x2kw
LED Light	1pc
Blower	300W
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	2pcs
Fiberglass Base Tray	1pc



Dimensions	2100x1050x760mm
Capacity	600L
Seating	1 Lounger
Dry Weight	180Kg
Filled Weight	780Kg
Total Jets	23pcs

EQUIPMENT	
High Performance Pumps	1x2HP 2speed
Heater	1x2kw
LED Light	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
Headrest	1pc
Fiberglass Base Tray	1pc



HJY8006



Dimensions	2100x1650x790mm
Capacity	950L
Seating	2 Loungers + 1seat
Dry Weight	300kg
Filled Weight	1250kg
Total Jets	24pcs

EQUIPMENT	
High Performance Pumps	1x3HP 2speed
Heater	1x3kw
LED Light	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	2pcs
Fiberglass Base Tray	1pc

Dimensions	2000x2000x900mm
Capacity	1400L
Seating	4 seats + 1 Lounger
Dry Weight	350kg
Filled Weight	1750kg
Total Jets	33pcs

EQUIPMENT	
High Performance Pumps	1x3HP
Circulation Pump	41x0.5HP
Heater	1x3kw
LED Light	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc



SPA HOT TUB SERIES

HJY8007



Dimensions	2200x2200x930mm
Capacity	1250L
Seating	3 Seats + 2 Loungers
Dry Weight	380kg
Filled Weight	1630kg
Total Jets	42pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8805



Dimensions	2180x1600x880mm
Capacity	1100L
Seating	2 seats + Lounger
Dry Weight	280kg
Filled Weight	1380kg
Total Jets	46pcs

EQUIPMENT

High Performance Pumps	1x3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	300W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8008



Dimensions	2200x2200x930mm
Capacity	1280L
Seating	5seats + 1 Lounger
Dry Weight	380 Kg
Filled Weight	1660 g
Total Jets	45pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8806



Dimensions	2180x1950x880mm
Capacity	1480L
Seating	4 seats
Dry Weight	380kg
Filled Weight	1950kg
Total Jets	41pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc



SPA HOT TUB SERIES

HJY8807



Dimensions	2130x2130x880mm
Capacity	1480L
Seating	3 seats + Lounger
Dry Weight	350kg
Filled Weight	1950kg
Total Jets	57pcs

EQUIPMENT

High Performance Pumps	2X3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	1pc
Fiberglass Base Tray	1pc

HJY8808



Dimensions	2130x2130x880mm
Capacity	1500L
Seating	8 seats
Dry Weight	380kg
Filled Weight	1900kg
Total Jets	52pes

EQUIPMENT

High Performance Pumps	2X3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8809



Dimensions	2130mmx2130mmx880mm
Capacity	1480L
Seating	3 seats + 2 Loungers
Dry Weight	380Kg
Filled Weight	1950Kg
Total Jets	57pcs

EQUIPMENT

High Performance Pumps	2x3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8810



Dimensions	2130x2130x880mm
Capacity	1450L
Seating	4 seats + 1 Lounger
Dry Weight	380Kg
Filled Weight	1880Kg
Total Jets	2pcs

EQUIPMENT

High Performance Pumps	2x3HP
Circulation Pump	41x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc



SPA HOT TUB SERIES

HJY8811



Dimensions	2250x2250x880mm
Capacity	1500L
Seating	3 seats + 2 Loungers
Dry Weight	380Kg
Filled Weight	1900Kg
Total Jets	69pcs

EQUIPMENT

High Performance Pumps	2x3HP
Circulation Pump	4x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8812



Dimensions	2250x2250x860mm
Capacity	1450L
Seating	5 seats + 1 Lounger
Dry Weight	380kg
Filled Weight	1880kg
Total Jets	76pcs

EQUIPMENT

High Performance Pumps	2x3HP
Circulation Pump	4x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8011



Dimensions	2200x2200x940mm
Capacity	1480L
Seating	4 seats + 1 Lounger
Dry Weight	350kg
Filled Weight	1950Kg
Total Jets	50pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	4x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8012



Dimensions	2200x2200x940mm
Capacity	1480L
Seating	3 seats + 2 Loungers
Dry Weight	380kg
Filled Weight	1950kg
Total Jets	61pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	4x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc



SPA HOT TUB SERIES

HJY8002



Dimensions	2880x2200x950mm
Capacity	2030L
Seating	4 seats + 2 Loungers
Dry Weight	450kg
Filled Weight	2860kg
Total Jets	68pcs

EQUIPMENT

High Performance Pumps	2x3HP
Circulation Pump	41x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8009



Dimensions	1830x1230x700mm
Capacity	800L
Seating	2 Loungers + 1 seat
Dry Weight	190kg
Filled Weight	900kg
Total Jets	17pcs

EQUIPMENT

High Performance Pumps	1x2HP 2speed
Heater	1x2kw
LED Light	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Headrest	1pc

HJY8003



Dimensions	2350x2350x950mm
Capacity	1700L
Seating	3 seats + 2 Loungers
Dry Weight	400kg
Filled Weight	2200kg
Total Jets	59pcs

EQUIPMENT

High Performance Pumps	2x3HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam insulation	1pc
Headrest	3pc
Fiberglass Base Tray	1pc

HJY8013



Dimensions	2100x1550x860mm
Capacity	1100L
Seating	2 seats + 1 Lounger
Dry Weight	280g
Filled Weight	1380Kg
Total Jets	39pcs

EQUIPMENT

High Performance Pumps	4x2HP
Circulation Pump	4x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	300W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc



SPA HOT TUB SERIES

HJY8015



Dimensions	2200x2200x940mm
Capacity	1500L
Seating	7 Seats
Dry Weight	380kg
Filled Weight	1900kg
Total Jets	42pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	4pcs
Fiberglass Base Tray	1pc

HJY8016



Dimensions	2200x2200x940mm
Capacity	1450L
Seating	5 seats + 1 Lounger
Dry Weight	380Kg
Filled Weight	1880Kg
Total Jets	44pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8017



Dimensions	2200x2200x940mm
Capacity	1550L
Seating	4 seats + 1 Lounger
Dry Weight	380Kg
Filled Weight	1920Kg
Total Jets	59pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater 1818	1x3kw
LED Light	1pc
Blower	400w
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc

HJY8018



Dimensions	2200x2200x940mm
Capacity	1500L
Seating	5 seats + 2 Loungers
Dry Weight	380kg
Filled Weight	1900kg
Total Jets	69pcs

EQUIPMENT

High Performance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Headrest	3pcs
Fiberglass Base Tray	1pc



SPA HOT TUB SERIES

HJY8010



Dimensions	2200x2200x240mm
Capacity	1400L
Seating	6 seats
Dry Weight	380kg
Filled Weight	1780kg
Total Jets	44pcs

EQUIPMENT

High Perfomance Pumps	2x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	300W
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam insulation	1pc
Headrest	4pcs
Fiberglass Base Tray	1pc

HJY8808



Dimensions	1900x1900x940mm
Capacity	1450L
Seating	4 seats
Dry Weight	360kg
Filled Weight	1920g
Total Jets	16pcs

EQUIPMENT

High Performance Pumps	1x2HP
Circulation Pump	1x0.5HP
Heater	1x3kw
LED Light	1pc
Blower	400W
Aromatherapy	1pc
Ozone	1pc
Controller	1pc
Synthetic Cabinet	1pc
Drain	1pc
Filtration	1pc
High Density Foam Insulation	1pc
Fiberglass Base Tray	1pc

CONTROL PANEL



CANADIAN GECKO CONTROL SYSTEM



AMERICAN BALBOA CONTROL SYSTEM



P23B32 SPA CONTROL



P15B66 SPA CONTROL

ACRYLIC SHELL



6427 Silver
white marble



6615 Summer
sapphire



6696 White
pearllescent



6811 Oceanwave



6878 Midnight



6256 Mayan
copper



6240 Mediterranean
sunset



9814 Gypsum

SYNTHETIC CABINET COLORS



TAKE COLOR



GREY



RED BROWN



COFFEE



PT. INDOTARA PERSADA

Our Marketing Office and After Sales Service Center

Head Office

50/F, Menara BCA Grand Indonesia
Jl. M.H. Thamrin No.1
Jakarta Pusat 10310
021 - 5011 2229
dwt@indotara.id



Semarang Office

Wisma HSBC Lt. 6 Suite 609
Jl. Gajah Mada No.135
Semarang, Jawa Tengah 50134
021 - 5011 2229
smg.dwt@indotara.id

Marketing Office

APL Tower 6th Floor No. 6 Central Park,
Jl. Letjen S. Parman Kav 28,
Jakarta Barat - 11440
021 - 5011 2229
dwt@indotara.id



Medan Office

Sutomo Tower Lantai 5H
Jl. Sutomo Ujung No.28,
Kota Medan, Sumatera Utara 20235
021 - 5011 2229
mdn.dwt@indotara.id

Graha Indotara

Millenium Industrial Estate
Jl. Millenium 22 Blok R3 No. 1
Cikupa, Tangerang - Banten 15720
021 - 5011 2229
dwt@indotara.id



Makassar Office

Fajar Graha Pena Lt. 5
Jl. Urip Sumoharjo No. 20,
Makassar - South Sulawesi 90234
021 - 5011 2229
mks.dwt@indotara.id

Bandung Office

Wisma HSBC Lt. 6 Suite B
Jl. Asia Afrika No. 116
Bandung, Jawa Barat 40112
021 - 5011 2229
bdg.dwt@indotara.id



Balikpapan Office

Panin Tower Lt. 8 - Grand Sudirman
Jl. Jendral Sudirman No.7 Klandasan Ilir,
Balikpapan Kota, Kalimantan Timur 76114
021 - 5011 2229
bpp.dwt@indotara.id

Surabaya Office

Japfa Indoland Center, Tower I Lt. 10/1008
Jl. Jendral Basuki Rahmat 129-137
Surabaya 60271
021 - 5011 2229
sby.dwt@indotara.id



Bali Office

Benoa Square Lt. 2
Jl. Bypass Ngurah Rai No. 21 A Kedonganan,
Kuta Badung - Bali Indonesia 80361
021 - 5011 2229
bali.dwt@indotara.id

Yogyakarta Office

Hartono Mall Yogyakarta Lt. 3
Kaliluwu, Condongcatur,
Sleman, Yogyakarta 55281
021 - 5011 2229
yog.dwt@indotara.id



Singapore Office

Marina Bay Financial Centre Tower 3
17F, 12 Marina Boulevard
Singapore - 018982
021 - 5011 2229
sing.dwt@indotara.id