

ROTLEP

H E A V Y D U T Y

SEMI TRAILER

POWERFULL PERFORMANCE ON EVERY ROAD



Easy
To Install



Large Load
Capacity



High
Durability

HEAVY DUTY
CONTAINER
SEMI TRAILER

Type
RCS60-12.5



High
Durability



Easy To
Install



Heavy Load
60 Ton

Rotler container semi trailer is a heavy load that has high durability, safe and reliable operation. With a beautiful appearance, rotler container semi trailer is quite easy to assemble, with welding and bolting.

SPECIFICATIONS

Model	RCS60-12.5
Overall Length	12500mm
Overall Width	2500
Overall Height	1550
Fifthwheel Height	1300
Tare Weight	7000kg
Payload	60000kg
Main Beam	2pcs, Material T700, tensile strength 700MPa, "I" shape, Thickness: upper board "I" 12mm, middle board "I" 8mm, bottom board "I" 14mm.
Cross Beam	Material T980, bended square steel board, 4mm thick, 14pcs
Bottom Platform	Diamond pattern steel board, thickness 3mm
King Pin	2" or 3.5"
Landing Gear	28tons * 2pcs, with T shoe. Crank handle is located on the driver's side of the chassis.
Twist Locks	12pcs
Axle	3x16tons standard axles with cast hubs
Suspension	Mechanical Suspensions with leaf springs 10Layers, width 90mm, thickness 13mm, 1 air suspension
Tire	12R22.5 * 12pcs
Rim	9.0x22.5 * 12pcs
Painting	Primer Coat, Polyurethane paint
Marks	All marks and signs as per customers' requirement
Electric System	24V, with all LED lights.
Brake System	Air brake, 6 chambers, air reservoir 2 pcs
Others	Reflection tape, side lamp, rubber mud flab, document holder

HEAVY DUTY
FLATBED
SEMI TRAILER

Type **RCS60-12.5**



Customized
Size



High
Durability



Strong
Suspension



Heavy Load
60 Ton

Rotler flatbed semi trailer is a heavy load that has light weight, reasonable structure, strong and reliable strength to support larger impact loads. Not only that, the length and width of flatbed semi trailer can be customized.

SPECIFICATIONS

Model	RFS60-12.5
Overall Length	12500mm
Overall Width	2500
Overall Height	1550
Fifthwheel Height	1300
Tare Weight	7500kg
Payload	60000kg
Main Beam	2pcs, Material T700, tensile strength 700MPa, "I" shape, Thickness: upper board "--" 12mm, middle board "I" 8mm, bottom board "_" 14mm.
Side Beam	160mm channel steel
Cross Beam	Material T980, bended square steel board, 4mm thick, 14pcs
Bottom Platform	Diamond pattern steel board, thickness 3mm
King Pin	3.5"
Landing Gear	28tons * 2pcs, with T shoe. Crank handle is located on the driver's side of the chassis.
Twist Locks	12pcs
Axle	3x16tons standard axles with cast hubs
Suspension	Mechanical Suspensions with leaf springs 10Layers, width 90mm, thickness 13mm, 1 air suspension
Tire	12R22.5 * 12pcs
Rim	9.0x22.5 * 12pcs
Painting	Primer Coat, Polyurethane paint
Marks	All marks and signs as per customers' requirement
Electric System	24V, with all LED lights.
Brake System	Air brake, 8 chambers, air reservoir 2 pcs
Others	Reflection tape, rubber mud flab, document holder

HEAVY DUTY
SIDE DUMP
SEMI TRAILER



Easy To Install



Durability Product



Heavy Load
60 Ton



Strong
Suspension

Rotler side dump semi trailer is a transport load that has high durability which can provide the strongest performance of the semi trailer. The capacity that can be transported is also quite large, so it can transport heavier loads.

SPECIFICATIONS

Overall Dimension	13000*2600*3800mm
Dump Box Dimension	12500*2500*1800mm
Curb Weight(KG)	9,500
Max Payload(KG)	80,000
Bottom Plate	8mm
Side Plate	4mm
Axle	3 x 20 tons
Suspension	3 Mechanical Suspensions
Tire	12R22.5 *12units
Volume	58CBM
Main Beam	Upper plate 16mm, bottom plate 18mm, middle plate 10mm, Mainbeam height 500mm
Unloading Method	Lateral unloading from both sides
King Pin	90#
Landing Gear	28tons, Steel
Hydraulic Cylinder	6+1, Good Quality HYLW Brand
Brake System	3 double and 2 chambers, air reservoir 2 pcs.
Leaf Spring	10 pieces
Electical System	24V, LED
Tool Box	1 unit, Iron material
Spare Tire Rack	1 unit
Accessories Ladder	Factory Standard
Marks	All marks and signs as per customers' requirement.
Painting	Primer Coat, Polyurethane paint
Color	Blue
Others	Reflection tape, rubber mud flab, document holder

◀ HEAVY DUTY ▶

ROTLER

3 AXLE LOWBED

SEMI TRAILER



High Load Capacity



Versatile Configurations



Durability and Longevity



SPECIFICATION

Overall Length	13500mm
Overall Width	3000mm
Loading Deck Height	1200mm
Fifthwheel Height	1300
Tare Weight	10000kg
Payload	80000kg
Main Beam	2pcs, Material T700, tensile strength 700MPa, "工" shape, Thickness: upper board "--" 12mm, middle board "l" 10mm, bottom board "_" 16mm.
Side Beam	Channel Steel
Cross Beam	Material T980, Banded Square Steel Board, 4mm Thick
Bottom Platform	Diamond Pattern Steel Board, Thickness 3mm
King Pin	3.5"
Landing Gear	28tons * 2pcs, with T shoe. Crank handle is located on the driver's side of the chassis.
Rear Ramp	2 rear ramps
Axle	3x16tons standard axles with cast hubs
Suspension	Mechanical Suspensions with leaf springs 10Layers, width 90mm, thickness 13mm
Tire	12R22.5 * 12pcs
Rim	9.0x22.5 * 12pcs
Painting	Primer Coat, Polyurethane paint
Marks	All marks and signs as per customers' requirement.
Electric System	24V, with all LED lights
Brake System	Air brake, 8 chambers, air reservoir 2 pcs
Others	Reflection tape, rubber mud flab, document holder

HEAVY DUTY CAR CARRIER TRAILER



High Load Capacity

Durability and Longevity

Versatile Configurations



SPECIFICATION	
WEIGHT & DIMENSIONS	
Overall Dimension (L*W*H)	17,000*2,500*3,800mm
Loading Height	4,500mm
Max Payload	8 cars
Wheelbase	11,610+1,360+1,300mm
Fifth Wheel Height	1,305mm
CHASSIS	
Axle	FUWA brand * 2
Suspension	2 axle air suspension , FUWA brand
Tires	245/70R19.5, equip 8pcs per chassis+ 2 units spare tire Linglong band
Rim	7.5x19.5 * 10pcs
Main Beam	Height strength carbon steel, welded together via automatic submerged-arc welding
Cross Beam	High Strength square pipe or channel steel
Floor	Checked steel plate, thickness 3mm
King Pin	50# or 90# optional
Landing Gear	28tons, double speed
Painting	Complete chassis sand blasting, double primer coating, double polyurethane painting
BODY	
Main Structure	Overall skeletal structure, Hydraulic lifting double-deck
Hydraulic System	High quality hydraulic system
Rear Ramps	Both floors are with rear extendable double ramps by 1200mm
Operation System	6 handlers with operation instruction
BRAKE & ELECTRIC SYSTEM	
Brake System	2 lines air brake system with 2 air tanks, WABCO emergency relay valve, 4 brake chambers and slack adjusters
ABS	Yes
Electric System	A. 24V LED lights, 7 pin electric connectors. B. Parking, stop, reverse, turning and indicator lights Conform to european standard and 3C certificate. C. Front, side and rear reflectors.
ACCESSORY	
Color and Logo	According to customer's requirement
Spare Tire Rack	1pc
Tool Box	1pc

HEAVY DUTY HIGH FENCE SEMI TRAILER

ROTLER



Versatile
Configurations



Durability
and Longevity



Enhanced
Maneuverability



SPECIFICATION

Overall Dimension	13000 x 2500 x 3400mm
Fifth Wheel Height	1150mm
Tare Weight	8 tons
Loading Capacity	70 tons
Main Beam	Height 500mm, "I" shape, Thickness: upper board "--" 12mm, middle board "I" 8mm, bottom board "_" 14mm.
Suspensions	3 mechanical Suspensions
Axles	3 x 16 tons mechanical axles
Floor	3mm, Diamond pattern steel board
Side Wall	600mm, corrugated steel board
Side Fence	1200mm
Tires	12R22.5 tires * 12pcs
King Pin	2.0" or 3.5"
Landing Gear	28tons * 2pcs, with T shoe. Crank handle is located on the driver's side of the chassis.
Rope Hook	14 pieces per side
Spare Tire Rack	1 pc
Tool Box	1 pc
Painting	Primer Coat, Polyurethane paint
Logo	All marks and signs as per customers' requirement.
Electric System	24V, with all LED lights.
Brake System	Air brake, 8 chambers, air reservoir 2 pcs.
Others	Reflection tape

◀ HEAVY DUTY ▶ REAR DUMP TRAILER

ROTLEP



Versatile
Configurations



Enhanced
Maneuverability



Durability
and Longevity



SPECIFICATION

Model	MXH9400ZZV
Brand	CH
Overall Dimension	10300*2600*3600mm
Tipper Box Dimension	9700*2400*1800mm
Curb Weight (KG)	10,200
Max Payload (KG)	80,000
Bottom Plate	8mm
Side Plate	6mm
Volume	42CBM
Main Beam	Upper plate 12mm, bottom plate 14mm, middle plate 8mm, Main beam height 500mm
Paint	Primer Coat, Polyurethane paint
Tarpauline	1pc
Tire	12R22.5 *16units
Rim	90-16 thickness
Axle	One air axle, 3 x 16 tons mechanical axles
King Pin	90#
Suspension	Front one- Air Suspension, Rear three- Mechanical Suspensions
Landing Gear	28tons, Steel
Hydraulic System	Good Quality HYLW Brand
Brake System	4 double and 2 chambers, air reservoir 2 pcs.
Leaf Spring	13 pieces. Width 120mm Thickness 16mm
Electrical System	24V, LED
Tool Box	1 unit, Iron material
Spare Tire Rack	2 units
Front Lifting Cylinder	R214#-1sh
Color	Customized

INDOTARA®

PT. INDOTARA PERSADA

Our Marketing Office and After Sales Service Center



Head Office

50/F, Menara BCA Grand Indonesia
Jl. M.H. Thamrin No.1
Jakarta Pusat 10310

021 - 5011 2224
dhe@indotara.id



Semarang Office

Wisma HSBC Lt. 6 Suite 609
Jl. Gajah Mada No.135
Semarang, Jawa Tengah 50134

024 - 40 300 889
smg.dhe@indotara.id



Bali Office

Benoa Square Lt. 2
Jl. Bypass Ngurah Rai No. 21 A Kedonganan,
Kuta Badung - Bali Indonesia 80361

021 - 5011 2224
bali.dhe@indotara.id



Marketing Office

APL Tower 6th Floor No. 6 Central Park,
Jl. Letjen S. Parman Kav 28,
Jakarta Barat - 11440

021 - 5011 2224
dhe@indotara.id



Medan Office

Sutomo Tower Lantai 5H
Jl. Sutomo Ujung No.28,
Kota Medan, Sumatera Utara 20235

061 - 50 300 592
mdn.dhe@indotara.id



Singapore Office

Marina Bay Financial Centre Tower 3
17F, 12 Marina Boulevard
Singapore - 018982

021 - 5011 2224
sing.dhe@indotara.id



Graha Indotara

Millenium Industrial Estate
Jl. Millenium 22 Blok R3 No. 1
Cikupa, Tangerang - Banten 15720

021 - 5011 2224
dhe@indotara.id



Makassar Office

Fajar Graha Pena Lt. 5
Jl. Urip Sumoharjo No. 20,
Makassar - South Sulawesi 90234

021 - 5011 2224
mks.dhe@indotara.id



Yogyakarta Office

Hartono Mall Yogyakarta Lt. 3
Kaliwaru, Condongcatur,
Sleman, Yogyakarta 55281

021 - 5011 2224
yog.dhe@indotara.id



Bandung Office

Wisma HSBC Lt. 6 Suite B
Jl. Asia Afrika No. 116
Bandung, Jawa Barat 40112

021 - 5011 2224
bdg.dhe@indotara.id



Balikpapan Office

Panin Tower Lt. 8 - Grand Sudirman
Jl. Jendral Sudirman No.7 Klandasan Ilir,
Balikpapan Kota, Kalimantan Timur 76114

021 - 5011 2224
bpp.dhe@indotara.id



Surabaya Office

Japfa Indoland Center, Tower I Lt. 10/1008
Jl. Jendral Basuki Rahmat 129-137
Surabaya 60271

031 - 3360 1485
sby.dhe@indotara.id