

ROTLEP

H E A V Y D U T Y

SEMI TRAILER

POWERFULL PERFORMANCE ON EVERY ROAD



Easy
To Install



Large Load
Capacity



High
Durability

ROTLER

HEAVY DUTY
CONTAINER
SEMI TRAILER

Type
RCS60-12.5



High
Durability



Easy To
Install



Heavy Load
60 Ton

Rotler container semi trailer is a heavy load that has high durability, safe and reliable operation. With a beautiful appearance, rotler container semi trailer is quite easy to assemble, with welding and bolting.

SPECIFICATIONS

Model	RCS60-12.5
Overall Length	12500mm
Overall Width	2500
Overall Height	1550
Fifthwheel Height	1300
Tare Weight	7000kg
Payload	60000kg
Main Beam	2pcs, Material T700, tensile strength 700MPa, "I" shape, Thickness: upper board "I" 12mm, middle board "I" 8mm, bottom board "I" 14mm.
Cross Beam	Material T980, bended square steel board, 4mm thick, 14pcs
Bottom Platform	Diamond pattern steel board, thickness 3mm
King Pin	2" or 3.5"
Landing Gear	28tons * 2pcs, with T shoe. Crank handle is located on the driver's side of the chassis.
Twist Locks	12pcs
Axle	3x16tons standard axles with cast hubs
Suspension	Mechanical Suspensions with leaf springs 10Layers, width 90mm, thickness 13mm, 1 air suspension
Tire	12R22.5 * 12pcs
Rim	9.0x22.5 * 12pcs
Painting	Primer Coat, Polyurethane paint
Marks	All marks and signs as per customers' requirement
Electric System	24V, with all LED lights.
Brake System	Air brake, 6 chambers, air reservoir 2 pcs
Others	Reflection tape, side lamp, rubber mud flab, document holder

HEAVY DUTY
FLATBED
SEMI TRAILER

Type **RCS60-12.5**



Customized
Size



High
Durability



Strong
Suspension



Heavy Load
60 Ton

Rotler flatbed semi trailer is a heavy load that has light weight, reasonable structure, strong and reliable strength to support larger impact loads. Not only that, the length and width of flatbed semi trailer can be customized.

SPECIFICATIONS

Model	RFS60-12.5
Overall Length	12500mm
Overall Width	2500
Overall Height	1550
Fifthwheel Height	1300
Tare Weight	7500kg
Payload	60000kg
Main Beam	2pcs, Material T700, tensile strength 700MPa, "工" shape, Thickness: upper board "--" 12mm, middle board "I" 8mm, bottom board "_" 14mm.
Side Beam	160mm channel steel
Cross Beam	Material T980, bended square steel board, 4mm thick, 14pcs
Bottom Platform	Diamond pattern steel board, thickness 3mm
King Pin	3.5"
Landing Gear	28tons * 2pcs, with T shoe. Crank handle is located on the driver's side of the chassis.
Twist Locks	12pcs
Axle	3x16tons standard axles with cast hubs
Suspension	Mechanical Suspensions with leaf springs 10Layers, width 90mm, thickness 13mm, 1 air suspension
Tire	12R22.5 * 12pcs
Rim	9.0x22.5 * 12pcs
Painting	Primer Coat, Polyurethane paint
Marks	All marks and signs as per customers' requirement
Electric System	24V, with all LED lights.
Brake System	Air brake, 8 chambers, air reservoir 2 pcs
Others	Reflection tape, rubber mud flab, document holder

ROTLEP

HEAVY DUTY
SIDE DUMP
SEMI TRAILER

Type **RCS60-12.5**



Easy To Install



Durability Product



Heavy Load 60 Ton



Strong Suspension

Rotler side dumb semi trailer is a transport load that has high durability which can provide the strongest performance of the semi trailer. The capacity that can be transported is also quite large, so it can transport heavier loads.

SPECIFICATIONS

Model	RSS80-13
Overall Dimension	13000*2600*3800mm
Dump Box Dimension	12500*2500*1800mm
Curb Weight(KG)	9,500
Max Payload(KG)	80,000
Bottom Plate	8mm
Side Plate	4mm
Axle	3 x 20 tons
Suspension	3 Mechanical Suspensions
Tire	12R22.5 *12units
Volume	58CBM
Main Beam	Upper plate 16mm, bottom plate 18mm, middle plate 10mm, Main beam height 500mm
Unloading Method	Lateral unloading from both sides
King Pin	90#
Landing Gear	28tons, Steel
Hydraulic Cylinder	6+1, Good Quality HYLW Brand
Brake System	3 double and 2 chambers, air reservoir 2 pcs.
Leaf Spring	10 pieces
Electical System	24V, LED
Tool Box	1 unit, Iron material
Spare Tire Rack	1 unit
Accessories Ladder	Factory Standard
Marks	All marks and signs as per customers' requirement.
Painting	Primer Coat, Polyurethane paint
Color	Blue
Others	Reflection tape, rubber mud flab, document holder

INDOTARA®

PT. INDOTARA PERSADA

Our Marketing Office and After Sales Service Center



Head Office

50/F, Menara BCA Grand Indonesia
Jl. M.H. Thamrin No.1
Jakarta Pusat 10310

021 - 5011 2224

dhe@indotara.id



Marketing Office

APL Tower 6th Floor No. 6 Central Park,
Jl. Letjen S. Parman Kav 28,
Jakarta Barat - 11440

021 - 5011 2224

dhe@indotara.id



Graha Indotara

Millenium Industrial Estate
Jl. Millenium 22 Blok R3 No. 1
Cikupa, Tangerang - Banten 15720

021 - 5011 2224

dhe@indotara.id



Bandung Office

Wisma HSBC Lt. 6 Suite B
Jl. Asia Afrika No. 116
Bandung, Jawa Barat 40112

021 - 5011 2224

bdg.dhe@indotara.id



Semarang Office

Wisma HSBC Lt. 6 Suite 609
Jl. Gajah Mada No.135
Semarang, Jawa Tengah 50134

024 - 40 300 889

smg.dhe@indotara.id



Medan Office

Sutomo Tower Lantai 5H
Jl. Sutomo Ujung No.28,
Kota Medan, Sumatera Utara 20235

061 - 50 300 592

mdn.dhe@indotara.id



Makassar Office

Fajar Graha Pena Lt. 5
Jl. Urip Sumoharjo No. 20,
Makassar - South Sulawesi 90234

021 - 5011 2224

mks.dhe@indotara.id



Balikpapan Office

Panin Tower Lt. 8 - Grand Sudirman
Jl. Jendral Sudirman No.7 Klandasan Ilir,
Balikpapan Kota, Kalimantan Timur 76114

021 - 5011 2224

bpp.dhe@indotara.id



Bali Office

Benoa Square Lt. 2
Jl. Bypass Ngurah Rai No. 21 A Kedonganan,
Kuta Badung - Bali Indonesia 80361

021 - 5011 2224

bali.dhe@indotara.id



Singapore Office

Marina Bay Financial Centre Tower 3
17F, 12 Marina Boulevard
Singapore - 018982

021 - 5011 2224

sing.dhe@indotara.id



Yogyakarta Office

Hartono Mall Yogyakarta Lt. 3
Kaliwaru, Condongcatur,
Sleman, Yogyakarta 55281

021 - 5011 2224

yog.dhe@indotara.id



Surabaya Office

Japfa Indoland Center, Tower I Lt. 10/1008
Jl. Jendral Basuki Rahmat 129-137
Surabaya 60271

031 - 3360 1485

sby.dhe@indotara.id