









35-98



99-108



----- 109-114



115-120



120-138







COFFEE MACHINES FOR PROFESSIONAL & COMMERCIAL USE

ROHS . BSCI EMC CB LFGB ISO9001





COMMERCIAL **MACHINE SERIES**

A strong mix of innovation and elegance, that satisfies every lover of real Italian coffee and suits any environment. These semi-automatic professional

coffee machines will be applicable in office, Ho, Re, Ca etc.





LED LAMP



DIGITAL DISPLAY



MANUAL CONTROL



HOT WATER



STEAM CONTROL **CHART**



STEAM



COFFEE



COFFEE HEATING POT BODY



COFFEE HEATING TUBE



COFFEE TABLE



MENU SETTINGS



PRIMARY AND **SECONDARY BOILER**



LIGHTING CONTROL



POWER CONTROL





















Model:	FCM3208	
Description:	 Stainless steel mirror housing; Multifunction for making coffee, steam and hot water at the same time; Resistive colorful touch screen with 4.3 inches; Commercial rotary vane pump with 9bar pressure; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Dual boilers: one is 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is full s. s. primary and secondary boiler with 7L capacity for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S. S. steam and water tube for cappuccino and hot water; With flowmeter and full inner cooper pipe; Top cover cup-warming plate & Adjustable non-slip foot; Level type steaming switch. 	
Power Consumption	3450W	
Voltage	220V	
Frequency	50Hz	
N.W	33KG/PCS	
G.W	37KG/CTN	
Unit Size	616*504*500mm	
CTN Size	702*523*530mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	81PCS	
Loading Capacity(40'GP)	171PCS	
Loading Capacity(40'HQ)	228PCS	









FCM3100C



























Description:	 Stainless steel mirror housing & plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Italian ULKA pump with 15bar pressure; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee Different barometers show the pressure when making coffee and steam; Dual boilers: one is 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is 7L s.s. boiler for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S. S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & Adjustable non-slip foot.
Power Consumption	3450W
Power Consumption Voltage	3450W 220V
Voltage	220V
Voltage Frequency	220V 50Hz
Voltage Frequency N.W	220V 50Hz 33KG/PCS
Voltage Frequency N.W G.W	220V 50Hz 33KG/PCS 37KG/CTN
Voltage Frequency N.W G.W Unit Size	220V 50Hz 33KG/PCS 37KG/CTN 616*504*500mm
Voltage Frequency N.W G.W Unit Size CTN Size	220V 50Hz 33KG/PCS 37KG/CTN 616*504*500mm 702*523*530mm
Voltage Frequency N.W G.W Unit Size CTN Size Package	220V 50Hz 33KG/PCS 37KG/CTN 616*504*500mm 702*523*530mm 1PCS/CTN



























沿





Model:	FCM3100E	
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commerical rotary vane pump with 9 bar pressure; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee Different barometers show the pressure when making coffee and steam; Dual boilers: one is 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is full or s. s. primary and secondary boiler with 7L capacity for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; With flowmeter and full inner cooper pipe; Top cover cup-warming plate & adjustable non-slip foot. 	
Power Consumption	3450W	
Voltage	220V	
Frequency	50Hz	
N.W	35KG/PCS	
G.W	40KG/CTN	
Unit Size	616*504*500mm	
CTN Size	702*523*530mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	126PCS	
Loading Capacity(40'GP)	255PCS	
Loading Capacity(40'HQ)	317PCS	



































Model:	FCM3120C	
Description:	 Stainless steel mirror housing & plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commercial rotary vane pump with 9bar pressure; Inlet pipe to connect tap water & drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Triple boilers: two 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is 12L s.s. boiler for making steam and hot water; Professional s.s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & adjustable non-slip foot. 	
Power Consumption	4900W	
Voltage	220V	
Frequency	50Hz	
N.W	43KG/PCS	
G.W	48KG/CTN	
Unit Size	816*504*565mm	
CTN Size	902*523*530mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	94PCS	
Loading Capacity(40'GP)	184PCS	
Loading Capacity(40'HQ)	224PCS	









COMMERCIAL MACHINE SERIES | ferralli ferra























Model:	Stainless steel mirror housing & plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commerical rotary vane pump with 9 bar pressure; Inlet pipe to connect tap water & drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 500ml heating tube to make temperature more stable for making coffee; another is 12L s.s. primary and secondary boiler for making steam and hot water; Professional s.s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; With flowmeter and full inner cooper pipe; Top cover cup-warming plate & adjustable non-slip foot.	
Description:		
Power Consumption	3800W	
Voltage	220V	
Frequency	50Hz	
N.W	45KG/PCS	
G.W	50KG/CTN	
Unit Size	816*504*565mm	
CTN Size	885*516*685mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	84PCS	
Loading Capacity(40'GP)	171PCS	
Loading Capacity(40'HQ)	171PCS	









FCM3103













Model:















Power Consumption 3450W Voltage 220V Frequency 50Hz N.W 35KG/PCS G.W 40KG/CTN Unit Size 616*504*500mm CTN Size 702*523*530mm	Description:	 Stainless steel mirror housing & plastic side cover; Resistive colorful touch screen with 4.3 inches; Multifunction for making coffee, steam and hot water at the same time; Commercial rotary vane pump with 9bar pressure; Inlet pipe to connect tap water & drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Dual boilers: one is 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is full s. s. primary and secondary boiler with 7L capacity for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S. S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & Adjustable non-slip foot; Level type steaming switch. 	
Frequency 50Hz N.W 35KG/PCS G.W 40KG/CTN Unit Size 616*504*500mm	Power Consumption	3450W	
N.W 35KG/PCS G.W 40KG/CTN Unit Size 616*504*500mm	Voltage	220V	
G.W 40KG/CTN Unit Size 616*504*500mm	Frequency	50Hz	
Unit Size 616*504*500mm	N.W	35KG/PCS	
	G.W	40KG/CTN	
CTN Size 702*522*520mm	Unit Size	616*504*500mm	
01N 3/26 //02 323 330/////	CTN Size	702*523*530mm	
Package 1PCS/CTN	Package	1PCS/CTN	
Loading Capacity(20'GP) 126PCS	Loading Capacity(20'GP)	126PCS	
Loading Capacity(40'GP) 255PCS	Loading Capacity(40'GP)	255PCS	
Loading Capacity(40'HQ) 317PCS	Loading Capacity(40'HQ)	317PCS	















简

மு















Model:	FCM3203	
Description:	 Stainless steel mirror housing & Plastic side cover; Dual resistive colorful touch screen with 4.3 inches; Multifunction for making coffee, steam and hot water at the same time; Commerical rotary vane pump with 9 bar pressure; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is full s. s. primary and secondary boiler with 12L capacity for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S. S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & Adjustable non-slip foot; Level type steaming switch. 	
Power Consumption	4900W	
Voltage	220V	
Frequency	50Hz	
N.W	45KG/PCS	
G.W	50KG/CTN	
Unit Size	816*504*565mm	
CTN Size	885*516*685mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	84PCS	
Loading Capacity(40'GP)	171PCS	
Loading Capacity(40'HQ)	171PCS	





























	FCM3101	
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commerical rotary vane pump with 9 bar pressure; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee. Different barometers show the pressure when making coffee and steam; Dual boilers: one is 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is full or s. s. primary and secondary boiler with 7L capacity for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; With flowmeter and full inner cooper pipe; Top cover cup-warming plate & adjustable non-slip foot. 	
Power Consumption	3000W	
Voltage	220V	
Frequency	50Hz	
N.W	35KG/PCS	
G.W	40KG/CTN	
Unit Size	616*580*565mm	
CTN Size	683*550*685mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	96PCS	
Loading Capacity(40'GP)	204PCS	
Loading Capacity(40'HQ)	204PCS	









COMMERCIAL MACHINE SERIES | ferralli ferra





















☆□



Model:	FCM3201	
Description:	 Stainless steel mirror housing & plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commerical rotary vane pump with 9 bar pressure; Inlet pipe to connect tap water & drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 500ml heating tube to make temperature more stable for making coffee; another is 12L s.s. primary and secondary boiler for making steam and hot water; Professional s.s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; With flowmeter and full inner cooper pipe; Top cover cup-warming plate & adjustable non-slip foot. 	
Power Consumption	3800W	
Voltage	220V	
Frequency	50Hz	
N.W	45KG/PCS	
G.W	50KG/CTN	
Unit Size	816*580*565mm	
CTN Size	885*550*685mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	72PCS	
Loading Capacity(40'GP)	156PCS	
Loading Capacity(40'HQ)	156PCS	































Model:	FCM 3121	FCM3121A
Description:	 Multifunction for making of Touch electronic button for Italian pump with 15bar pound boilers: one is 550m stable for making coffee; Inter pipe to connet tap word button for making coffee; Inter pipe to connet tap word button button button for making coffee; Inter pipe to connet tap word button button button for making coffee; Inter pipe to connet tap word button button for professional s. s. porta-fi With LED illuminator; Pre-infusion system to end S.s. steam and water tub 	using & plastic side cover; coffee, steam and hot water at the same time; or easy operation; oressure (commercial pump with 9bar pressure for optional) al. s. s. boiler with s. s. heating tube to make temperature more another is 5.25L s.s. boiler for making steam and hot water; vater&drain pipe to drain water directly; w the pressure of coffee and steam; liter holder and filter with 58mm diameter; house perfect extraction and crema; se for cappuccino and hot water; olate & Adjustable non-slip foot.

Power Consumption	3050W;3200W	
Voltage	220V/50Hz	
N.W/G.W	26.5kg/29.5kg/PCS; 27.5kg/30.5kg/PCS	
Unit Size/CTN Size	478*578*520mm / 550*676*508mm	
Package	1PCS/CTN	
Loading Capacity 20'GP	132PCS	
Loading Capacity 40'GP	264PCS	
Loading Capacity 40'HP	264PCS	















COMMERCIAL MACHINE SERIES ferratti ferra



















%□





Model:	FCM3122	FCM3122A
Description:	 Stainless steel mirror housing & plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Italian pump with 15bar pressure (commercial pump with 9bar pressure for option Dual boilers: one is 550ml s. s. boiler with s. s. heating tube to make temperature in stable for making coffee; another is 5.25L s.s. boiler for making steam and hot wa 1.7L removable water reservoir; With a barometer, can know the pressure when making coffee; Professional s. s. porta-filter holder and filter with 58mm diameter; With LED illuminator; Pre-infusion system to ensure perfect extraction and crema; S.s. steam and water tube for cappuccino and hot water; Removable drip tray for easy cleaning; Also can connect drain pipe to drain water directly; Top cover cup-warming plate & Adjustable non-slip foot. 	

	Power Consumption	2700VV;2850VV
	Voltage	220V/50Hz
	N.W/G.W	25kg/PCS; 27.5kg/PCS
	Unit Size/CTN Size	324*522*442mm / 428*567*545mm
	Package	1PCS/CTN
	Loading Capacity 20'GP	220PCS
	Loading Capacity 40'GP	442PCS
	Loading Capacity 40'HP	444PCS















RELIABLE GUARANTEED























Model:	FCM3200	FCM3200C
Description:	 1.7L removable water rese With a barometer, can knoth Professional s. s. porta-filte With LED illuminator; Pre-infusion system to ens S.s. steam and water tube Removable drip tray for ea Top cover cup-warming pla Optional: FCM3200C Multi boilers: one thermo-b 	offee, steam and hot water; easy operation; essure; in can make coffee and steam at the same time; rvoir; with the pressure when making coffee; er holder and filter with 58mm diameter; ure perfect extraction and crema; for cappuccino and hot water; sy cleaning; ite & Adjustable non-slip foot. locks are for making coffee and hot water; ting Aluminium boiler for making steam;

Power Consumption	3000W;2950W
Voltage	220V/50Hz
N.W/G.W	16kg/PCS; 18.5kg/PCS
Unit Size/CTN Size	345*485*432mm / 420*580*510mm
Package	1PCS/CTN
Loading Capacity 20'GP	220PCS
Loading Capacity 40'GP	418PCS
Loading Capacity 40'HP	484PCS















RELIABLE GUARANTEED























Model:	FCM3200B	FCM3200D
Description:	 1.7L removable water reservence With a barometer, can knowence Professional s. s. porta-filterence With LED illuminator; Pre-infusion system to ensurence S.s. steam and water tube for Removable drip tray for easyence Top cover cup-warming plate Optional: FCM3200D 	ee, steam and hot water; easy operation; sure; can make coffee and steam at the same time; voir; the pressure when making coffee; holder and filter with 58mm diameter; ere perfect extraction and crema; or cappuccino and hot water; y cleaning; e & Adjustable non-slip foot. ecks are for making coffee and hot water; the oth one is 1 iller for making steam;

Power Consumption	2700W;2650W
Voltage	220V/50Hz
N.W/G.W	16kg/PCS; 18.5kg/PCS
Unit Size/CTN Size	345*485*432mm / 420*580*510mm
Package	1PCS/CTN
Loading Capacity 20'GP	220PCS
Loading Capacity 40'GP	418PCS
Loading Capacity 40'HP	484PCS















RELIABLE GUARANTEED

























Model:

FCM3107

Description

- · Stainless steel mirror housing;
- · Multifunction for making coffee, steam and hot water at the same time;
- · Resistive colorful touch screen with 4.3 inches;
- · Commercial rotary vane pump with 9bar pressure;
- · Inlet pipe to connect tap water & Drain pipe to drain water directly;
- · With LED illuminator; Temperature and time can be adjusted when making coffee;
- · Different barometers show the pressure when making coffee and steam;
- Dual boilers: one is 550ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is full s. s. primary and secondary boiler with 5.25L capacity for making steam and hot water;
- · Professional s. s. porta-filter holder and filter with 58mm diameter;
- Pre-infusion system to ensure perfect extraction and crema;
- · S. S. steam and water tube for cappuccino and hot water;
- · With flowmeter and full inner copper pipe;
- · Top cover cup-warming plate & Adjustable non-slip foot;
- · Lever type steaming switch.

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	88KG / PCS
Unit Size/CTN Size	870*730*775 mm
Package	1PCS / CTN
Loading Capacity	



(20'GP/40'GP/40'HQ)







































Model:	FCM3207
Description:	 Stainless steel housing and artificial marble side panel; Multifunction for making coffee, steam and hot water at the same time; Resistive colorful touch screen with 4.3 inches; Commercial rotary vane pump with 9 bar pressure; Inlet pipe to connect tap water and drain pipe to drain water directly; With LED illuminator, adjustable temperature and flow rate; Different barometers show the pressure when making coffee and steam; Triple boilers: two 550ml S.S boilers with s. s. heating tube to make temperature another is full ss primary and secondary boiler with 10.5L capacity for making steam and hot water; Professional S.S porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; Removable drip tray for easy cleaning; also can connect drain pipe directly; With flow meter and full inner cooper pipe; Auto hot water and lever type steam function; Auto pressure release to protect the machine; Top cover cup-warming plate and adjustable non-slip foot. FCM3207A: Pressure adjustable rotary vane pump (9 bar)
Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	88KG / PCS
Unit Size/CTN Size	870*730*775 mm
Package	1PCS / CTN



Loading Capacity

(20'GP/40'GP/40'HQ)



28PCS / 56PCS / 56PCS





























Model:

FCM3202

Description

- · Stainless steel mirror housing;
- · Multifunction for making coffee, steam and hot water at the same time;
- · Resistive colorful touch screen with 4.3 inches;
- · Commercial rotary vane pump with 9bar pressure;
- Inlet pipe to connect tap water & Drain pipe to drain water directly;
- · With LED illuminator; Temperature and time can be adjusted when making coffee;
- · Different barometers show the pressure when making coffee and steam;
- · Triple boilers: two 550ml S.S boilers with s.s. heating tube to make temperature another is full ss primary and secondary boiler with 10.5L capacity for making steam and hot water;
- · Professional s. s. porta-filter holder and filter with 58mm diameter;
- Pre-infusion system to ensure perfect extraction and crema;
- · S. S. steam and water tube for cappuccino and hot water;
- · With flowmeter and full inner copper pipe;
- · Top cover cup-warming plate & Adjustable non-slip foot;
- · Lever type steaming switch.

Power Consum	ption 42	200W
Voltage	22	20V~50Hz
N.W/G.W	11	9KG/PCS;155KG/PCS
Unit Size/CTN	Size 98	30*680*590*mm / 1070*780*760mm
	12.2	

Package 1PCS/CTN 28PCS/56PCS/56PCS Loading Capacity (20'GP/40'GP/40'HQ)







































Model:	FCM3226
Description:	 Stainless steel housing; 10.5L S.S primary and secondary boiler and double E61 brewing head with electronic Control; Connecting tap water Rotary vane pump (9 bar); Dual pressure gauge, dual temperature and time display; PID temperature control technology; Touch button operation or manual lever operation to make coffee; Multifunction for automatic hot water and double manual steam; Copper pipe connection; With automatic pressure relief protection device; With drainage function; Removable drip tray; Cup warmer design

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	57.6 Kg / 67.4 Kg
Unit Size/CTN Size	700*450*510*mm / 900*650*710mm
Package	1PCS/CTN
Loading Capacity	75PCS/156PCS/208PCS
(20'GP/40'GP/40'HQ)	















RELIABLE GUARANTEED























Model:	FCM3245
Description:	 Stainless steel housing; 10.5L S.S primary and secondary boiler and double E61 brewing head with electronic Connecting tap water Rotary vane pump (9 bar); Dual pressure gauge, dual temperature and time display; PID temperature control technology; Touch button operation or manual lever operation to make coffee; Multifunction for automatic hot water and double manual steam; Copper pipe connection; With automatic pressure relief protection device; With drainage function; Removable drip tray; Cup warmer design

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	57.8KG/67.6KG
Unit Size/CTN Size	700*450*510mm / 900*650*710mm
Package	1PCS/CTN
Loading Capacity	75PCS/156PCS/208PCS
(20'GP/40'GP/40'HQ)	

































Model:	FCM3143 Le Gazzio Singola
Description:	 Stainless steel housing with white or black color painting. One 550ml S.S coffee boiler and 5.5L S.S steam boiler for making steam and hot water; With inlet water pipe to connect tap water; Rotatory pump; Different barometers show the pressure of coffee and steam; Multifunction for automatic hot water and manual steam; The coffee brewing time can be adjusted with light touch button operation; Digital display show brewing time and temperature, and the temperature can be set; With automatic pressure release for protection; Drainage function and removable drip tray;

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	33.5 Kg / 42.1 Kg
Unit Size/CTN Size	535*400*568*mm / 650*480*600mm
Package	1PCS/CTN
Loading Capacity	130PCS/270PCS/273PCS
(20'GP/40'GP/40'HQ)	













































MO	uei.	
Des	scription:	

FCM3243 Le Gazzio Doppio

· Stainless steel housing with white or black color painting.

. Two 550ml S.S coffee boiler and 5.5L S.S steam boiler for making steam and hot

water;

· With inlet water pipe to connect tap water;

· Rotatory pump;

· Different barometers show the pressure of coffee and steam;

· Multifunction for automatic hot water and manual steam;

• The coffee brewing time can be adjusted with light touch button operation;

· Digital display show brewing time and temperature, and the temperature can be set;

· With automatic pressure release for protection;

· Drainage function and removable drip tray;

Power Consumption	4200W
Voltage	220V~50Hz
N.W/G.W	43.3KG/52.9KG
Unit Size/CTN Size	760*400*568mm / 840*460*600mm
Package	1PCS/CTN
Loading Capacity	65PCS/130PCS/140PCS
(20'GP/40'GP/40'HQ)	

































Model:	FCM3100C
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Italian pump with 15 bar pressure or Commercial rotary pump with 9 bar pressure fo optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Dual boilers: one is 550m1 s.s. boiler with s.s.heating tube to make temperature more stable for making coffee; another is 5.25 L s.s. boiler for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & adjustable non-slip foot.

Power Consumption	3050W
Voltage	220V~50Hz
N.W/G.W	32.5KG / 39KG / PCS
Unit Size/CTN Size	616*504*500*mm / 695*560*580mm
	816*504*500*mm / 895*560*580mm
Package	1PCS / CTN
Loading Capacity	120PCS / 263PCS / 264PCS
(20'GP/40'GP/40'HQ)	72PCS / 150PCS / 200PCS















RELIABLE GUARANTEED





















凸



Model:	FCM3120C
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Italian pump with 15 bar pressure or Commercial rotary pump with 9 bar pressure fo optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Dual boilers: one is 550m1 s.s. boiler with s.s.heating tube to make temperature more stable for making coffee; another is 5.25 L s.s. boiler for making steam and hot water Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & adjustable non-slip foot.

Voltage	220V~50Hz
N.W/G.W	52.4KG / 63KG / PCS
Unit Size/CTN Size	616*504*500*mm / 695*560*580mm
	816*504*500*mm / 895*560*580mm
Package	1PCS / CTN
Loading Capacity	120PCS / 263PCS / 264PCS
(20'GP/40'GP/40'HQ)	72PCS / 150PCS / 200PCS















GUARANTEED























Model:	FCM3100E
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commercial rotary pump with 9 bar pressure for optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 550ml heating tube to make temperature more stable for making coffee; another is 10.5L s.s. primary and secondary boiler for making steam and hot water. Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & adjustable non-slip foot.

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	32.5KG / 39KG / PCS
Unit Size/CTN Size	616*504*500*mm / 695*560*580mm
	816*504*500*mm / 895*560*580mm
Package	1PCS / CTN
Loading Capacity	127PCS / 263PCS / 264PCS
(20'GP/40'GP/40'HQ)	72PCS / 150PCS / 200PCS

















RELIABLE GUARANTEED





















Model:	FCM3120C
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commercial rotary pump with 9 bar pressure for optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 550ml heating tube to make temperature more stable for making coffee; another is 10.5L s.s. primary and secondary boiler for making steam and ho water. Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; Top cover cup-warming plate & adjustable non-slip foot.

Power Consumption	4200W	
Voltage	220V~50Hz	
N.W/G.W	52.4KG / 63KG / PCS	
Unit Size/CTN Size	616*504*500*mm / 695*560*580mm	
	816*504*500*mm / 895*560*580mm	
Package	1PCS / CTN	
Loading Capacity	127PCS / 263PCS / 264PCS	
(20'GP/40'GP/40'HQ)	72PCS / 150PCS / 200PCS	















RELIABLE GUARANTEED





























Model: FCM3109 · Stainless steel mirror housing & Plastic side cover; Description: · Multifunction for making coffee, steam and hot water at the same time; · Touch electronic button for easy operation; · Commercial rotary pump with 9 bar pressure for optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; · With LED illuminator; Temperature and time can be adjusted when making coffee; · Different barometers show the pressure when making coffee and steam; Double boilers: two 550ml S.S boiler with S.S heating tube to make temperature more stable for make coffee; another is full of S.S primary and secondary boiler with 5.25L capacity for making steam and hot water. · Professional S.S porta-filter holder and S.S filter with 58mm diameter; · Pre-infusion system to ensure perfect extraction and crema; · S.S. steam and water tube for cappuccino and hot water; · Top cover cup-warming plate & adjustable non-slip foot.

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	49KG / PCS;56. 5KG / PCS
Unit Size/CTN Size	703*605*555mm / 780*670*685mm
Package	1PCS / CTN
Loading Capacity	69PCS / 144 PCS / 144 PCS
(20'GP/40'GP/40'HQ)	





























Model:	FCM3120C	
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commercial rotary pump with 9 bar pressure for optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 550ml heating tube to make temperature more stable for making coffee; another is 10.5L S.S primary and secondary boiler for making steam and hot water. Professional S.S porta-filter holder and S.S filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; With flowmeter and fell inner copper pipe; Top cover cup-warming plate & adjustable non-slip foot. 	

Power Consumption	4200W
Voltage	220V~50Hz
N.W/G.W	56KG / PCS; 68.5KG / PCS
Unit Size/CTN Size	905*605*555*mm / 980*670*685mm
Package	1PCS / CTN
Loading Capacity	61PCS / 105PCS / 105PCS
(20'GP/40'GP/40'HQ)	















RELIABLE **GUARANTEED**





















Model:	FCM3101
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commercial rotary pump with 9 bar pressure for optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 550ml heating tube to make temperature more stable for making coffee; another is 10.5L S.S primary and secondary boiler for making steam and hot water. Professional S.S porta-filter holder and S.S filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; With flowmeter and fell inner copper pipe; Top cover cup-warming plate & adjustable non-slip foot.

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	40KG / PCS; 48KG / PCS
Unit Size/CTN Size	650*565*525*mm
Package	1PCS / CTN
Loading Capacity	72PCS / 162PCS / 216PCS
(20'GP/40'GP/40'HQ)	

















RELIABLE GUARANTEED

























Model:	FCM3201
Description:	 Stainless steel mirror housing & Plastic side cover; Multifunction for making coffee, steam and hot water at the same time; Touch electronic button for easy operation; Commercial rotary pump with 9 bar pressure for optional; Inlet pipe to connect tap water & Drain pipe to drain water directly; With LED illuminator; Temperature and time can be adjusted when making coffee; Different barometers show the pressure when making coffee and steam; Triple boilers: two 550ml heating tube to make temperature more stable for making coffee; another is 10.5L S.S primary and secondary boiler for making steam and hot water. Professional S.S porta-filter holder and S.S filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; With flowmeter and fell inner copper pipe; Top cover cup-warming plate & adjustable non-slip foot.

Power Consumption	4200W
Voltage	220V~50Hz
N.W/G.W	54KG / PCS; 65KG / PCS
Unit Size/CTN Size	850*565*525mm / 934*655*710mm
Package	1PCS / CTN
Loading Capacity	50PCS / 123PCS / 123PCS
(20'GP/40'GP/40'HQ)	















RELIABLE GUARANTEED



























Model:	FCM3506
Description:	 Desktop metal spray housing with spray color; Multifunction for making coffee steam and hot water at the same time; Touch screen for easy operation, adjustable temperature and flow rate; Dual boilers: one is 550ml s.s boiler with s.s heating tube to make; temperature more stable for making coffee; Another is full or s.s primary and secondary boiler with 5.25L capacity for making steam and hot water; Commercial rotary vane pump with 9 bar pressure; Inlet pipe to connect tap water and drain pipe to drain water directly; Professional s.s porta-filter holder and filter with 58mm diameter; Manual control for hot water and steam function; With barometer shows the pressure when making coffee; With flow meter and full inner cooper pipe; Auto-pressure release to protect the machine; S.S steam and water tube for cappuccino and hot water; Pre-infusion system to ensure perfect extraction and crema.

Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	40.8KG / PCS; 59.5KG / PCS
Unit Size/CTN Size	560*400*790mm / 640*485*975mm
Package	1PCS / CTN
Loading Capacity	72PCS / 152PCS / 152PCS
(20'GP/40'GP/40'HQ)	















RELIABLE GUARANTEED

TEA AND COFFEE MAKER SERIES

ferralli ferro
coffee espresso machine

Modern, stylish, compact: style stands out at first glance. The entire loose-leaf tea experience, recreated and automated. Tea-square, professional craft tea & coffee brewer.







FCM35	33
Power Consumption	4200W
Voltage	220V
Frequency	50Hz







COMMERCIAL MACHINE SERIES ferratti ferra























Model:	FCM3131 Allora	FCM3131A Allora
Description:	stable for making coffee,another steam and hot water; Detachable water tank with of 2.5 Italian ULKA pump with 15bar proptional; With a barometer, can show the properties of the professional s.s porta-filter holders. Touch screen for easy operation, Leva type manual hot water and a Automatic pressure release to professional s.s.	ressure or Rotary vane pump with 9bar pressure for pressure when making coffee; r and filter with 58mm diameter; adjustable temperature and flowing capacity; manual steam functions; otect the machine; aning; also can connect draip pipe directty.

Power Consumption	2510W / 2650W
Voltage	220V~50Hz
N.W/G.W	26.8KG / 32.6KG / PCS; 31.2KG / 37KG / PCS
Unit Size/CTN Size	520*330*476mm / 586*396*598mm
Package	1PCS / CTN
Loading Capacity	156PCS / 327PCS / 436PCS
(20'GP/40'GP/40'HQ)	



















8□

(h















Model:	FCM3124	FCM3124A
Description:	 Stainless steel housing; With 2L stainless steel primary and second to what it is a steel primary and second to with 2.5L detachable water tank; Italian pump with 15bar pressure; With coffee pressure showing; Knob type manual hot water and manual Light touch button operation, coffee time Teflon pipe connecting; Automatic pressure release and keep say with water drainage function; With water drainage function; With detachable drip try; Top cup warmer function. FCM3124: Italian pump with 15bar pression. FCM3124A: Commercial rotary vane pure 	I steam function; adjustable; ifety; sure;
Power Consumption	1510W / 1660W	
Voltage	220V~50Hz	
N.W/G.W	23KG/28.1KG/PCS / 29.1KG/33.5KG/PCS	
Unit Size/CTN Size	517*297*410mm / 616*386*562/mm	
Package	1PCS / CTN	
Loading Capacity	156PCS/327PCS/327PCS	



(20'GP/40'GP/40'HQ)













RELIABLE GUARANTEED









凸

Ф













Model:	FCM3137A
Description:	 Stainless steel housing; 2L S.S primary and secondary boiler; Detachable water tank, capacity 2.5L; Rotary vane pump (9 bar); Display for coffee and steam pressure; Turn knob of manual hot water and manual steam function; Leva handle operation, adjustable temperature& pre-infusion time; Copper pipe connection; With automatic pressure release for protection device; With drainage function; Removable drip tray; Cup warmer design
Power Consumption	1650W

Power Consumption	1650W
Voltage	220V~50Hz
N.W/G.W	25.6kg/31.7kg
Unit Size/CTN Size	537*335*405mm / 600*400*540 mm
Package	1PCS / CTN
Loading Capacity	216PCS/452PCS/452PCS
(20'GP/40'GP/40'HQ)	















RELIABLE GUARANTEED





















Model:	FCM3139 Luga Vanini
Description:	 Stainless steel housing; 2L S.S primary and secondary steam boiler and 500ml S.S coffee boilers; Detachable water tank, capacity 2.5L; Italian vibration pump (15bar); Display shows coffee and steam pressure; Turn knob for manual hot water and manual steam function; Leva handle operation, adjustable temperature and pre-infusion time Copper pipe connection; With automatic pressure pressure protection device; With drainage function; Removable drip tray; Cup warmer design.

Power Consumption	1650W
Voltage	220V~50Hz
N.W/G.W	21.4kg / 25.7kg
Unit Size/CTN Size	537*335*405 / mm/600*400*540mm
Package	1PCS / CTN
Loading Capacity	216PCS / 452PCS / 452PCS
(20'GP/40'GP/40'HQ)	



























Model:













Description:	 Stainless steel housing; Multifunction for making coffee, steam and hot water; Touch electronic button for easy operation, adjustable coffee brewing time; Italian pump with 15bar pressure; Dual-boilers:One thermo block is for making coffee and hot water; and one is 1L die-casting boiler for making steam; Auto- hot water and manual steam function; 1.7L removable water reservoir; With a barometer, can know the pressure when making coffee; Professional s.s. porta-filter holder and filter with 58mm diameter; S.S. steam and water pipe for cappuccino and hot water; Removable drip tray for easy cleaning: also can connect drain pipe directly; Auto-pressure release to protect the machine; Top cover cup-warming plate & Adjustable non-slip foot.
Power Consumption	2950W
Voltage	220V~50Hz
N.W/G.W	26.6kg/32.7kg
Unit Size/CTN Size	410*320*515mm / 567*428*545 mm
Package	1PCS / CTN

FCM3129 Allegrio



Loading Capacity

(20'GP/40'GP/40'HQ)











220PCS/442PCS/444PCS



RELIABLE GUARANTEED









(h

















Model:	FCM3812 Garazzi
Description:	 Stainless steel mirror housing & plastic side cover; Dual boilers: one is 5.5L S.S boiler for making steam, another is thermo-block for making coffee; Tap water connection; Italian 15 bar vibration pump; With barometer for steam display; Steam temperature setting function; Easy operation, setting brewing time and steam temperature by touch button; Inside teflon pipe; With auto-pressure release function to protect the machine; Also can connect drain pipe to drain water directly; Removable drip tray; Cup warmer on the top plate;
Power Consumption	3200W
Voltage	220V~50Hz
N.W/G.W	17.2KG/21.34KG
Unit Size/CTN Size	410*350*547mm / 426*413*620mm
Package	1PCS / CTN



Loading Capacity (20'GP/40'GP/40'HQ)















RELIABLE





















Model:	FCM3125A
Description:	 Stainless steel mirror housing&plastic side cover; Dual boilers: one is 5.5L S.S boiler for making steam, another is thermo-block for making coffee; Tap water connection; Italian 15 bar vibration pump; With barometer for steam display; Steam temperature setting function; Easy operation, setting brewing time and steam temperature by touch button; Inside teflon pipe; With auto-pressure release function to protect the machine; Also can connect drain pipe to drain water directly; Removable drip tray; Cup warmer on the top plate;
Power Consumption	3350W
Voltage	220V~50Hz
N.W/G.W	20.5kg/26.0kg
Unit Size/CTN Size	442*324*520/mm / 428*545*576mm
Package	1PCS / CTN



Loading Capacity

(20'GP/40'GP/40'HQ)











218PCS/450PCS/450PCS





COMMERCIAL MACHINE SERIES formatti ferro

























Model:	FCM3130
Description:	 Stainless steel housing and wood grain side panel; Multifunction for making coffee, steam and hot water; Touch electronic button for easy operation, adjustable coffee brewing time; Italian pump with 15bar pressure; Dual-boilers: One thermo block is for making coffee and hot water and one is 1L die-casting AL boiler for making steam; Auto- hot water and manual steam function; 1.7L removable water reservoir; With a barometer, can know the pressure when making coffee; Professional s. s. porta-filter holder and filter with 58mm diameter; S. S. steam and water pipe for cappuccino and hot water; Removable drip tray for easy cleaning; Auto-pressure release to protect the machine; Top cover cup-warming plate & Adjustable non-slip foot.
Power Consumption	2950W
Voltage	220V/50Hz
N.W/G.W	
Unit Size/CTN Size	348*273*407mm / 400*32*462mm
Package	1PCS/CTN



Loading Capacity

(20'GP/40'GP/40'HQ)











220PCS / 750PCS / 750PCS



RELIABLE









凸

பு

















stable for making coffee; Another 1L boiler for making steam and hot water; 1.7L removable water reservoir; With barometer, show the pressure of coffee; Professional S.S. porta-filter holder and filter with 58mm diameter;	Model:	FCM3128
 S.S. steam and water tube for cappuccino and hot water; Removable drip tray for easy cleaning Also can connect drain pipe to drain water directly; Top cover cup-warming plate& adjustable non-slip feet. 	Description:	 Multifunction for making coffee, steam and hot water at the same time; Commercial pump with 9bar pressure; Dual boilers: one is 550m1 S.S boiler with S.S heating tube to make temperature more stable for making coffee; Another 1L boiler for making steam and hot water; 1.7L removable water reservoir; With barometer, show the pressure of coffee; Professional S.S. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.S. steam and water tube for cappuccino and hot water; Removable drip tray for easy cleaning Also can connect drain pipe to drain water directly;

Power Consumption	2950W
Voltage	220V~50Hz
N.W/G.W	23.5kg/PCS;28.5kg/PCS
Unit Size/CTN Size	410*320*515mm/526*376*610 mm
Package	1PCS / CTN
Loading Capacity	220PCS/442PCS/444PCS
(20'GP/40'GP/40'HQ)	





















A strong mix of innovation and elegance, that satisfies every lover of real Italian coffee and suits any environment. These semi-automatic professional

coffee machines will be applicable in office, Ho, Re, Ca etc.





MANUAL CONTROL



POWER CONTROL



COFFEE HEATING TUBE



HOT WATER



STEAM



COFFEE TABLE



COFFEE



COFFEE HEATING POT BODY



















Model:	FCM3005C
Description:	Stainless steel housing; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; Thermoblock with s. s. heating tube to prevent aluminum oxidizing and healthier; With a barometer, can know the pressure when making coffee; Professional s. s.porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.s. steam nozzle for cappuccino or latte; Removable drip tray & top cup-warming plate.
Power Consumption	1450W
Voltage	220-240V
Frequency	50Hz
N.W	6.8KG/PCS
G.W	8KG/CTN
Unit Size	290*255*325mm
G.B Size	357*287*367mm
CTN Size	370*300*380mm
Package	1PCS/CTN
Loading Capacity(20'GP)	622PCS
Loading Capacity(40'GP)	1314PCS
Loading Capacity(40'HQ)	1542PCS

























Model:	FCM3005	FCM 3005A
Description:	Stainless steel housing; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; Thermoblock with s. s. heating tube to prevent aluminum oxidizing and healthier; Professional s. s.porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.s. steam nozzle for cappuccino or latte; Removable drip tray & top cup-warming plate.	
Power Consumption	1450W	
Voltage	220-240V	
Frequency	50Hz	
N.W	6.8KG/PCS	
G.W	8KG/CTN	
Unit Size	290*255*325mm	
G.B Size	357*287*367mm	
CTN Size	370*300*380mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	622PCS	
Loading Capacity(40'GP)	1314PCS	
0 , ,		









HOME MACHINE SERIES



























Power	1240~1450 W
Voltage	220~240V, 50Hz~60Hz
Power Pump	19 BAR
Water Tank	1.4 L
Loading Capacity (20'GP)	790 PCS
Loading Capacity (40'GP)	1628 PCS
Loading Capacity (40'HQ)	1790 PCS













BEST MATERIAL



RELIABLE GUARANTEED























Model:	FCM3009	
Description:	Stainless steel housing; Multifunction for making coffee, steam and hot water; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; 500ml s.s.boiler with s.s.heating tube to make temperature more stable; Professional s.s.porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.s. steam nozzle for cappuccino or latte; With a barometer, can know the pressure when making coffee; Removable drip tray & top cup-warming plate.	
Power Consumption	1500W	
Voltage	220-240V	
Frequency	50Hz	
N.W	13KG/PCS	
G.W	15.6KG/CTN	
Unit Size	315*313*425mm	
G.B Size	388*355*464mm	
CTN Size	402*369*474mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	403PCS	
Loading Capacity(40'GP)	819PCS	
Loading Capacity(40'HQ)	873PCS	

























Model:	FCM3009A		
Description:	 Stainless steel housing; Multifunction for making coffee, steam and hot water; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; 500ml s.s.boiler with s.s.heating tube to make temperature more stable; Professional s.s.porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; S.s. steam nozzle for cappuccino or latte; With a barometer, can know the pressure when making coffee; With separate hot water pipe to make hot water easily; Removable drip tray & top cup-warming plate. 		
Power Consumption	1500W		
Voltage	220-240V		
Frequency	50Hz		
N.W	13KG/PCS		
G.W	15.6KG/CTN		
Unit Size	315*313*425mm		
G.B Size	388*355*464mm		
CTN Size	402*369*474mm		
Package	1PCS/CTN		
Loading Capacity(20'GP)	403PCS		
Loading Capacity(40'GP)	819PCS		
Loading Capacity(40'HQ)	873PCS		





























Model:	FCM3009B
Description:	 Stainless steel housing; Multifunction for making coffee, steam and hot water at the same time; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; Dual boilers: one is 500ml s. s. boiler with s. s. heating tube to make temperature more stable for making coffee; another is thermoblock for making steam and hot water; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; With a barometer, can know the pressure when making coffee; S.S. steam and water tube for cappuccino and hot water; With descale function, can clean the boiler easily; Removable drip tray & Top cup-warming plate.
Power Consumption	3000W
Voltage	220-240V
Frequency	50Hz
N.W	15KG/PCS
G.W	17.2KG/CTN
Unit Size	315*313*425mm
G.B Size	388*355*464mm
CTN Size	402*369*474mm
Package	1PCS/CTN
Loading Capacity(20'GP)	403PCS
Loading Capacity(40'GP)	819PCS
Loading Capacity(40'HQ)	873PCS

























Model:	FCM3012	
Description:	Stainless steel housing; Multifunction for making coffee, steam and hot water at the same time; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; Professional s. s. porta-filter holder and filter with 58mm diameter; Pre-infusion system to ensure perfect extraction and crema; Independent multi-thermoblock system for making coffee and steam; With a barometer, can know the pressure when making coffee; S. S. steam and water tube for cappuccino and hot water; With descale function, can clean the boiler easily.	
Power Consumption	3000W	
Voltage	220-240V	
Frequency	50Hz	
N.W	12KG/PCS	
G.W	14KG/CTN	
Unit Size	320*360*400mm	
G.B Size		
CTN Size	396*396*450mm	
Package	1PCS/CTN	
Loading Capacity(20'GP)	335PCS	
Loading Capacity(40'GP)	687PCS	
Loading Capacity(40'HQ)	740PCS	































Model:	FCM3605	
Description:	 Multifunction for making coffee, steam and hot water; Plastic housing with brushed S.S. decorative panel; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; Thermoblock with s. s. heating tube to prevent aluminum oxidizing and healthier; Professional s. s. porta-filter holder and filter with 58mm diameter; With a barometer, can know the pressure when making coffee; With separate hot water pipe to make water; Electronic switch, microcomputer temperature control; S.S. steaming nozzle for cappuccino or latte; Removable drip tray & warm cup function. 	
Power Consumption	1450W	
Voltage	220-240V	
Frequency	50Hz	
N.W	4.8KG/PCS	
G.W	11KG/CTN	
Unit Size	285*257*315mm	
G.B Size		
CTN Size	521*438*395mm	
Package	2PCS/CTN	
Loading Capacity(20'GP)	792PCS	
Loading Capacity(40'GP)	1680PCS	
Loading Capacity(40'HQ)	1960PCS	























Model:	FCM3006	FCM3601	
Description:	Plastic housing with brus Italian ULKA pump with 1 1.7L removable water res Thermoblock with s. s. h Die - casting aluminum fi Electronic switch, micros S.S. steaming nozzle for	Multifunction for making coffee, steam and hot water; Plastic housing with brushed S.S. decorative panel; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; Thermoblock with s. s. heating tube to prevent aluminum oxidizing and healthier; Die - casting aluminum filter holder and s.s. filter with 58mm diameter; Electronic switch, microcomputer temperature control; S.S. steaming nozzle for cappuccino or latte; Removable drip tray & warm cup function.	
Power Consumption	1450W		
Voltage	220-240V		
Frequency	50Hz		
N.W	4.8KG/PCS		
G.W	11KG/CTN		
Unit Size	285*257*315mm		
G.B Size	318*384*355mm		
CTN Size	521*438*395mm		
Package	2PCS/CTN		
Loading Capacity(20'GP)	792PCS		
Loading Capacity(40'GP)	1680PCS		
Loading Capacity(40'HQ)	1960PCS		





























Model:	FCM3602
Description:	Stainless steel housing; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; 500ml s. s. boiler with s.s.heating tube to make temperature more stable; Professional s. s.porta-filter holder and filter with 58mm diameter; S.s. steam nozzle for cappuccino or latte; Removable drip tray & top cup-warming plate.
Power Consumption	850-1000W
Voltage	220-240V
Frequency	50Hz
N.W	7.8KG/PCS
G.W	9KG/CTN
Unit Size	270*220*330mm
G.B Size	303*253*335mm
CTN Size	521*318*355mm
Package	2PCS/CTN
Loading Capacity(20'GP)	924PCS
Loading Capacity(40'GP)	1860PCS
Loading Capacity(40'HQ)	2170PCS























Model:	FCM3606
Description:	Stainless steel housing; Italian ULKA pump with 15 bar pressure; 1.7L removable water reservoir; Thermoblock with s. s. heating tube to prevent aluminum oxidizing and healthier; Professional s. s.porta-filter holder and filter with 58mm diameter; S.s. steam nozzle for cappuccino or latte; Removable drip tray & top cup-warming plate.
Power Consumption	850-1000W
Voltage	220-240V
Frequency	50Hz
N.W	7.8KG/PCS
G.W	9KG/CTN
Unit Size	270*220*330mm
G.B Size	303*253*335mm
CTN Size	521*318*355mm
Package	2PCS/CTN
Loading Capacity(20'GP)	924PCS
Loading Capacity(40'GP)	1860PCS
Loading Capacity(40'HQ)	2170PCS





























Model:	FCM2001	FCM2008
Description:	 Llluminated on/off switch Removable drip tray for e 	cappuccino or latte; built-in safety valve; re protection; omatic pressure-releasing protecting device; ;
Power Consumption	730-870W	
Voltage	220-240V	
Frequency	50Hz	
N.W	1.6KG/PCS	
G.W	4.9KG/CTN	
Unit Size	235*165*300mm	
G.B Size	269*213*331mm	
CTN Size	441*284*351mm	
Package	2PCS/CTN	
Loading Capacity(20'GP)	1236PCS	
Loading Capacity(40'GP)	2520PCS	
Loading Capacity(40'HQ)	2940PCS	























Model:	FCM2002	FCM2008B
Description:	 Llluminated on/off switch Removable drip tray for e 	built-in safety valve; re protection; omatic pressure-releasing protecting device;
Power Consumption	730-870W	
Voltage	220-240V	
Frequency	50Hz	
N.W	1.6KG/PCS	
G.W	4.9KG/CTN	
Unit Size	235*165*300mm	
G.B Size	269*213*331mm	
CTN Size	441*284*351mm	
Package	2PCS/CTN	
Loading Capacity(20'GP)	1236PCS	
Loading Capacity(40'GP)	2520PCS	
Loading Capacity(40'HQ)	2940PCS	

























Model:	FCM4682
Description:	 Stainless steel housing; ULKA pump 15Bar Capacity of water tank 1.25L No water drip during preheating; less pressure loss during brewing to improve coffee extraction More stable coffee temperature, comparable to commercial coffee machine. Working principle similar to commercial coffee machine, single layer filter and good brewing result.
Power Consumption	1050W
V-11	220-240V
Voltage	
Frequency	50Hz
1949 STA	50Hz 890PCS
Frequency	























Model:	FCM5003	
Description:	 Stainless steel housing; ULKA pump Italian -style steam Milk Frothing system Built-in water filtering installation with modular filter cartridge, allows safe water usages as well as raising the coffe quality. Preheating drip prevention Function. Temperature control technology. Overheating protection and excessive pressure protection to guarantee safety. Cup warming funtion. Double servings of espresso can be extracted at once. Professional grade coffee filter handle. 	
Power Consumption	1050W	
Voltage	220-240V	
Frequency	50Hz	
	700000	
Loading Capacity (20'GP)	788PCS	
Loading Capacity (20'GP) Loading Capacity (40'GP)	1604PCS	

























par powerful pressure pump -casting aluminum alloy boiler L detachable transparent water tank r 2 cups dual-stainless steel filter h high pressure frothing function h overheating and overpressure protected device achable drop tray for easy cleaning ustable steam knob h thermometer to show the temperature clearly
W
240V
AR
Z
PCS
DPCS
PCS























Model:	FCM5013B	
Description:	 Cup warmer Adjustable steam Aluminum die-casting boiler 15Bar ITALY ULKA pump pressure Control Panel with chrome plated decoration Removable transparent water tank Removable and washable drip tray With milk frothing function to make cappuccino With over-heat & over-pressure protecting device Coffee options: espresso, cappuccino and latte Thermometer helps you monitor boiler water temperature 1 & 2 cups ground coffee SUS 304 filter and aluminum die-casting filter holder 	
Power Consumption	1000W	
Voltage	220V	
Frequency	50Hz	
N.W/G.W	5/6 Kgs	
Water Tank	1000ML	
Heating Time	45 Seconds	
Brewing Pressure	5/6 Kgs	
Dimension	272 x 207.5 x 292 mm	
Basket Filter	Stainless Steel SUS304 Double Basket	
Loading Capacity (20'GP)	850PCS	
Loading Capacity (40'GP)	1820PCS	
Loading Capacity (40'GP)	2100PCS	

























Model:	FCM5013C
Description:	 Cup warmer Adjustable steam Aluminum die-casting boiler 15Bar ITALY ULKA pump pressure Control Panel with chrome plated decoration Removable transparent water tank Removable and washable drip tray With milk frothing function to make cappuccino With over-heat & over-pressure protecting device Coffee options: espresso, cappuccino and latte Thermometer helps you monitor boiler water temperature 1 & 2 cups ground coffee SUS 304 filter and aluminum die-casting filter holder
Power Consumption	1050W
Voltage	220-240V
Frequency	50/60Hz
N.W/G.W	5/6 Kgs
Water Tank	1000ML
Heating Time	45 Seconds
Brewing Pressure	5/6 Kgs
Dimension	272 x 207.5 x 292 mm
Basket Filter	Stainless Steel SUS304 Double Basket
Loading Capacity (20'GP)	850PCS
Loading Capacity (40'GP)	1820PCS
Loading Capacity (40'GP)	2100PCS

























Model:	FCM54001
Description:	 Appearance Power switch, knob to control coffee vapor The overal dimensions are 300x150x307mm Water tank AS transparent, capacity 1.25L With pressure relief box function Contains espresso and cappuccion Dismountable water connection tray for easy cleaning, convenient and practical Equipped with 2 cups of filter, make coffee sanitary and easy to clean Electromagnetic pressure pump with 15bar (48w) The amount of coffee produced is manual Thermometer helps you monitor boiler water temperature With overheat protection device, safe and reliable
Capacity	1.25L
Voltage	100-240v
Wattage	1250=1450w
Loading Capacity (20'GP)	1150PCS
Loading Capacity (40'GP)	2390PCS
Loading Capacity (40'GP)	2668PCS





























Model:	FCM7401
Description:	 One button operation for brewing coffee with modes of small cup volume, big cup volume, and adjustable cup volume. Instant-heating boiler with SS pipe, more clean, no scale accurate NTC temperature control. Flowmeter for controlling accurate coffee amount. Preheating time ≤90S. Suitable for tall,middle and short cups. With detachable milk tank and water tank. Funnel and filter can be stored at back of the unit. New frothing system can make fine crema.
Water capacity	1.7L
Milk tank capacity	500ML
Voltage	100V/120V/220V
Wattage	1230-1470W
Loading Capacity (20'GP)	600PCS
Loading Capacity (40'GP)	1200PCS
Loading Capacity (40'GP)	1400PCS

























Model:	FCM4622
Description:	 Pump can provide 15bar powerful pressure for rich taste. Die-casting aluminum alloy boiler. 1.5L large removable water tank with closing lid. 1 or 2 cups dual-stainless steel filter with patent design to make perfect crema. Can make coffee with coffee pod of ground coffee. High pressure frothing function for making cappuccino or other hot beverage. 3 switches with indicator lights to make cottee or steam convenient. Elegant design with ABS spraying color decoration. With overheating and overpressure protected eace, safe and reliable. Detachable frothing deviceand drip tray for easy cleaning. Warming coffee cups pre-heating.
Power	1050W
Voltage	230V
Pressure	15BAR
Capacity	1.5L
Loading Capacity (20'GP)	938PCS
Loading Capacity (40'GP)	1998PCS
Loading Capacity (40'GP)	2190PCS





























Model:	FCM4621
Description:	 Pump can provide 15 bar powerful pressure for rich taste. 1.5L large removable water tank with closing lid. 1 or 2 cups dual-stainless steel filter with patent design to make perfect crema. Elegant design with stainless steel decoration With overheating and overpressure protected device, safe and reliable. Can make coffee with coffee pod or ground coffee. With high pressure frothing. Function for making cappuccino or other hot beverage. Die-casting aluminum alloy boiler. Detachable frothing device and drip tray and for easy cleaning.
Voltage	100V~120V
Frequency	50/60 Hz
Power Pump	15 BAR
Water Tank	1.5L
Loading Capacity (20'GP)	1006PCS
Loading Capacity (40'GP)	2042PCS
	2316PCS









HOME MACHINE SERIES

















Model:	FCM4695D
Description:	 15bar powerful pressure pump. Die-casting aluminum alloy boiler. 1.5L detachable transparent water tank. 1 or 2 cups dual-stainless steel filter. With high pressure frothing function. With overheating and overpressure protected device. Detachable drip tray for easy cleaning. Adjustable steam knob.
Power	850W
Power Voltage	850W 220v-240v
Voltage	220v-240v
Voltage Frequency	220v-240v 50Hz
Voltage Frequency Power Pump	220v-240v 50Hz 15 BAR
Voltage Frequency Power Pump Water Tank	220v-240v 50Hz 15 BAR 1.5L

























Model:	FCM5005
Description:	 Can add water filter. Die-casting aluminum alloy boiler. 1 or 2 cups dual-stainless steel filter. Coffee brewing system with patent design. Detachable frothing nozzle and drip tray. With overheating and verpressure protected device.
Voltage	100v - 240v
Wattage	1050 W
Powe Working	15 Bar
Loading Capacity (20'GP)	858PCS
Loading Capacity (40'GP)	1772PCS
Loading Capacity (40'HQ)	1960PCS























Model:	FCM5700
Description:	 Grinding Bean Gear: 15 Gears Manual Adjustable (tentative), 5 Gears Brewing Pressure (>9bar). Flowmeter precise control, can automatically brew large and small cups of coffee (large 60 ml,small 30 ml). Cone mill direct powder dropping system, no powder outlet, no powder hiding, removable grinding head, easy cleaning Central temperature of coffee funnel: 92±2°C. The thermal efficiency of brewing system can reach more than 90%. With automatic power-off function, economize on environmental protection. Double NTC High Precision PID Precise Temperature Control.
Туре	Coffee Machine with Built-in Grinder
Power	1470W
Voltage	230V
Frequency	50Hz
Size	L348 x W322 x H410 MM
Brewing Pressure	20BAR
Water Tank	2.7 L
Bean Hopper capacity	250 GRAM
Material	STAINLESS STEEL
Loading Capacity (20'GP)	435PCS
Loading Capacity (40'GP)	820PCS
Loading Capacity (40'HQ)	830PCS

























Model:	FCM4675
Description:	 15 bar powerful pressure pump Thermoblock fast heating system to ensure the precise temperature and instant steam. Aluminum alloy boiler with stainless steel heating channel to prevent aluminum oxidating. 1.5L removable transparent water tank. Dual-stainless steel filter with patent design to make perfect cream. Can make coffee with coffee pod or ground coffee. With high pressure frothing function to make cappuccino. Elegant design with stainless steel decoration. With overheating and overpressure protected device safe and reliable. Elegant design with stainless steel decoration. Detachable frothing device and drip tray.
Power Pump	15 Bar
Water Tank	1.5L
Loading Capacity (20'GP)	740PCS
Loading Capacity (40'GP)	1556PCS
Loading Capacity (40'HQ)	1820PCS

























Description:	 Pump can provide 15bar powerful pressure for rich taste. Die-casting aluminum alloy boiler. 1.0L detachable transparent water tank. 1-2 cups dual-stainless steel filter with patent design to make perfect crema. With high pressure frothing function for making cappuccino or other hot beverage. With overheating and overpressure protected device safe and reliable. Detachable drip tray for your easy cleaning. Warming plate for coffee cups pre-heating.
Power Pump	15 BAR
Water Tank	1.0 L
Voltage	230V
Frequency	50Hz
Loading Capacity (20'GP)	435PCS
Loading Capacity (40'GP)	820PCS
Loading Capacity (40'HQ)	830PCS

























Model:	FCM4602S
Description:	 Pump Can provide 15bar powerful pressure for rich taste. Die-casting aluminum alloy boiler. 1.4L large detachable water tank. Aluminum alloy filter holder attached with dual-stainless filter. Can make coffee with coffee pod or ground coffee. Make espresso with perfect crema. With high pressure frothing function. 3 switches with indicator lights. With 2 independent thermostats to ensure the temperatures of water and steam more accurate. Detachable frothing nozzle and drip tray for easy cleaning Metallic cup plate for coffee cups pre-heating.
Power Pump	15 BAR
Water Tank	1.4L
Loading Capacity (20'GP)	910PCS
Loading Capacity (40'GP)	1866PCS
Loading Capacity (40'HQ)	2102PCS

























Model:	FCM4626
Description:	 Pump can provide 15 bar powerful pressure for rich taste. Die-casting aluminum alloy boiler. 1.5L large removable water tank. 1-2cups dual-stainless steel filter with patent design to make perfect crema. Can make coffee with coffee pod or ground coffee with high pressure frothing function for making. Cappuccino or other hot beverage. Elegant design with ABS spraying color decoration with overheating and overpressure protected device. safe and reliable. Adjustable steam knob for convenient operation. Detachable frothing device and drip tray for easy cleaning.
Power Pump	15 BAR
Water Tank	1.5 L
Loading Capacity (20'GP)	990PCS
Loading Capacity (40'GP)	2050PCS
Loading Capacity (40'HQ)	2218PCS























Model:	FCM4656
Description:	 With rotary high pressure steam-spouting pipe, can choose to make espresso and cappuccino at will with aluminum diecasting boiler (800w). With two independent thermostats to control the temperatures of water and steam. With overheating protecting device for safe and reliable using. With thermometer on the front of the body to show the temperature clearly. With detachable drip tray for convenient cleaning. With safe device and automatic pressurereleasing protecting device. With safe device and automatic pressurereleasing protecting device. With detachable drip tray and high pressure funnel for convenient cleaning.
Power Consumption	800 W
Brewing Pressure	15 Bar
Voltage	220V/50Hz
Water Tank	240 ML
Heating Time	45 Seconds
Porta Filter	Unpressurised
Portafilter	Die Cast Alumunium Diameter 52mm
Basket Filter	Stainless Steel SUS304 Single Basket
Dimension	237 x 210 x 310 mm
Loading Capacity (20'GP)	1132PCS
	11021.00
Loading Capacity (40'GP)	2340PCS























Model:	FCM5018-GS
Description:	 220-240V/50Hz/1100W. 15bar powerful pressure pump. Die-casting aluminum alloy boiler. 1.2L detachable transparent water tank. 2 cups dual-stainless steel filter. With high pressure frothing function. With overheating and overpressure protected device. Detachable drop tray for easy cleaning. Adjustable steam knob. With thermometer to show the temperature clearly.
Power	1100W
Voltage	220-240V/50Hz
Power Pump	15 BAR
Water Tank	1.2 L
Loading Capacity (20'GP)	990PCS
Loading Capacity (40'GP)	2050PCS
Loading Capacity (40'HQ)	2218PCS





























Model:	FCM5002
Description:	 220-240V/50Hz/1100W. 15bar powerful pressure pump. Die-casting aluminum alloy boiler. 1.2L detachable transparent water tank. 2 cups dual-stainless steel filter. With high pressure frothing function. With overheating and overpressure protected device. Detachable drop tray for easy cleaning. Adjustable steam knob. With thermometer to show the temperature clearly.
Power	1100W
Voltage	220-240V/50Hz
Power Pump	15 BAR
Water Tank	1.2 L
Loading Capacity (20'GP)	890PCS
Loading Capacity (40'GP)	1840PCS
Loading Capacity (40'HQ)	2130PCS























Power 1050W Voltage • Capa	5 Bar Italy Ulka Pump. city: 1.0L num die-casting boiler. e options: espresso, cappuccino and latte. cups ground coffee S/S filter. //S filter is optional. vable transparent water tank.
Voltage 220-24	nilk frothing function to make cappuccino. table steam. over-heat & over-pressure protecting device.
D D 45 DAD	V
Power Pump 15 BAR	
Water Tank 1.0 L	
Loading Capacity (20'GP) 850PC	
Loading Capacity (40'GP) 1820PG	
Loading Capacity (40'HQ) 2100PG	

























Model:	FCM4682GA
Description:	 15Bar Capacity of water tank 1.25L No water drip during preheating; Less pressure loss during brewing to improve coffee extraction. More stable coffee temperature, comparable to commercial coffee machine. Working principle similar to commercial coffee machine, single layer filter and good brewing result.
Power	1050W
Voltage	220-240V/50Hz
Power Pump	15 BAR
Water Tank	1.25 L
Loading Capacity (20'GP)	890PCS
Loading Capacity (40'GP)	1840PCS
Loading Capacity (40'HQ)	2130PCS























Power 1470W Power 1470W Voltage 220-240V Power Pump 15 BAR Water Tank 1.7 L Loading Capacity (20'GP) Loading Capacity (40'GP) Loading Capacity (40'GP) Loading Capacity (40'GP) 1.5 bar powerful pressure pump. 1.7 bar powerful pressure pump. 1.7 bar powerful pressure with SS pipe, more clean, no scale. 1.7 L water tank, 500ML milk tank. One button operation for brewing coffee with modes of small cup volume, big cup volume for espresso, cappuccino and latte. Accurate NTC temperature control. Flow meter for controlling accurate coffee amount. Preheating time ≤90S. Detachable milk tank, water tank and adjustable drip tray.	Model:	FCM5411A-GS
Voltage 220-240V Power Pump 15 BAR Water Tank 1.7 L Loading Capacity (20'GP) 860PCS Loading Capacity (40'GP) 1760PCS	Description:	 15 bar powerful pressure pump. Thermo block fast heating system with SS pipe, more clean, no scale. 1.7L water tank, 500ML milk tank. One button operation for brewing coffee with modes of small cup volume, big cup volume for espresso, cappuccino and latte. Accurate NTC temperature control. Flow meter for controlling accurate coffee amount. Preheating time ≤90S.
Power Pump 15 BAR Water Tank 1.7 L Loading Capacity (20'GP) 860PCS Loading Capacity (40'GP) 1760PCS	Power	1470W
Water Tank 1.7 L Loading Capacity (20'GP) 860PCS Loading Capacity (40'GP) 1760PCS	Voltage	220-240V
Loading Capacity (20'GP) 860PCS Loading Capacity (40'GP) 1760PCS	Power Pump	15 BAR
Loading Capacity (40'GP) 1760PCS	Water Tank	1.7 L
	Loading Capacity (20'GP)	860PCS
Loading Capacity (40'HQ) 1960PCS	Loading Capacity (40'GP)	1760PCS
	Loading Capacity (40'HQ)	1960PCS























Model:	FCM2009B
Description:	 Removable and washable drip tray, S/S filter and aluminum die-casting filter holder. Coffee options: espresso, cappuccino and latte. 1 or 2 cups ground coffee S/S filter. With milk frothing function to make cappuccino. Pod S/S filter is optional (with extra cost). Over- heat&over-pressure protecting device. Adjustable steam. Cup warmer.
Power	1050 W
Voltage	220V/50Hz
Power Pump	15 BAR
Water Tank	1500 ML
Heating Time	45 Seconds
Porta Filter	Unpressurised
Portafilter	Die Cast Alumunium Diameter 52mm
Basket Filter	Stainless Steel SUS Single Basket
Colour	Silver+Black
Loading Capacity (20'GP)	354 CTN / 708 PCS
Loading Capacity (40'GP)	751 CTN / 1502 PCS
Loading Capacity (40'HQ)	840 CTN /1680 PCS























Model:	FCM2010A
Description:	 15 bar Italian pump pressure. Aluminum die-casting boiler. With 76 cm export carton Drop testing. Coffee options: espresso, cappuccino and latte. 1 or 2 cups ground coffee s/s filter. Pod S/S filter is optional. Removable and washable drip tray, S/S filter and aluminum die-casting filter holder. With milk frothing function to maker cappuccino Adjustable steam. With over-heat & over pressure protecting device. Thermometer helps you monitor boiler water temperature. Removable transparent water tank. With S/S decoration plate.
Power Pump	15 BAR
Loading Capacity (20'GP)	314 CTN / 628 PCS
Loading Capacity (40'GP)	660 CTN / 1320 PCS
Loading Capacity (40'HQ)	744 CTN / 1488 PCS
























Model:	FCM2011
Description:	 220-240V/ 50Hz /1050W. Capacity: 1.1L, slim style. Italian pump 15 bar pressure. Thermal block heating system, S/S water tube. Coffee options: espresso, cappuccino and latte. 1 or 2 cups ground coffee S/S filter, optional Pod S/S filter. Removable transparent water tank. Removable and washable drip tray, S/S filter and aluminum die-casting filter holder. With milk frothing function to make cappuccino. Adjustable steam. With over-heat & over-pressure protecting device Cup warmer. With painted S/S decoration plate (red, blue, natural, etc). With plated Top Rim decoration.
Power	1050 W
Voltage	220-240V/50Hz
Power Pump	15 BAR
Water Tank	1.1 L
Loading Capacity (20'GP)	880 PCS
Loading Capacity (40'GP)	1888 PCS









HOME MACHINE SERIES

















Model:	FCM265E1
Description:	 Rating:120V, 60Hz,1300W. 900ml removable transparent water reservoir. High performance pump with max.15 bar Defond pump. Make the nice Espresso and Cappuccino. Integrated cup warmer on housing top. Thermostatic controlled hot water system (thermoblock) with automatic emptying of remaining water. Cool-touch steam nozzle with frothing function. ON/OFF switch on side panel. On the top side, multifunction knobs of 4-ways valve integrated 3 micro switches for espresso or steam/hot water. Removable drip tray for easy cleaning. Non-slip foot pads. Portafilter polished. Accessory: measuring spoon, single and double cup coffee filter. Product size: 266x205x285mm.
Power	1300 W
Voltage	120V/60Hz
Power Pump	15 BAR
Loading Capacity (20'GP)	314 CTN / 628 PCS
Loading Capacity (40'GP)	660 CTN / 1320 PCS
Loading Capacity (40'HQ)	744 CTN / 1488 PCS


























Model:	FCM265B
Description:	 Rating: 120V, 60Hz, 1300W 900ml removable transparent water reservoir High performance pump with max.15 bar Defond pump Make the nice Espresso and Cappuccino. Integrated cup warmer on housing top Thermostatic controlled hot water system (thermoblock) with automatic emptying of remaining water. Cool-touch steam nozzle with frothing function ON/OFF switch on side panel On the top side, multifunction knobs of 4-ways valve integrated 3 micro switches for espresso or steam/hot water. Removable drip tray for easy cleaning Non-slip foot pads. Portafilter polished. Accessory: measuring spoon, single and double cup coffee filter. Product size: 266x205x285mm.
Power	1300 W
Voltage	120V/60Hz
Power Pump	15 BAR
Water Tank	900 ML
Loading Capacity (20'GP)	882 PCS
Loading Capacity (40'GP)	1826 PCS
Loading Capacity (40'HQ)	2114 PCS


























Model:	FCM265E1
Description:	 Rating: 120V/220v, 50Hz/60Hz,1300W. 900ml removable transparent water reservoir. High performance pump with max.15 bar Defond pump. Make the nice Espresso and Cappuccino. Integrated cup warmer on housing top. Thermostatic controlled hot water system (thermoblock) with automatic emptying of remaining water. Cool-touch steam nozzle with frothing function. ON/OFF switch on side panel. Removable drip tray for easy cleaning. Non-slip foot pads. Portafilter polished. Accessory: measuring spoon, single and double cup coffee filter. Product size: 266x205x285mm.
Power	1300 W
Voltage	120V220V 50/60Hz
Power Pump	15 BAR
Water Tank	900 ML
Loading Capacity (20'GP)	882 PCS
Loading Capacity (40'GP)	1826 PCS


























Description:	 Rating: 120V/220v, 50Hz/60Hz,1300W. 900ml removable transparent water reservoir. High performance pump with max.15 bar Defond pump. Make the nice Espresso and Cappuccino. Integrated cup warmer on housing top. Thermostatic controlled hot water system (thermoblock) with automatic emptying of remaining water. Cool-touch steam nozzle with frothing function. ON/OFF switch on side panel. Removable drip tray for easy cleaning. Non-slip foot pads. Portafilter polished. Accessory: measuring spoon, single and double cup coffee filter. Product size: 266x205x285mm.
Power	1300 W
Voltage	120V/220V, 50Hz/60Hz
Power Pump	15 BAR
Water Tank	900 ML
Loading Capacity (20'GP)	882 PCS
Loading Capacity (40'GP)	1826 PCS
Loading Capacity (40'HQ)	2114 PCS

























Model:	FCM265A
Description:	Power rating :120V,60Hz,1250W Material : S.S. front panel &drip tray cover; AS milk tank & water tank; ABS water tank lid & drip tray;PP plastic of main body frame & base & top lid & water tank lid; 19 bar Defond pump, thermo block heating element with S.S. water pipe heating system, PCB electronic controller to ensure more accurate beverage temperature. One button operation for single cup espresso, double cup espresso, cappuccino, latte, milk foam, self cleaning, every button with illumination light. With detachable milk frothing device and transparent milk tank for easy cleaning and store, special design for direct using milk box. 1.4L detachable & transparent water tank, 390ml milk tank. Rolling-over drip tray cover for espresso coffee cup, removable drip tray with S.S. cover for easy clean up. With overheating and over-pressure
Power	1250 W
Voltage	120V/60Hz
Power Pump	19 BAR
Water Tank	1.4 L
Loading Capacity (20'GP)	882 PCS
Loading Capacity (40'GP)	1706 PCS
Loading Capacity (40'HQ)	1876 PCS
























Model:	FCM265C
Description:	 Power rating: 220~240V, 50~60Hz, 1240~1450W; Measurement: L265*W220*H326mm Water capacity: 1.4L; removable transparent water tank, with filter and handle, easy to operate and clean. Milk box capacity: 390ML 19 bar Defond pump, thermo block heating element with S.S. Water pipe heating system, PCB electronic controller to ensure more accurate beverage temperature. Three interchangeable stainless steel strainer can be used to brew single cup (7g); double cups (14g) One button operation three kinds of beverages (Espresso/Cappuccino/ Latte) Espresso: 40ML (single cup)/80ML (double cup) Control panel with stainless steel panels embedded silicone keypad. Automatic boil-dry protection, auto shutoff after 30 minutes standby, conserve energy. Removable milk emulsifier, can adjust the size of milk foam, easy to operate
Power	1240~1450 W
Voltage	220~240V, 50Hz~60Hz
Power Pump	19 BAR
Water Tank	1.4 L
Loading Capacity (20'GP)	790 PCS
Loading Capacity (40'GP)	1628 PCS
Loading Capacity (40'HQ)	1790 PCS

























Model:	FCM6861
Description:	 220V 850W 15bar high pressure pump. 1.6L detachable transparent water tank. With safety valve can release pressure automatically. Die-casting aluminum alloy boiler. Aluminum alloy filter holder attached with dual-stainless filter to improve coffee quality. Can use for coffee pod or ground coffee. Can make coffee or steam conveniently. Safe and reliable, with overheating and overpressure protechted device. Detachable frothing nazzle and drip tray for easy cleaning. Durable stainless cup plate for coffee cups preheating. With pressure meter on front body to show the display.
Power	850 W
Voltage	220V
Power Pump	15 BAR
Water Tank	1.6 L
Loading Capacity (20'GP)	1062 PCS













Model:	FCM3007D	FCM3007G
Description:	 Thermoblock for mai Set the boiler tempe Professional s.s port With a timer, can see With indication light Pre-infusion system S.S steam nozzle fo Removable drip tray FCM3007-G: 	ing; bar pressure; er reservoir; .S. boiler to make coffee temperature more stable; king steam drier; rature from 85-102; a filter holder with 58mm diameter S.S. filter; e the brewing time when machine heating to ensure perfect extraction and crema;
Power Consumption	1500W / 1850W	
Voltage	220-2240V/50Hz	
N.W/G.W	8.8Kg/PCS; 10Kg/C	TN
Unit Size/CTN Size	310*220*370 / 380*2	280*430 mm
Package	1PCS/CTN	
Loading Capacity (20'GP/40'GP/40'HQ)	600PCS / 1230PCS	/ 1474 PCS













BEST MATERIAL



RELIABLE GUARANTEED

HOME MACHINE SERIES





















Model:	FCM3005E	FCM3005H
Description:	healthier; Professional s.s.porta-fill Pre-infusion system to e S.s. steam nozzle for cal Removable drip tray & to FCM3005H:	servoir; eating tube to prevent aluminum oxidizing and ter holder and filter with 58mm diameter; nsure perfect extraction and crema; ppuccino or latte;
Power Consumption	1450W	
Voltage	220-2240V/50Hz/60Hz	
N.W/G.W	6.8Kg/PCS; 8.3Kg/CTN	
Unit Size/CTN Size	290*255*325 / 370*300*3	390 mm
Package	1PCS/CTN	
Loading Capacity	670PCS / 1384PCS / 155	57PCS



(20'GP/40'GP/40'HQ)











BEST MATERIAL



RELIABLE GUARANTEED



















healthier; Professional S.S. porta-filter With a barometer, can know the pressure when making coffee; Electronic switch, microcomputer temperature control; Brewing time can be adjustable; S.S steaming nozzle for cappuccino or latte;	Model:	FCM3603
	Description:	 Plastic housing with brushed S.S decorative panel; Italian pump with 15bar pressure; 1.7L removable water tank; Thermoblock with S.S heating tube to prevent aluminum oxidizing an healthier; Professional S.S. porta-filter With a barometer, can know the pressure when making coffee; Electronic switch, microcomputer temperature control; Brewing time can be adjustable; S.S steaming nozzle for cappuccino or latte; Removable drip tray & warm cup function; Option: top cover with detachable S/S. decoration for warming cup; S.S porta filter holder;

Power Consumption	150000 / 185000	
Voltage	220-2240V/50Hz	
N.W/G.W	8.8Kg/PCS; 10Kg/CTN	
Unit Size/CTN Size	310*220*370 / 380*280*430 mm	
Package	1PCS/CTN	
Loading Capacity (20'GP/40'HQ)	600PCS / 1230PCS / 1474 PCS	















RELIABLE GUARANTEED

HOME MACHINE SERIES



















Model:	FCM3016
Description:	 Elegant and retro design; Italian pump with 15 bar pressure; Adjustable steam knob; Three classical buttons with 3 indicators; Power ON/OFF function; Espresso brewing function; Detachable water tank 1.0L; With milk frothing nozzle; With detachable drip tray; Including measuring spoon and tamper.

Power Consumption	1100W
Voltage	220-240V/50Hz
N.W/G.W	6.8Kg/PCS; 8.3Kg/CTN
Unit Size/CTN Size	
Package	
Loading Capacity	



(20'GP/40'GP/40'HQ)













RELIABLE GUARANTEED



















Model:	FCM1016
Description:	 Elegant design with plastic housing; Dual functions: both for tea and coffee; Electronic panel operation & keeping warm function; 1.8L removable water reservoir; With water level detection switch, water shortage prompt; Multiple electrical and mechanical safety protection; With automatic pumping water function, can connect bottled water to fill water; Transparent glass cup & s.s. filter;
Power Consumption	1000W
Voltage	220-240V
Frequency	50Hz
N.W	7.2KG/PCS
G.W	11.5KG/CTN
Unit Size	275*140*340mm
G.B Size	325*185*395mm
CTN Size	570*340*410mm
Package	3PCS/CTN
Loading Capacity(20'GP)	990PCS
Loading Capacity(40'GP)	2040PCS
Loading Capacity(40'HQ)	2448PCS









TEA AND COFFEE MAKER SERIES





















Model:	FCM4106
Description:	Plastic housing & Stainless steel decorative sheet Rotary brewing head for making coffee; Electronic panel operation & keeping warm function; 1.8L removable water reservoir; With water level detection switch, water shortage prompt; Multiple electrical and mechanical safety protection; With automatic pumping water function, can connect bottled water to fill water; Transparent glass cup & s.s. filter.
Power Consumption	1000W / 2000W
Voltage	120V / 220V
Frequency	60Hz
N.W	3.1KG/PCS
G.W	7KG/CTN
Unit Size	360*190*330mm
G.B Size	325*185*395mm
CTN Size	475*415*394mm
Package	2PCS/CTN
Loading Capacity(20'GP)	640PCS
Loading Capacity(20'GP) Loading Capacity(40'GP)	640PCS 1360PCS











TEA AND COFFEE MAKER SERIES

Modern, stylish, compact: style stands out at first glance.
The entire loose-leaf tea experience, recreated and automated.
Tea-square, professional craft tea & coffee brewer.





MANUAL CONTROL



POWER CONTROL



COFFEE HEATING TUBE



TEMPERATURE CONTROL



TEACUP



HEATING ASSEMBLY



COFFEE



TEA AND COFFEE MAKER SERIES















Model:	FCM1018
Description:	 One-touch start/off switch; Dual functions: both for tea and coffee; Water temperature: 98 degree; Water tank capacity: 800ml; Tea cup capacity: 600ml; Lack cup warning function: there is a sensor on the bottom of machine, it will no work when out of cup; Four settings for boiled time for different kinds tea: refresh tea, light tea, mediu tea and strong tea; Removable glass and s.s.tea barket, easy for cleaning; With a high temperature resistant glass cup.
Power Consumption	1000W
Voltage	220-240V
Frequency	50Hz
N.W	7.2KG/PCS
G.W	11.5KG/CTN
Unit Size	275*140*340mm
G.B Size	325*185*395mm
CTN Size	570*340*410mm
Package	3PCS/CTN
Loading Capacity(20'GP)	1000PCS
Loading Capacity(40'GP)	2040PCS









TEAAND COFFEE MAKER SERIES | ferralli ferra | Coffee espresso machine



















Model:

FCM1019

Description:

- · Plastic housing;
- · Rotary brewing head for making coffee;
- · Electronic panel with four mode: hot water, keeping warm;
- · 2 cups / 4cups function;
- · Brewing procedure can be setting according to different request;
- 1.8L removable water tank;
- · with water level detection switch, water shortage warning;
- · With fuse and dry boil protection device;
- · Multiple electrical and mechanical safety protection;
- · Transparent glass cup & S/S filter.

HARMAN AND AND AND AND AND AND AND AND AND A	
Power	Consumption
LOWEI	Consumption

1600 W Voltage 220-240V 50 Hz

N.W/G.W

Unit Size/CTN Size

Package

Loading Capacity (20'GP/40'GP/40'HQ)

















RELIABLE GUARANTEED

TEA AND COFFEE MAKER SERIES

















Model:

Description:

- · Plastic housing:
- · Rotary brewing head for making coffee; · Electronic panel with four mode: hot water, keeping warm;
- · 2 cups / 4cups function;
- · Brewing procedure can be setting according to different request;
- · 1.8L removable water tank;
- · with water level detection switch, water shortage warning;
- · With fuse and dry boil protection device;
- · Multiple electrical and mechanical safety protection;
- · Transparent glass cup & S/S filter.

Power Consumption

1250 W / 1800 W Voltage 120V/60Hz; 220-240V/50Hz

N.W/G.W

Unit Size/CTN Size

Package

Loading Capacity (20'GP/40'GP/40'HQ)

















TEAAND COFFEE MAKER SERIES | ferralli ferro | Coffee espresso machine





















Model:	FCM4106B
Description:	 Plastic housing; Rotary brewing head for making coffee; Electronic panel with four mode: hot water, keeping warm; 2 cups / 4cups function; Brewing procedure can be setting according to different request; 1.8L removable water tank; with water level detection switch, water shortage warning; With fuse and dry boil protection device; Multiple electrical and mechanical safety protection; Transparent glass cup & S/S filter. Option: Ceramic filter & glass cup.

Power Consumption	1250W / 1800W
Voltage	120V/60Hz; 220-240V/50Hz
N.W/G.W	3.6 Kg/PCS; 5.2Kg/PCS
Unit Size/CTN Size	340*150*358mm / 403*230*435mm
Package	1PCS/CTN
Loading Capacity (20'GP/40'GP/40'HQ)	679PCS/1386PCS/1660PCS

































Model:	FCM1701
Description:	 Touch button and digital display; Accurately control the water temperature by NTC; Automatic detection of empty cup; Automatic water outlet function; Accurately control the water amount by electronic scale; Triple safety protection (water shortage protection, dry burning protection and abnormal using protection); Stainless steel heating plate and high borosilicate glass water tank for high temperature resistance;

Power Consumption	800W	
Voltage	220V/50Hz	
N.W/G.W		
Jug Max Capacity	800 ML	
Unit Size/CTN Size	200*142*329 mm	
Package		
Loading Capacity		
(20'GP/40'GP/40'HQ)		























K-CUP COFFEE MAKER SERIES

The simplicity of its design shows sleek finishes and stylish details, available for various k-cup capsules, designed to make a one-off piece for its style, compactness and features. A real pleasure.





KEY CONTROL



POWER CONTROL



COFFEE HEATING TUBE



TEMPERATURE CONTROL



COFFEE



K-CUP COFFEE MAKER SERIES















Model:	FCM6101A
Description:	 Single cup brewer; With patented capsule system; With elegant design; With s.s.boiler; Adjustment solutions are available for various k-cup capsules; One-button operation, with indicator; Over-heat & over-pressure protection; With device and automatic pressure-releasing protecting device; With removable capsule holder.
Power Consumption	650W
Voltage	AC120V
Frequency	60Hz
N.W	1.45KG/PCS
G.W	9.26KG/CTN
Unit Size	195*123*243mm
G.B Size	205*130*257mm
CTN Size	408*220*529mm
Package	6PCS/CTN
Loading Capacity(20'GP)	3336PCS
Loading Capacity(40'GP)	7008PCS









K-CUP COFFEE MAKER SERIES




















Model:	FCM6601
Description:	With patented capsule system; With three groups for convenient making coffee, can connect to tap water directly; With s.s.boiler; Adjustment solutions are available for various k-cup capsules; One-button operation, with indicator; Over-heat & over-pressure protection; With safe device and automatic pressure-releasing protecting device; With a removable capsule holder.
Power Consumption	2000W
Voltage	AC120V
Frequency	60Hz
N.W	25KG/PCS
G.W	37KG/CTN
Unit Size	616*504*500mm
G.B Size	
CTN Size	702*523*530mm
Package	1PCS/CTN
Loading Capacity(20'GP)	136PCS
Loading Capacity(40'GP)	284PCS
Loading Capacity(40'HQ)	284PCS









K-CUP COFFEE MAKER SERIES













ferratti ferro
Coffee espresso machine

Model:	FCM6107
Description:	 With patented capsule system; With elegant design; With s.s.boiler; Adjustment solutions are available for various k-cup capsules; One-button operation, with indicator; Over-heat & over-pressure protection; With safe device and automatic pressure-releasing protecting device; With a removable capsule holder; 1.7L removable water reservoir.
Power Consumption	600W
Voltage	AC120V
Frequency	60Hz
N.W	1.45KG/PCS
G.W	9.26KG/CTN
Unit Size	195*123*243mm
G.B Size	205*130*257mm
CTN Size	408*220*529mm
Package	6PCS/CTN
Loading Capacity(20'GP)	3336PCS
Loading Capacity(40'GP)	7008PCS
Loading Capacity(40'HQ)	8346PCS











GRIDING AND MILK FROTHING MACHINE **SERIES**

Simple and elegant design, ideal complement to coffee maker or espresso machines. Flat burr coffee grinder, available for various home-use and commercial-use. Large capacity design, adjustable thickness to meet any types of coffee machine.

Power Consumption Voltage	120W 220-240V
Frequency	50/60Hz
	OOFOOTIE











Power Consumption

Voltage

Frequency

600W

220-240V

50/60Hz

MILK FROTHER SERIES

















Model:	FCM8002
Description:	 Compact design, ideal complement for coffee maker; Four settings: milk frothing, heating or both; Latte art function-perfect balance between milk & foam for cappuccino; Soft touch on/off button with automatic shut-off; Dual wall design: s.s.304 inner layer and cold touch plastic housing; Non-stick teflon coating interior for easy cleaning; With detachable base, power cord with 0.7m exposed length.
Power Consumption	600W
Voltage	220V-240V
Frequency	50Hz/60Hz
Milk Frothing/Heating Capacity	160/260ML
Jug Max Capacity	580ML
N.W	0.8KG/PCS
G.W	8.2KG/CTN
Unit Size	174*110*206mm
G.B Size	174*128*200mm
CTN Size	364*272*415mm
Package	8PCS/CTN
Loading Capacity(20'GP)	5120PCS
Loading Capacity(40'GP)	10560PCS
Loading Capacity(40'HQ)	12672PCS









MILK FROTHER SERIES

















Model:	FCM8008
Description:	 Compact design, ideal complement for coffee maker; Soft on/off touch button with automatic shut-off; Triple settings with one button:milk frothing, heating or both; Dual wall design:s.s. 304 inner layer and cold touch plastic housing; With non-stick teflon coating interior for easy cleaning; With 360° detachable base, power cord with 0. 7m exposed length. Push one time, Is for hot frothing, it can make kinds of art latte; (blue indicator always light) Push two times is for heating milk; (blue indicator always light) Push three times is for cold frothing; (blue indicator is flashing)
Power Consumption	600W
Voltage	220V-240V
Frequency	50Hz/60Hz
Milk Frothing/Heating Capacity	160/260ML
Jug Max Capacity	580ML
N.W	0.8KG/PCS
G.W	8KG/CTN
Unit Size	156*112*200mm
G.B Size	160*120*200mm
CTN Size	340*260*420mm
Package	8PCS/CTN
Loading Capacity(20'GP)	6000PCS
Loading Capacity(40'GP)	12200PCS
Loading Capacity(40'HQ)	14300PCS









MILK FROTHER SERIES















Model:	FCM8008A
Description:	 Compact design, ideal complement for coffee maker; Soft on/off touch button with automatic shut-off; Triple settings with one button:milk frothing, heating or both; Dual wall design:s.s. 304 inner layer and cold touch plastic housing; With non-stick teflon coating interior for easy cleaning; With 360° detachable base, power cord with 0.7m exposed length. Push one time, Is for hot frothing, it can make kinds of art latte; (blue indicator always light) Push two times is for heating milk; (blue indicator always light) Push three times is for cold frothing; (blue indicator is flashing)
Power Consumption	600W
Voltage	220V-240V
Frequency	50Hz/60Hz
Milk Frothing/Heating Capacity	160/260ML
Jug Max Capacity	580ML
N.W	0.8KG/PCS
G.W	8KG/CTN
Unit Size	156*112*200mm
G.B Size	160*120*200mm
CTN Size	340*260*420mm
Package	8PCS/CTN
Loading Capacity(20'GP)	6000PCS













Simple and elegant design, ideal complement to coffee maker or espresso machines. Flat burr coffee grinder, available for various home-use and commercial-use. Large capacity design, adjustable thickness to meet any types of coffee machine.





KEY CONTROL



POWER CONTROL



BEAN GRINDING SYSTEM



TIMING



COFFEE POWDER



GRINDING MACHINE SERIES





Model:	FGM9083	
Description:	 8-gear coarse setting as per your requirement; S.s. Flat burr make coffee bean grind easily and fast; Speed: 1400 r/min; With 1200g capacity holder; With control button for the quantitative of powder; Grinding capacity: 10-15kg/hour; Hopper capacity: 1.2kg; Hp: 1/2hp. 	
Power Consumption	360W	
Voltage	220V	
Frequency	50Hz	
Bean hopper capacity	1.2KG	
Color	black or red (original color)	
N.W	14KG	
G.W	14.5KG	



























Model:	FGM9091
Description:	 Dispenser capacity: 250gr. (powder coffee); Dispensing capacity: 5-9.5gr/cup; Grinding stones diameter:64mm; Aluminum body; Specially hardened tooling steel grindstones; Micro adjust high resolution knob for accurate grinding setting; 3 optional mode: continues/single cup/double cup; Grinding capacity: 4-7kg/hour; Heavy duty cast.
Power Consumption	350W
Voltage	2200V
Frequency	50Hz
N.W	10.5KG
G.W	15KG
Grinding capacity	4-7Kg/hour
Bean Hopper capacity	1.2KG
Product size	425*210*330mm
CTN size	400*250*500mm
Package	1PCS/CTN
Loading Capacity(20'GP)	560PCS
Loading Capacity(40'GP)	1164PCS
Loading Capacity(40'HQ)	1455PCS









GRINDING MACHINE SERIES















Model:	FGM9092
Description:	 Grinding stones diameter:58mm; Dispenser capacity: 250gr. (powder coffee); Dispensing capacity: 5-9.5gr/cup; Industrial extruded aluminum body; All Aluminum alloy casted dispenser, right/left hand handle; Specially hardened tooling steel grindstones; Micro adjust high resolution knob for accurate grinding setting; Grinding capacity: 4-7kg/hour.
Power Consumption	350W
Voltage	220V
Frequency	50Hz
N.W	8.87KG
G.W	12KG
Grinding capacity	4-7Kg/hour
Bean Hopper capacity	1.2KG
Product size	450*210*330mm
CTN size	340*250*500mm
Package	1PCS/CTN
Loading Capacity(20'GP)	464PCS
Loading Capacity(40'GP)	968PCS
Loading Capacity(40'HQ)	

























Model:	FGM9008
	 Compact design with touch switch; Bean hopper with 250g capacity; Can adjust the fineness as you required with 8-gear coarse setting; With s.s. flat burr can grind coffee bean more fast and smooth; Removable coffee powder box for easily use.
Description:	
Power Consumption	100W
Voltage	220V
Frequency	50Hz
N.W	14.5KG/PCS
G.W	15.5KG/CTN
Grinding capacity	
Bean Hopper capacity	
Product size	380*180*280mm
CTN size	600*380*270mm
Package	4PCS/CTN
Loading Capacity(20'GP)	1824PCS
Loading Capacity(40'GP)	3648PCS
Loading Capacity(40'HQ)	4104PCS









GRINDING MACHINE SERIES

















Model:	FGM9053
Description:	 Transparent beans coffee cover; Stainless-steel blades ensure uniform grinding; Compact with touch switch; High speed grinds; Safty lock system; Grinds up to 30g of coffee beans at a time; Can easily use for spices, nuts and grains; Recessed cord storage in the base of grinder.
Power Consumption	130W
Voltage	220V
Frequency	50Hz
N.W	0.6KG/PCS
G.W	8.5KG/CTN
Grinding capacity	
Unit Size	105*102*181mm
G.B Size	110*110*193mm
CTN size	345*235*410mm
Package	12PCS/CTN
Loading Capacity(20'GP)	9780PCS
Loading Capacity(40'GP)	20340PCS
Loading Capacity(40'HQ)	22536PCS





















Model:	FGM9015A
Description:	 Full stainless steel housing; Electronic control and time setting for single cup/double cup / manual function; Easy to operate and convenient use; Adjustable roughness of 1-8 gear grinding for different kinds of coffee; Fast grinding speed with dia.60mm S.S flat burr and smooth Bean hopper with 250g capacity; With porta-filter holder;
Power Consumption	250W
Voltage	220V/50Hz
N.W/G.W	5.18kG / 6.08KG
Unit Size/CTN Size	212*175*361mm / 297*237*450 mm
Package	1PCS/CTN
Loading Capacity (20'GP/40'GP/40'HQ)	684PCS/1376PCS/1676PCS















GRINDING MACHINE SERIES















Model:	FGM9009
Description:	 Compact design with ABS housing; Easy to operate and convenient use; Adjustable roughness of 1-8 gear grinding for different kinds of coffee; Fast grinding speed with dia.60mm S.S flat burr and smooth; Bean hopper with 120g capacity;
Power Consumption	180W
Voltage	220V/50Hz
N.W/G.W	2.7KG/PCS;3.1KG/CTN
Unit Size/CTN Size	218*122*312mm / 630*370*268mm
Package	4PCS/CTN
Loading Capacity (20'GP/40'GP/40'HQ)	1800PCS/3708PCS/4152PCS















RELIABLE GUARANTEED















Model:	FGM90112	FGM90112A
Description:	 64mm Italian stainless steel blade Strong hardness grinding discs. Accurate grinding and durable. Strong and low speed induction motors 	

- Adjustable roughness of 1-8 gear grinding for different kinds of coffee.
 Bean hopper capacity: 1.2L
- FGM9012A
 Low-speed DC motor
- LCD display
- · Inching button for powder output, manual control the amount flexibly

Power Consumption	360W	365W
Voltage	220V/50Hz	220V/50Hz
N.W/G.W		9.17KG/12.2KG
Unit Size/CTN Size	569*220*360 mm	316*288*678 mm
Package	1PCS/CTN	1PCS/CTN
Loading Capacity (20'GP/40'HQ)	479PCS/963PCS/1086PCS	479PCS/963PCS/1086PCS













BEST MATERIAL



GRINDING MACHINE SERIES

















Model:	FGM9016
Description:	 64mm stainless steel grinding disc; Strong hardness grinding disc and is not easy to wear; Accurate grinding, sturdiness and durability, ensuring uniform thickness; Tough low-speed induction motor; LCD screen display; Manual inching model, can control the amount of powder; Transparent bean hopper with 280g capacity; Adjustable roughness of 1-11 gear grinding ofr different kinds of coffee;

Electric power:	250W
Voltage/Hz:	220V50Hz
Grinding discs diameter:	64mm
Bean hopper capacity:	1.65kg
Unit size:	327*237*482mm
N.W./G.W:	8.6kg/11.2kg
Loading Capacity (20GP/40G	P/40HQ)















BEST MATERIAL



RELIABLE GUARANTEED

STEAM MAKER













Model:	FCM1206
Description:	 Multi-purpose: can make Cappuccino/Latte and different kinds of hot drink; Easy for operation with touch button and light indicator; Professional rotary steam nozzle; Italian ULKA pump 15 bar; Dual thermoblocks heating stystem with stronger steam and more efficiency. With double thermostats for temperature control protection; Automatic pressure release and keep safety; With detachable water tank and drip tray; With temperature sensor, can set the temperature and stop automatically; Cup warmer function.

Power Consumption	1650W
Voltage	220V/50Hz
N.W/G.W	7.2KG/PCS; 8.7 KG/PCS
Unit Size/CTN Size	310*220*381 mm / 380*280*430 mm
Package	1PCS/CTN
Loading Capacity (20'GP/40'GP/40'HQ)	600PCS/1230PCS/1474PCS

















STEAM MAKER

















Power Consumption	1650W
Voltage/Hz	220V/50Hz
N.W/G.W	6.8KG/PCS; 7.8KG/CTN
Unit Size/CTN Size	301*232*394mm / 288*288*502mm
Package	1PCS/CTN
Loading Capacity	613PCS/1291PCS/1463PCS
(20GP/40GP/40HQ)	



















STEAM MAKER











NEW



Model:	FCM1208
Description:	 Stainless steel housing; With 5.25L stainless steel boiler; With self-priming pump (self-priming height 2M); With steam pressure showing; Electronic timing hot water function and automatic constant temperature steam function (adjustable fixed temperature); External water source; Automatic pressure release and keep safety; With water drainage function; With detachable drip try; Cup warmer function; With leakage of electricity protection switch.
Power Consumption	2000W
Voltage/Hz	220V/50Hz
N.W/G.W	
Unit Size/CTN Size	370*260*550 mm / 420*310*590 mm
Package	1PCS/CTN
Loading Capacity	210PCS/420PCS/560PCS



(20GP/40GP/40HQ)







STEAM MAKER

















Model:	FCM1209
Description:	 Stainless steel housing; With 5.25L stainless steel boiler; With self-priming pump (self-priming height 2M); Knob type manual hot water and knob type manual steam function; External water source; Automatic pressure release and keep safety; With water drainage function; With detachable drip try; Cup warmer function; With leakage of electricity protection switch.

Power Consumption	2000W
Voltage/Hz	220V/50Hz
N.W/G.W	
Unit Size/CTN Size	370*260*550 mm / 420*310*590 mm
Package	1PCS/CTN
Loading Capacity	210PCS/420PCS/560PCS
(20GP/40GP/40HQ)	

















STEAM MAKER













Description

- · Stainless steel housing;
- · 2.5Bar steam pressure;
- · 5.25L S.S boiler to ensure temperature more stable;
- · Professional rotary steam nozzle;
- · Independent system can make steam and hot water at the same time;
- · Can connect tap water and bottled water to fill water;
- · Over-heat & over-pressure protection;
- · With safe device and automatic pressure-releasing protect device;

Power Consumption	2000W
Voltage/Hz	220V/50Hz
N.W/G.W	15KG/PCS;17.5KG/CTN
Unit Size/CTN Size	420*295*520mm / 492*377*582 mm
Package	1PCS/CTN
Loading Capacity (20GP/40GP/40HQ)	240PCS/502PCS/590PCS















GUARANTEED









P0101 SINGLE PORTA FILTER HOLDER



P0450 CRM2008 CARAFE



CRM3963

1000ML
LATTE ART CUP



P0312/P0310 STAINLESS STEEL TAMPER



P0511
TAMPER BASE



P0100

DOUBLE PORTA
FILTER HOLDER



P0201/P0200
58MM SINGLE&
DOUBLE PORTA FILTER

P0400

LATTE ART CUP

P0301/P0311

PLASTIC TAMPER

600ML





P0103

CRM2008 PORTA

FILTER HOLDER



P0501 SMALL SIZE SLAT POT



1000G COFFEE BEAN JAR



P0300 COFFEE SPOON



BIG SIZE SLAT POT



500G COFFEE BEAN JAR



(INDOTARA)®

PT. INDOTARA PERSADA

Our Marketing Office and After Sales Service Center

Head Office

50/F, Menara BCA Grand Indonesia Jl. M.H. Thamrin No.1 Jakarta Pusat 10310



horeca@indotara.id



Surabaya Office

Bumi Mandiri Tower I Lt. 10 Suite 1008 Jl. Jend. Basuki Rachmat 129-137 Surabaya 60271

031 - 3313 3333

sby.horeca@indotara.id 😰



Makassar Office

Fajar Graha Pena Lt. 5 Jl. Urip Sumoharjo No. 20, Makassar - South Sulawesi 90234

021 - 5011 2223

mks.horeca@indotara.id



Marketing Office

Graha Kencana Building, Lt.10 Suite 10F Jl. Raya Perjuangan No. 88, Kebon Jeruk - Jakarta Barat 11530

021 - 5011 2223 🖀

horeca@indotara.id



Hartono Mall Yogyakarta Lt. 3 Kaliwaru, Condongcatur, Sleman, Yogyakarta 55281

021 - 5011 2223

yog.horeca@indotara.id



Balikpapan Office

Panin Tower Lt. 8 - Grand Sudirman Jl. Jendral Sudirman No.7 Klandasan Ilir, Balikpapan Kota, Kalimantan Timur 76114

021 - 5011 2223

bpp.horeca@indotara.id



Graha Indotara

Millenium Industrial Estate Jl. Millenium 22 Blok R3 No. 1 Cikupa, Tangerang - Banten 15720

021 - 5011 2223 🖀

horeca@indotara.id

Semarang Office Wisma HSBC Lt. 6 Suite 609

Jl. Gajah Mada No.135 Semarang, Jawa Tengah 50134

024 - 40 33 88 99

smg.horeca@indotara.id



Bali Office

Benoa Square Lt. 2 Jl. Bypass Ngurah Rai No. 21 A Kedonganan, Kuta Badung - Bali Indonesia 80361

021 - 5011 2223



bali.horeca@indotara.id

Bandung Office

Wisma HSBC Lt. 6 Suite B Jl. Asia Afrika No. 116 Bandung, Jawa Barat 40112

021 - 5011 2223 🕿

bdg.horeca@indotara.id



Medan Office

Sutomo Tower Lantai 5H Jl. Sutomo Ujung No.28, Kota Medan, Sumatera Utara 20235

061 - 50 300 600 @

mdn.horeca@indotara.id



MBFC Tower 3 17F, 12 Marina Boulevard Singapore - 018982

021 - 5011 2223

sing.horeca@indotara.id



Singapore Office



